View NSN Online: https://aerobasegroup.kr/nsn/6525-01-076-8677

EASTMAN KODAK COMPANY -- 180 5134 RP X-OMAT FIXER & REPLENISHER, PART A - 6525-01-076-8677

Product ID:180 5134 RP X-OMAT FIXER & REPLENISHER, PART A MSDS Date:08/02/1995 FSC:6525 NIIN:01-076-8677 MSDS Number: CDQMW === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716 -477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

======= Composition/Information on

Ingredients =========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 40-45% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE CAS:7783-18-8 RTECS #:XN6465000 Fraction by Wt: 35-40% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM THIOSULFATE CAS:7772-98-7 RTECS #:XN6476000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM BISULFITE (CERCLA) CAS:10192-30-0 RTECS #:WT3595000 Fraction by Wt: 1-5% Other REC Limits:NONE RECO MMENDED EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM ACETATE (CERCLA) CAS:631-61-8 RTECS #:AF3675000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA) CAS:7631-90-5 RTECS #:VZ2000000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL:EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. EYES:NO SPECIFIC HAZARD KNOWN.MAY CAUSE TRANSIENT IRRITATION. SKIN:LOW HAZARD FOR RECOMMENDED HANDLING. INGEST:EXPECTED TO BE LOW INGESTION HAZRD. Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY CLASSIFICATION:IARC/A CGIH/NTP/OSHA:NONE. Effects of Overexposure:TRANSIENT EYE IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:INHAL:IF SYMPTOMATIC MOVE TO FRESH AIR. GET MED ATTN IF SYMPTONS PERSIST. EYES:ANY MATL THAT CONTACTS EYE SHOULD BE WASHED OUT IMMED W/WATER. GET MED ATTN IF SYMPTOMS OCCUR. SKIN:WASH W/SOAP & WATER. GET MED ATTN IF SYMPTOMS OCCUR. INGEST:DRINK 1-2 GLASSES OF WATE

R. SEEK MED ATTN.

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NP

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:DRIED PRODUCT RESIDUE CAN ACT AS A REDUCING AGENT.

==========

Spill Release Procedures: FLUSH TO SEWER W/LG AMTS OF WATER. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: USE W/ADEQUATE VENTI.KEEP FROM CONTACT W/OXIDIZING MATLS.KEEP CNTNR TIGHTLY CLOSED.KEEP AWAY FROM INCOMPATIBLE SUBSTANCES.

Other Precautions: PROPERTIES: MOD BIOCHEM OXY DEMAND, MAY CAUSE OXY DEPLETION IN AQU SYS.LOW POT

TO AFFECT AQU ORGANISMS/2ND WASTE TREATMENT MICROBIAL METABOLISM/GERM &/OR EARLY GROWTH OF SOME PLANTS/PERSIST IN ENVIRO/BI OCONCEN.AFT DILUTION W/LG AMTS OF (SUPP)

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE SHOULD BE NEEDED. Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves:IMPERVIOUS GLOVES. Eye Protection:SAFETY GLASSES W/ SIDE SHIELDS, GOGGLES. Other Protective Equipment:EYEBATH, WASHING FACILITIES, SAFETY SHOWER. Work Hygienic Practices:WASH THOROUGHLY AFT HNDLG.GOOD INDUSTRIAL HYG PRAC TO MIN EYE/SKIN CONTACT. Supplemental Safety and Health OTHER PRECAUT:WATER/2ND WASTE TREAT MATL NOT EXPECTED TO CAUSE ADVERSE ENVIRO EFFECTS. TO MAKE 200 GALLONS.

HCC:N1 Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decom p Text:NP Vapor Pres:18 @20C Vapor Density:0.6 Spec Gravity:1.361 pH:4.1 Viscosity:NP Evaporation Rate & amp; Reference:NP Solubility in Water:COMPLETE. Appearance and Odor:LIQUID, COLORLESS, SLIGHT AMMONIA ODOR. Percent Volatiles by Volume:45 Corrosion Rate:NP

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS, BAES, SODIUM HYPOCHLORITE (BLEACH).CONTACT W/BASE LIBERATES FLAMMABLE MATL. Stabili

ty Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:AMMONIA, CHLORAMINE. HAZ COMBUST PROD:CO2,CO,OXIDES OF NITROGEN,OXIDES OF SULFUR.

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO NATIONAL/STATE/LOCAL LAWS. FLUSH TO SEWER W/LG AMTS OF WATER. CHEM(S) SUBJ TO REPORTING REQMTS OF SEC 313 TITLE III SARA/40CFR372:NONE.

Disclaimer (provided with this inform

ation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.