

DOW CORNING CORPORATION -- OS-120 -- 6850-01-435-5655

=====
Product Identification
=====

Product ID:OS-120
MSDS Date:10/18/1996
FSC:6850
NIIN:01-435-5655
MSDS Number: CDQQQ
=== Responsible Party ===
Company Name:DOW CORNING CORPORATION
Address:3901 S SAGINAW RD
Box:997
City:MIDLAND
State:MI
ZIP:48640
Country:US
Info Phone Num:517-496-6000/8577 (TRANSPORT)
Emergency Phone Num:517-496-5900/800-424-9
300(CHEMTREC)
CAGE:5D028
=== Contractor Identification ===
Company Name:DOW CORNING CORP
Address:3901 S SAGINAW RD
Box:997
City:MIDLAND
State:MI
ZIP:48686-0997
Country:US
Phone:517-496-6000/517-496-6315
CAGE:5D028

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXAMETHYLDISILOXANE
CAS:107-46-0
RTECS #:JM9237000
Fraction by Wt: 89%
Other REC Limits:TWA 200 PPM (MFR)

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 11

%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9596

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY &
GI TRACTS. ACUTE- EYE:MAY CAUSE DISCOMFORT. SKIN:REPEATED/PROLONGED
CONTACT MAY CAUSE DEFATTING. INHALE:MAY
CAUSE DROWSINESS.

ORAL:SMALL AMOUNTS TRANSFERRED TO MOUTH BY FINGERS SHOULD NOT
INJURE. SWALLOWING LARGE AMOUNTS MAY INJURE SLIGHTLY & CAUSE
DROWSINESS. CHRONIC- DERMATITIS.

Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, NAUSEA, SKIN DRYNESS,
TEARING, BLURRED VISION, ITCHING, DERMATITIS, DISCOMFORT
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH
AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH
WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP &
WATER. ORAL: SEEK MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:CC
Flash Point:=-4.C, 24.8F
Autoignition Temp:=-365.C
, 689.F
Lower Limits:1.3%
Upper Limits:18.6%
Extinguishing Media:USE DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL
FOAM/WATER FOG FOR SMALL FIRE. USE ALCOHOL FOAM, WATER SPRAY FOR
LARGE FIRE.
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS
WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL
CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.
CONTAIN

ERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND OR VERMICULITE. TRANSFER TO DISPOSAL DRUMS USING NON-SPARKING TOOLS. PREVENT LIQUID FROM ENTERING SEWERS OR WATERWAYS.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA, AWAY FROM HEAT, FLAMES, SPARKS, HOT SURFACES AND STRONG OXIDIZING AGENTS. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. KEEP OUT OF REACH OF CHILDREN. DO NOT INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHEN ADEQUATE VENTILATION CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGH, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR.

Ventilation:USE EXPLOSION-PROOF VENTILATION EQUIPMENT TO CONTROL VAPOR CONCENTRATIONS.

Protective Gloves:NITRILE FOR REPEATED/PROLONGED CONTACT

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE LOCATED NEARBY. WEAR APPROPRIATE PROTECTIVE CLOTHING FOR RISK OF EXPOSURE.

Work Hygiene

Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

NRC/State Lic Num:NOT RELEVANT

Vapor Pres:44.6 @ 77F

Vapor Density:>1

Spec Gravity:0.77

Viscosity:0.64 CST

Appearance and Odor:COLORLESS LIQUID; ETHER-LIKE ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:

YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, FLAMES, SPARKS, HOT SURFACES, OTHER
IGNITION SOURCES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
SILICONE DIOXIDE AND FORMALDEHYDE MAY BE FORMED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN AN APPROVED INCINERATOR OR
CONTRACT WITH LICENSED CHEMICAL WASTE DISPOSAL SERVICE. DISCHARGE,
TREATMENT OR DISPOSAL IS SUBJECT T
O FEDERAL, STATE OR LOCAL LAWS.
EPA D001 (IGNITABLE). FOR MORE INFORMATION, CALL DOW AT
517-496-6315.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional
advice to verify and
assume responsibility for the suitability of this information to their
particular situation.