View NSN Online: https://aerobasegroup.kr/nsn/3439-00-205-1003

ARCOS ALLOYS DIV HOSKINS MFG CO -- BARE-WIRE FILLER METALS, 813 -- 3439-00-205-1003

Product ID:BARE-WIRE FILLER METALS, 813 MSDS Date:05/01/1994 FSC:3439 NIIN:00-205-1003 MSDS Number: CDVGF === Responsible Party === Company Name: ARCOS ALLOYS DIV HOSKINS MFG CO Address:1 ARCOS DR **City:MT CARMEL** State:PA ZIP:17851 Country:US Info Phone Num:717-339-5200 **Emergency Ph** one Num:800-424-9300(CHEMTREC) CAGE:03805 === Contractor Identification === Company Name: ARCOS ALLOYS DIV OF HOSKINS MFG CO Address:#1 ARCOS DRIVE Box:308 City:MTCARMEL State:PA ZIP:17851 Country:US Phone:717-339-5200, CHEMTREC 800-424-9300 CAGE:03805 Company Name: ARCOS ALLOYS DIVISION OF HOSKINS MFG. CO. Address:#1 ARCOS DRIVE Box:City:MT CARMEL State:PA ZIP:17851 Country:US Phone:570-339-5200; 717-339-5200 CAGE:19270

Ingred

Name: IRON; (FE) CAS:7439-89-6 RTECS #:NO4565500 Fraction by Wt: 1% OSHA PEL:N/K ACGIH TLV:N/K Ingred Name: CHROMIUM; (CR) (SARA 313) (CERCLA) CAS:7440-47-3 RTECS #:GB4200000 Fraction by Wt: 0.01% OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:COPPER; (CU) (SARA 313) (CERCLA) CAS:7440-50-8 RTECS #:GL5325000 Fraction by Wt: 70.5% OSHA PEL:0.1MG/M3 FUME;1 DUST ACGIH TLV:0.2 MG/M3 FUME EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:NICKEL; (NI) (SARA 3 13) (CERCLA) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 32% OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3

Ingred Name:EFTS OF OVEREXP:CHRONIC:EXPOS MAY RSLT IN NEUROLOGICAL DMG, LUNG FIBROSIS, PNEUMOCONIOSIS & OTHER LUNG DISEASES. (ING 6) RTECS #:9999999ZZ

Ingred Name:ING 5:CHROMIUM IS CONSIDERED POSS CARCIN UNDER OSHA (29 CF4 1910.1200) (MFR). STUDIES FORMING BASIS FOR THIS (ING 7) RTECS #:99999992Z

Ingred Name: ING 6: CLASSIFICATION WERE FROM OPERATIONS OTHER THAN WELDING OF CHROMIUM. T

HERE IS CONSIDERABLE CONTROVERSY ON (ING 8) RTECS #:99999992Z

Ingred Name:ING 7:EXTENT OF RESP CANCER PROBS DUE TO CHROMIUM. NEVERTHELESS EXPOS MUST BE MAINTAINED BELOW LEVELS SPECIFIED. RTECS #:9999999ZZ

Ingred Name:OTHER PROT EQUIP:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS.

RTECS #:9999999ZZ

Ingred Name:HAZ DECOMP PROD:BEING WELDED, PROCS, PROCESSES & TYPE OF WIRE/ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THE(ING 11) RTECS #:9999999ZZ

Ingred Name:ING 10:PRESENCE OF CONTA MS IN ATM. DECOMP PRODS FROM WELDING/CUTTING OPERATION INCL THOSE FROM VOLATILIZATION, (ING 12) RTECS #:9999999ZZ

Ingred Name:ING 11:RXN &/OR OXIDATION OF INGS & MAY INCL OXIDES OF METALS, CHROMATES & COMPLEX METALLICS. GASEOUS RXN PRODS (ING 13) RTECS #:9999999ZZ

Ingred Name:ING 12:MAY INCL CARBON MONOXIDE, OZONE & NITROGEN OXIDES. CHLORINATED SOLVS MAY BE DECOMPOSED INTO TOX GASES (ING 14) RTECS #:9999999ZZ

Ingred Name:ING 13:SUCH AS PHOSGENE. WHEN ELECTRODES ARE CONSUMED, FUME & GAS DECOMP PRODS GENERATED ARE DIFF IN FORM FROM (ING 15) RTECS #:9999999ZZ

Ingred Name:ING 14:INGS LISTED. NEW CMPDS NOT IN ELECTRODES MAY FORM. KNOWN GASES & FUMES THAT MAY FORM DURING WELDING/HOT (ING 16) RTECS #:9999999ZZ

Ingred Name:ING 15:CUTTING & THEIR EXPOS LIMS ARE:ALUMINUM FUMES, CARBON MONOXIDE, CHROMIUM, CHROMIUM (CHROMATES), COBALT (ING 17) RTECS #:9999999ZZ

Ingred Name:ING 16:FUME(CO), COPPER FUME(CU), IRON OXIDE FUME(FE), MANGANESE FUME(MN), MOLYBDENUM(MO) (S OLUBLE), NICKEL(NI) (ING 18) RTECS #:9999999ZZ

Ingred Name:ING 17:(SOLUBLE), TUNGSTEN(W) (SOLUBLE), NITROGEN DIOXIDE, OZONE & PHOSGENE. RTECS #:9999999ZZ

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic: THIS PROD POSES NO HLTH HAZ AS SHIPPED BUT MAY POSE HLTH HAZ DURING U SE. ELEC ARC WELDING RAGS CAN INJURE EYES & BURN SKIN. DUST, FUMES & GASES CAN BE DANGEROUS TO YOUR TEETH. LUNG DMG MAY RSLT FROM O VEREXP. ACUTE: SHORT TERM EXPOS TO WELDING FUMES, GASES/DUST MAY RSLT IN DISCOMFORT SUCH AS DIZZ, NAUS, (EFTS OF OVEREXP) Explanation of Carcinogenicity:NICKEL:IARC MONOGRAPHS ON EVAL OF CARCIN RISK OF CHEMS TO MAN, VOL 49, PG 257, 1990:GRP 2B. NTP 7TH ANNUAL RPT (SUPDAT) Effects of Overexposure: HLTH HAZ: FEVER, DRYNESS &/OR IRRIT OF NOSE, THROAT & EYES. SKIN SENSITIVITY MAY ALSO BE NOTED. ACUTE EXPOS CAN RSLT IN SAME SYMPS EXCEPT TO GREATER DEGREE AS WELL AS WATERY EYES. HDCH, BRTHG DFCLTY, F REQUENT COUGH &/OR CHEST PAINS. SOME TOX GASES MAY CAUSE PULM EDEMA, ASPHY & EXCESSIVE EXPOS CAN BE FATAL. (ING 5) Medical Cond Aggravated by Exposure:SOME WORKERS MAY EXPERIENCE DISCOMFORT AT CONCS BELOW THE TLVS & OTHER MAY BE AFFECTED BY A PRE-EXISTING CONDITION OR OTHER OCCUP ILLNESS BECAUSE OF WIDE VARIATION

IN INDIVIDUAL SUSCEPTIBILITIES.

First Aid:IN CASE OF ELEC SHOCK, TURN OFF POWER PRIOR TO REMOVAL FROM EXPOS AREA & ADMIN OF FIRST AID. INHAL:REMOVE TO FRESH AIR. IF BRTHG IS DFCLT ADMIN OXYG. IF NOT BRTHG BEGIN ARTF RESP. IF NO DETECTABLE PUL SE BEGIN EXTERNAL HEART MASSAGE. SKIN:WASH AFFECTED AREA W/SOAP & WATER. EYES:FLUSH W/LG AMTS OF FRESH WATER FOR AT LST 15 MINS. INGEST:SEEK MED ATTN. IN ALL CASES, S Flash Point:NONFLAMMABLE Extinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE . Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:NONFLAMMABLE; HOWEVER, ARCS, SPARKS & MOLTEN METAL CAN IGNITE FLAMMABLES & COMBUSTIBLES OR CAUSE EXPLOSIONS. Spill Release Procedures: CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES & PLACE IN SUITABLE DEPARTMENT OF TRANSPORTATION (DOT) APPROVED CONTAINERS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: AVOID INHALATION & SKIN EXPOSURE. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING. Other Precautions: NONE SPECIFIED BY MANUFACTURER. ========= Exposure Controls/Personal Protection == Respiratory Protection: USE NIOSH APPRVD WELD FUME RESP OR AIR SUPPLIED RESP WHEN CUTTING, GRINDING/WELDING IN CONFINED SPACE/WHERE LOC EXHST/GEN VENT DOES NOT KEEP EXPOS BELOW REC LIMS. MONITOR AIR QUALITY INSIDE WELDER'S H ELMET, IF WORN, &/OR WORKER'S (SUPDAT) Ventilation: USE ENOUGH VENT WHEN CUTTING, GRINDING/WELDING TO KEEP DUST, FUMES & GASES FROM WORKERS BRTHG ZONE & GEN AREA. (SUPDAT) Protective Gloves: IMPERVIOUS GLOVES. Eye Protection: ANSI APPRVD CHEM WORKER S GOGGS & (SUPDAT) Other Protective Equipment: ANSI APPRVD EYE WASH FOUNTAIN & DELUGE SHOWER . WEAR FLAME RETARDANT CLTHG WHEN CUTTING, GRINDING/WELDING. (ING 9) Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health EXPLAN OF CARCIN: ON CARCIN, 1994: ANTIC TO BE CARCIN. ANIMAL: LUNGS, NASAL CAVITIES. RESP PROT: BRTHG ZONE TO DETERM IF RESP IS REQD & TYPE NEEDED. USE ONLY NIOSH APPRVD RESPS. VENT: KEEP EXPOS BELOW LIMS SPECIFIED. EYE PROT: FULL LGTH F

CSHLD ; W/FILTER LENS. SELECT WELDING LENS SHADE FROM AWS PUBLICATION F2.2. HCC:T6 Appearance and Odor: BARE FILLER METALS ARE SOLID WIRE. Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:WELDING & HOT CUTTING FUMES & GASES CANNOT B E CLASSIFIED SIMPLY. THEIR COMPOSITION & QTY ARE DEPENDENT ON METAL (ING 10) Waste Disposal Methods: DISPOSE OF IN FULL COMPLIANCE W/FEDERAL, STATE & LOCAL REGULATIONS. Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this inform ation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.