

NAZDAR COMPANY -- 5500 SERIES FLAT POSTER INK -- 7510-00-460-5887

=====
Product Identification
=====

Product ID:5500 SERIES FLAT POSTER INK

MSDS Date:01/22/1992

FSC:7510

NIIN:00-460-5887

MSDS Number: CDXKC

=== Responsible Party ===

Company Name:NAZDAR COMPANY

Address:1087 N NORTH BRANCH ST

City:CHICAGO

State:IL

ZIP:60622-4234

Country:US

Info Phone Num:312-943-8338/800-424-9300

Emergency Phone Num

:312-943-8338/800-424-9300

CAGE:NAZDA

=== Contractor Identification ===

Company Name:DICK BLICK

Box:UNKNOW

CAGE:9S136

Company Name:NAZDAR COMPANY

Address:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622-4292

Country:US

Phone:312-943-8338;800-736-7636

CAGE:76708

Company Name:NAZDAR COMPANY

Address:1087 N BRANCH ST

City:CHICAGO

State:IL

ZIP:60622

Country:US

Phone:(312)943-8338

CAGE:NAZDA

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA (P

ETROLEUM) MEDIUM ALIPHATIC/ALIPHTIC
HYDROCARBON

CAS:64742-88-7

Fraction by Wt: 31-51%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:LEAD (SARA 313) (CERCLA)/LEAD COMPOUNDS

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 2-17%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE 1910.1025

ACGIH TLV:0.15MG/M3 DUST; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:CHROMIUM (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt:

1-3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:EYE:PRIMARY IRRITATION. SKIN:PRIMARY

IRRITATION. INHALATION:ANESTHETIC. IRRITATION OF RESPIRATORY TRACT

OR CNS DEPRESSION CAUSING HEADACHE, DIZZINESS, STAGGERING,
CONFUSION, UNCONSCIOUSNESS, COMA. ING ESTION:CONTAINS LEAD &
CHROMATES; ADVISE PHYSICIAN. PROLONGED &/OR REPEATED INGESTION MAY
CAUSE DELAYED SYSTEMIC INJURY.

Explanation of Carcinogenicity:CONTAINS LEAD & CHROMIUM COMPOUNDS. SEE
INDIVIDUAL REPORTS FOR DETAILS.

Effects of Overexposure:IRRITATION, TEARING, REDNESS AND STINGING OF
EYES, DRYING OF SKIN, NAUSEA, VOMITING, DIZZINESS, HEADACHE,
DROWSINESS, WEAKNESS

, FATIGUE, BURNS, DERMATITIS
Medical Cond Aggravated by Exposure:N/A.

===== First Aid Measures =====

First Aid:IF IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL ATTENTION.
EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE
CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE. INHALED:REMOVE FROM
EXPOSURE. A ID OR RESTORE BREATHING AS NEEDED. INGESTED:DO NOT
INDUCE VOMITING. GIVE 1-2 GLASSES OF MILK OR WATER TO DRINK. GET
IMMEDIATE ME
DICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105F,41C
Lower Limits:1
Extinguishing Media:USE DRY CHEMICAL, CARBON DIOXIDE, FOAM. IF WATER IS
USED, FOG NOZZLES ARE PREFERRED.
Fire Fighting Procedures:CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO
EXTREME HEAT. COOL FIRE EXPOSED CONTATINERS W/WATER TO PREVENT
PRESSURE BUILD UP & POSSIBLE EXPLOSION.
Unusual Fire/Explosion Hazard:KEEP TIGHTLY CLOSED. ISOLATE FROM
IGNITION SOURCES. DO NOT APPLY TO HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. AVOID BREATHING
VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING
TOOLS.
Neutralizing Agent:MFR GAVE NO INFORMATION OF MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNE
D FOR STORAGE OF NFPA CLASS II
COMBUSTIBLE LIQUIDS.
Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERSS SHOULD BE
GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUIDS IN EXCESS OF A
FEW INCHES. DO NOT FLAME CUT, BRAZE, WELD W/O MSHA OR NIOSH
APPROVED RESPIRATOR OR APPROP RIATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPOR CONCENTRATION EXCEEDS TLV, USE NIOSH
APPROVED RESPIRATORY W/ORGANIC CHEMICAL CARTRIDGE.

CONSULT

REPUTABLE SAFETY SULLLY CO FOR PROPER RESPIRATOR SELECTION.

Ventilation:USE MECHANICAL (GENERAL) VENTILATION OR LOCAL EXHAUST TO

KEEP EXPOSURE 315F,>157C

Vapor Density:>1

Spec Gravity:>1

Evaporation Rate & Reference: