

DAP INC -- DAP 1012 GLAZING -- 8030-00-823-7921

=====  
Product Identification  
=====

Product ID:DAP 1012 GLAZING  
MSDS Date:01/07/1994  
FSC:8030  
NIIN:00-823-7921  
MSDS Number: CDXTS  
=== Responsible Party ===  
Company Name:DAP INC  
Box:277  
City:DAYTON  
State:OH  
ZIP:45401  
Country:US  
Info Phone Num:800-543-3840  
Emergency Phone Num:800-535-5053; 800-543-3840  
CAGE:90300

==== Contractor Identification ===

Compa  
ny Name:DAP INC.  
Box:277  
City:DAYTON  
State:OH  
ZIP:45401-0277  
Country:US  
Phone:513-253-7154/800-543-3840  
CAGE:90300

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:HYDROUS MAGNESIUM SILICATE  
CAS:14807-96-6  
RTECS #:WW2710000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC = 48 G/L  
RTECS #:9999999VO  
Other REC Lim

its:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE EFFECTS: MAY IRRITATE EYES,  
SKIN, NOSE & RESPIRATORY TRACT. HARMFUL IF INHALED. HARMFUL OR  
FATAL IF SWALLOWED. IF INGESTED, THIS PRODUCT MAY CAUSE VOMITING,  
DIARRHEA, & DEPRESSED RESPIRATION. IN HALATION MAY AFFECT THE BRAIN  
OR NERVOUS SYSTEM  
CAUSING DIZZINESS, HEADACHE, NAUSEA.  
Effects of Overexposure:CHRONIC: REPORTS HAVE ASSOCIATED PERMANENT  
BRAIN & NERVOUS SYSTEM DAMAGE WITH PROLONGED AND REPEATED  
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS. PROLONGED OR REPEATED  
CONTACT WITH SKIN MAY CAUSE IRRITATION .

=====  
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15  
MINUTES. CONTACT A PHYSICIAN IMMEDIATELY. SKIN CONTACT: WASH WITH  
SOAP AND WATER.  
INHALATION: REMOVE TO FRESH AIR. CONTACT A  
PHYSICIAN IMMEDIATELY . INGESTION: DO NOT INDUCE VOMITING. CALL DR.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC  
Flash Point:194F,90C  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS  
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING SCBA, IS  
RECOMMENDED TO PROTECT FROM COMBUSTION PRODUCTS. COOL EXPOSED  
CONTAINERS WITH WATER  
Unusual Fire/Explosion Hazard:CONTAINER MAY EXPLODE  
W/EXTREME HEAT.  
ELIMINATE IGNITION SOURCES. DONT PUT IN CONTACT W/OXIDIZERS OR  
CAUSTIC MATERIAL

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP DRIED MATERIAL AND PLACE INTO  
CONTAINERS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM CAUSTICS AND  
OXIDIZERS. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS FROM  
EXCESSIVE HEAT AND FREEZING.

Other Precau

tions:KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. DO NOT STORE AT TEMPERATURES ABOVE 120F. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING VAPOR MAY BE HARMFUL OR FATAL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF 8 HOUR EXPOSURE LIMIT OR VALUE IS EXCEEDED FOR ANY COMPONENT, USE AN APPROVED NIOSH/OSHA RESPIRATOR. CONSULT YOUR SAFETY EQUIPMENT SUPPLIER AND THE OSHA REGULATION, 29 CFR 1910.134 FOR RESPIRATOR REQUIREMENTS.

Ventilation:PROVIDE SUFFICIENT MECHANICAL VENT (LOCAL OR GENERAL EXHAUST) TO MAINTAIN EXPOSURE BELOW PEL/TLV.

Protective Gloves:IMPERVIOUS GLOVES RECOMMENDED

Eye Protection:SAFETY GLASSES ARE RECOMMENDED

Other Protective Equipment:PROVIDE EYEWASH AND SOLVENT IMPERVIOUS APRON IF BODY CONTACT WITH PRODUCT MAY OCCUR. BARRIER CREAMS MAY BE USED.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NK

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>325F,>163C

Vapor Pres:3.1

Vapor Density:>1.0

Spec Gravity:2.2 (WATER=1)

Evaporation Rate & Reference: