

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 5210 NL, PART B -- 8030-01-007-9153

===== Product Identification =====

Product ID:CS 5210 NL, PART B

MSDS Date:08/03/1992

FSC:8030

NIIN:01-007-9153

Kit Part:Y

MSDS Number: CDXVB

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Phone Num:818-892-1650

Emerge

ncy Phone Num:800-424-9300 CHEMTREC

Preparer's Name:HERBERT MOORE

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:DGBA EPOXY RESINS

CAS:25068-38-6

RTECS #:SL6475000

Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDANTOIN EPOXY RESIN

CAS:15336-82-0

Other REC Li

imits:NONE RECOMMENDED

Ingred Name:VOC = 2.0 G/L

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: ALLERGIC RASH, ITCHING. EYES:
TEARING.

Medical Cond Aggravated by Exposure:DERMATITIS.

=====
===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER AT LEAST 15
MINUTES, CALL DR. INGEST: GIVE MILK/WATER, INDUCE VOMIT, CALL DR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:>200F,>93C

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:FOAM, WATER FOG, DRY CHEMICAL, CO2.

Fire Fighting Procedures:IN CONFINED AREAS, USE SCBA.

Unusual Fire/Explosion Hazard:DECOMP & COMBUSTION PRODUCTS MAY BE
TOXIC.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP & RETURN TO CONTAINER. WASH RESIDUE
W/SOAP & WATER.

Neutralizing Agent:NA

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREAS AWAY FROM
DIRECT SUNLIGHT.

Other Precautions:DO NOT STORE >80F FOR PROLONGED PERIODS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RE

SPIRATOR W/ORGANIC FUME CANISTER.

Ventilation:LOCAL EXHAUST, YES. MECHANICAL (GENERAL) FAN.

Protective Gloves:SOLVENT RESISTANT.

Eye Protection:SAFETY GLASSES W/FACE SHIELD.

Other Protective Equipment:COAT OR APRON TO AVOID SPLASH CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE SMOKING/DRINKING/EATING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>400F,>204C

Melt/Freeze Pt:M.P/F.P Text: