

DE SOTO INC SOUTHWESTERN PLANT -- 910X376 SD AL POLY ACTIVA -- 8010-01-100-9094

=====
Product Identification
=====

Product ID:910X376 SD AL POLY ACTIVA

MSDS Date:01/04/1995

FSC:8010

NIIN:01-100-9094

Kit Part:Y

MSDS Number: CDXVG

=== Responsible Party ===

Company Name:DE SOTO INC SOUTHWESTERN PLANT

Address:FOREST LN AND SHILOH RD

Box:401268

City:GARLAND

State:TX

ZIP:75042

Country:US

CAGE:97460

===

Contractor Identification ===

Company Name:DE SOTO INC SOUTHWESTERN PLANT

Address:FOREST LN AND SHILOH RD

Box:401268

City:GARLAND

State:TX

ZIP:75042

Country:US

CAGE:97460

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL-AMYL KETONE (VP = 2.1)

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 30.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

Ingred Name:HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE (HDI)

CAS:28182-81-2

RTECS #:NQ9170000

Fraction by Wt: 30.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:CYCLOHEXANONE (CERCLA) (VP = 2.0)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:25 PPM/50 STEL
ACGIH TLV:25 PPM/100 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)
(VP = 70.0)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/3
00 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA) (VP = 6.6)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA) (VP = 23.0)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 120F.
Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT,
PUNCTURE/WELD ON

/NEAR DRUM. AVOID SKIN CONTACT BY USE OF OTHER
PROTECTIVE CLOTHING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING/APPLYING IN ANY CIRCUMSTANCES
LIKELY TO PRODUCE AIRBORNE LEVELS OF HAZARDOUS INGREDIENTS IN
EXCESS OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED
RESPIRATOR.

Ventilation:GENERAL TO MAINTAIN VAPORS AIR

Spec Gravity:0.908

Evaporation Rate & Reference:NA

Appearance and Odor:CLEAR LIQUID, SOLVENT ODO

R

Percent Volatiles by Volume:75.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, ALCOHOLS, & AMINES.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
OXIDES OF NITROGEN & TRACES OF HCN & ISOCYANATE MONOMER.

===== Disposal Considerations =====

Waste Disposal Methods:PACKAGE, STORE, TRANSPORT IAW/FEDERAL, STATE &
LOCAL REGULATIONS. FLAMMABLE LIQUID.

Disclaimer (pro

vided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.