

INTERNATIONAL COATINGS CO -- PLASTISOL, VINYL CHLORIDE, BLACK -- 8030-00-145-0156
===== Product Identification =====

Product ID:PLASTISOL, VINYL CHLORIDE, BLACK

MSDS Date:01/01/1996

FSC:8030

NIIN:00-145-0156

Kit Part:Y

MSDS Number: CDZTG

=== Responsible Party ===

Company Name:INTERNATIONAL COATINGS CO

Address:13929 EAST 166TH ST

City:CERRITOS

State:CA

ZIP:90701

Country:US

Info Phone Num:310-925-0

747

Emergency Phone Num:310-926-8332

Preparer's Name:EISENHARD

CAGE:0M246

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:INTERNATIONAL COATINGS

Address:7059 BARRY ST

Box:City:ROSEMONT

State:IL

ZIP:60018

Country:US

Phone:312-824-6070

CAGE:0M246

===== Composition/Information on Ingredients =====

Ingred Name:VINYL CHLORIDE

MONOMER (SARA III)

CAS:75-01-4

RTECS #:KU9625000

Fraction by Wt: 15 MINUTES. SKIN: WASH W/SOAP &
WATER. INHAL: REMOVE TO FRESH AIR. INGEST: GIVE FLUIDS. SEEK
MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:415F,213C

Lower Limits:0.4%

Upper Limits:NA

Extinguishing Media:WATER SPRAY, FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE
EQUIP

MENT.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE W/HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB, TRANSFER TO CONTAINER FOR DISPOSAL AS
HAZARDOUS WASTE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. ELEVATED
TEMPERATURES THICKEN PRODUCT & SHORTEN USEFUL LIFE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.

Ventilation:GOOD VENTILATION SHOULD BE PROVIDED

Protective Gloves:IMPERVIOUS GLOVES (NEOPRENE).

Eye Protection:CHEM WORKERS GOGGS.

Other Protective Equipment:NOT REQUIRED.

Work Hygienic Practices:WASH HANDS AFTER USE, BEFORE EATING, DRINKING
OR SMOKING.

Supplemental Safety and Health

MORE INFORMATION ON FILE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:410F,210C

Vapor Pres:NIL

Vapor Density:>1.0

Spec Gravit

y:1-1.4

Evaporation Rate & Reference:NIL (BUTYL ACETATE=1)

Solubility in Water:NIL

Appearance and Odor:BLACK, SMOOTH THICK LIQUID; FAINT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:ELEVATED TEMPERATURES.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
HYDROGEN CHLORIDE, ACETIC ACID, TOXIC METAL FUMES.

===== Disposal Considerations =

=====

Waste Disposal Methods:DISPOSE OF ALL WASTES I/A/W FEDERAL, STATE &
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.