View NSN Online: https://aerobasegroup.kr/nsn/8040-00-843-7873

Product ID:D.E.R. (R) 324 EPOXY RESIN, #19242 MSDS Date:05/03/1995 FSC:8040 NIIN:00-843-7873 MSDS Number: CDZVX === Responsible Party === Company Name: DOW CHEMICAL U.S.A. Address: CHEMICAL AND METALS DEPARTMENT City:MIDLAND State:MI ZIP:48674 Country:US Info Phone Num:517-636-1000 Emerge ncy Phone Num:517-636-4400 CAGE:96717 === Contractor Identification === Company Name: DOW CHEMICAL CO Address:100 LARKIN CENTER Box:City:MIDLAND State:MI ZIP:48674 Country:US Phone:800-258-2436 CAGE:96717

Ingred Name:REACTION PRODUCTS OF EPICHLOROHYDRIN AND BISPHENOL A CAS:25085-99-8 Fraction by Wt: 83-98% Other REC Limits:NONE RECOMMENDED

Ingred Name:ALKYL GLYCIDYL ETHER CAS:68609-97-2 Fraction by Wt: 2-17% Other REC Limits: LD50 LC50 Mixture:LD50 ORAL 2000 MG/KG RAT Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: MAY CAUSE SLIGHT TRANSIENT EYE IRRITATION. CORNEAL INJURY IS UNLIKELY. SKIN CONTACT: ALLERGIC SKIN REACTIONS. PROLONGED EXPOSURE NOT LIKELY TO CAUSE SIGNIFICANT SKIN IRRITATION. INGEST: INJURY. I NHAL: IRRITAT ION.

First Aid:EYE: FLUSH W/PLENTY OF WATER. SKIN: WASH OFF W/FLOWING WATER OR SHOWER. INGESTION: GET MEDICAL AID. DON'T INDUCE VOMITING UNLESS DIRECTED TO DO SO BY DR. INHALATION: MOVE TO FRESH AIR. CALL DR.

Flash Point Method:PMCC Flash Point:350 TO 375F Lower Limits:NOT EST. Upper Limits:NOT EST. Extinguishing Media:FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures:WEAR POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE EQUIPMENT

Spill Release Procedures: EVACUATE. REMOVE IGNITS. LARGE: EVACUATE UPWIND. DIKE/ABSORB. CONTAINERIZE. REMOVE RESIDUAL RESIN W/STEAM OR HOT SOAPY WATER. SOLVENTS NOT RECOMMENDED FOR CLEAN-UP.

Handling and Storage Precautions:PRACTICE CAUTION A ND GOOD PERSONAL CLEANLINESS TO AVOID SKIN AND EYE CONTACT. AVOID BREATHING VAPORS OF HEATED MATERIAL.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:NO RESPIRATORY PROTECTION SHOULD BE NEEDED. IF RESPIRATORY IRRITATION IS EXPERIENCED, USE AN APPROVED AIR-PURIFYING RESPIRATOR.

Ventilation: GOOD GENERAL VENT SHOULD BE SUFFICIENT FOR MOST CONDITIONS. LOCAL EXHAUST VENT MAY BE NECESSARY FOR SOME OPERATIONS. Protective Gloves: IMPERVIOU S GLOVES Eye Protection:SAFETY GLASSES OR CHEMICAL GOGGLES Other Protective Equipment:WEAR CLEAN, LONG-SLEEVED, BODY-COVERING CLOTHING. USE PROTECTIVE CLOTHING IMPERVIOUS TO THIS MATERIAL. Supplemental Safety and Health MORE INFORMATION ON FILE.

Boiling Pt:B.P. Text:300F,149C Vapor Pres:0.06 Vapor Density:NA Spec Gravity:1.11 Solubility in Water:NONE Appearance and Odor:CLEAR (LIGHT YELLOW) LIQUID OF LOW VISCOSITY; FAINT EPOXY ODOR.

Stability Indicator/Materials to Avoid:YES BASES, ACIDS, AMINES, OXIDIZING MATERIALS. Stability Condition to Avoid:EXCESSIVE HEATING OVER LONG TIME PERIODS. FREEZING MAY CAUSE TEMPORARY HAZINESS. FIRE CONDITIONS INCREASE VISCOSITY. Hazardous Decomposition Products:UNDER CONDITIONS OF IMPERFECT

COMBUSTION AND/OR PYROLYSIS VARIOUS PHENOLIC COMPOUNDS CO AND/OR CO2 MAY BE EVOLVED.

Waste Disposal Methods:COMPLY W/ALL FEDERAL, STATE, LOCAL REGULATIONS. SEND TO PROPERLY LICENSED/PERMITTED RECYCLER/RECLAIMER/INCINERATOR.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability f

or its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.