

COURTAULDS AEROSPACE, INC. -- PR-1436-G SPRAYABLE, BASE -- 8030-00-008-7203
===== Product Identification =====

Product ID:PR-1436-G SPRAYABLE, BASE

MSDS Date:04/04/1994

FSC:8030

NIIN:00-008-7203

Kit Part:Y

MSDS Number: CFCZH

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE, INC.

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2

060

Emergency Phone Num:800-228-5635/800-424-9300(CHEMTREC)

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (VP = 70.0)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA

PEL:200 PPM/STEL 300 PPM
ACGIH TLV:200 PPM/STEL 300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingrid Name:HYDROGENATED TERPHENYLS (VP=1.0 MMHG)

CAS:61788-32-7

RTECS #:WZ6535000

Fraction by Wt: PEL MAY CAUSE

HEADACHE/FATIGUE/CONFUSION/DIZZINESS/DROWSINESS/NUMBNESS/UNCONSCIOUSNESS/LIVER & KIDNEY DAMAGE/PENETRATING ULCERS OF SKIN/MUCOUS MEMBRANES OF NOSE & PERFORATION OF CARTILAGINOUS NASAL SEPTUM/NOSEBLEEDS.

Medical Cond Aggravated by Exposure:SKIN: PROLONGED EXPOSURE TO

HEXAVALENT CHROMIUM COMPOUNDS OVER THE PEL MAY CAUSE PAINLESS PENETRATING ULCERS OF THE SKIN.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES, IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN.INGESTION: CONSULT DR.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:35.0F,1.7C

Lower Limits:1.3

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG.

Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:PROTECT FROM IGNITION. WEAR AIR-SUPPLIED RESPIRATOR

TOR FOR UNVENTILATED SPILL. COVER WITH ABSORBENT MATERIAL
AND SCOOP INTO CONTAINER. CLEAN RESIDUE WITH SUITABLE SOLVENT.
CERCLA RQ FOR MEK = 5000 LBS, F OR TOLUENE = 1000 LBS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. STORE