

F & L COMPANY, INC. -- TECTYL 437, #50501527 -- 8030-00-231-2353

=====  
Product Identification  
=====

Product ID:TECTYL 437, #50501527

MSDS Date:03/23/1994

FSC:8030

NIIN:00-231-2353

MSDS Number: CFDBN

=== Responsible Party ===

Company Name:F & L COMPANY, INC.

Address:1537 E. DEL AMO BLVD

City:CARSON

State:CA

ZIP:90746

Country:US

CAGE:JO940

=== Contractor Identification ===

Company Name:F & L COMPAN

Y

Address:1537 E DEL AMO BLVD

Box:City:CARSON

State:CA

ZIP:90746

Country:US

Phone:310-603-2200

CAGE:0KWT9

Company Name:F & L COMPANY, INC.

Address:1537 E. DEL AMO BLVD

Box:City:CARSON

State:CA

ZIP:90746

Country:US

CAGE:JO940

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HEAVY NAPHTHENIC HYDROTREATED DISTILLATE

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 55-70%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3 STEL 10

Ingred Name:PARAF

FIN WAX  
CAS:8002-74-2  
RTECS #:RV0350000  
Fraction by Wt: 25-40%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3

Ingred Name:CALCIUM PETROLEUM SULFONATE  
CAS:61789-86-4  
RTECS #:WR7140000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3 STEL 10

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards  
Acute and Chronic:EYES: IRRITATION. SKIN: IRRITATION.  
INGEST: GI IRRIT, NAUSEA, VOMIT, DIARRHEA. LUNG DAMAGE. INHAL:  
RESPIRATORY TRACT IRRITATION.

=====  
===== First Aid Measures =====

First Aid:SKIN: THOROUGHLY WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES,  
WASH BEFORE REUSE. EYE: FLUSH W/LARGE AMOUNTS WATER, LIFT LIDS. GET  
MED AID. INGEST: DONT INDUCE VOMIT. KEEP WARM/QUIET. GET MED AID.  
INHAL : MOVE TO FRESH AIR.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:350F,177C  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM.  
Fire Fighting Procedures:USE SCBA WITH FULL FACE PIECE IN POSITIVE  
PRESSURE MODE. WATER/FOAM MAY CAUSE FROTHING (VIOLENT, DANGEROUS).

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: ABSORB. LARGE SPILL: DIKE. IF  
RUNOFF OCCURS, NOTIFY PROPER AUTHORITIES AS R

EQUIRED. EVAC AREA.

SHOVEL MATERIAL INTO CONTAINER. THOROUGHLY SWEEP AREA TO CLEAN UP  
RESIDUAL MATERIAL.

=====  
Handling and Storage  
=====

Other Precautions:EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED SUPPLIED AIR RESPIRATOR.

Ventilation:PROVIDE SUFFICIENT MECHANICAL, (GENERAL) &/OR LOCAL  
EXHAUST.

Protective Gloves:NITRILE RUBBER

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:NORMAL WORK CLOTHES COVERING ARMS & LEGS.

Supplemental Safety and Health  
(MORE INFORMATION ON FILE).

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. Text:NA

Vapor Pres:AIR

Evaporation Rate & Reference: