

ACCUMETRIC INC. -- SILICONE ELASTOMER -- 8040-00-877-9872

===== Product Identification =====

Product ID:SILICONE ELASTOMER

MSDS Date:05/11/1995

FSC:8040

NIIN:00-877-9872

Kit Part:Y

MSDS Number: CFDDC

=== Responsible Party ===

Company Name:ACCUMETRIC INC.

Address:350 RING ROAD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385 FAX: 502-765-2412

Emergency Phone Num

:800-424-9300

Preparer's Name:GARY HARTLAGE

CAGE:58149

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

===== Composition/Information on Ingredients =====

Ingred Name:METHYLTRACETOXYSILANE

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM, STEL 15

Ingred Name:ETHYLTRACETOXYSILANE

CAS:17

689-77-9

Fraction by Wt: 2.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM, STEL 15

Ingred Name:SILICA, AMORPHOUS

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:6 MG/M3

ACGIH TLV:15 MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRITATION, REDNES
S, SWELLING.

SKIN: IRRITATION. INHAL: IRRITATION. INGEST: DIGESTIVE PAIN.

Medical Cond Aggravated by Exposure:ALLERGIC REACTIONS.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES. GET MED AID. SKIN: WIPE
OFF. FLUSH W/WATER. GET MED AID. INHAL: REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:212F,100C

Autoignition Temp:Autoignition Temp Text:NE

Ex

tinguishing Media:FOG, CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE SCBA AND PROTECTIVE CLOTHING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT AND CONTAIN FOR SALVAGE OR
DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 90F. KEEP CONTAINER CLOSED
UNTIL READY TO USE.

Other Precautions:PROTECT FROM ACETIC ACID WHEN EXPOSED TO WATER OR
HUMI

D AIR. PROVIDE VENT TO WITHIN 10 PPM OR USE RESPIRATORY PROTECTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: YES

Ventilation: LOCAL EXHAUST RECOMMENDED, MECHANICAL (GENERAL) RECOMMENDED.

Eye Protection: SAFETY GLASSES MINIMUM

Work Hygienic Practices: WASHING AT MEAL TIME AND END OF SHIFT IS ADEQUATE. REMOVE CONTAM CLOTHES/SHOES & WASH BEFORE REUSE.

Supplemental Safety and Health

KEY1: N1. THIS ENTRY DESCRIBES PART 1 OF A TWO PART KIT. SEE THE SAME

NSN, P/N IND B, FOR PART 2 DATA.

===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: NA

Vapor Pres: