

GRIGGS PAINT -- TT-E-527D, #36375 GRAY, #700AA125 -- 8010-01-270-0717

=====
Product Identification
=====

Product ID:TT-E-527D, #36375 GRAY, #700AA125

MSDS Date:05/01/1995

FSC:8010

NIIN:01-270-0717

MSDS Number: CFDFT

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-424-9300 C

HEMTREC

Preparer's Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (SARA 313) (CERCLA) (VP 8 @ 68F)

CAS:123-86-4

RTECS #:AF7350000

Fractio

n by Wt: 17.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:150 PPM
ACGIH TLV:200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:MAGNESIUM SILICATE
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 30.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHA
L: DROWSINESS, DIZZINESS, FATIGUE,
COMA, LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION,
CNS DEPRESSION. EYE: IRRITATION. SKIN: IRRITATION &/OR DERMITITIS,
ABSORPTION (IRRITATION, DEF ATTING & DERMITITIS). INGEST:
PNEUMONITIS, PULMONARY EDEMA, HEMORRAGE, GI DISTURBANCE.
Medical Cond Aggravated by Exposure:DISEASES OF SKIN, CENTRAL NERVOUS
SYSTEM, LIVER AND KIDNEYS.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY
FLUSH W/LARGE AMOUNTS WATER FOR 15 MINUTES.
SEEK MED AID. SKIN: WASH THOROUGHLY W/SOAP & WATER. SEEK MED AID.
INGEST: IMMEDIATELY SEEK MED AID. DONT INDUCE VOMITING. DONT GIVE
ANYTHI NG BY MOUTH TO UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:81.0F,27.2C
Lower Limits:1.7
Upper Limits:NA
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FI

GHTING

PERSONNEL. WATER MAY BE INEFFECTIVE, MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM IGNITION SOUCES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA W /WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED & UPRIGHT TO PREVENT LEAKAGE. AVOID IGNITION SOURCES. Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANKS OR PITS WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MSHA /NIOSH APPROVED UNITS. USE UNITS PER CURRENT 29 CFR 1910.134 REGULATIONS & FOLLOW MANUFACTURERS' INSTRUCTIONS & WARNINGS. AIR PURIFYING OV/FILTER UNITS MAY BE ACCEPTABLE. Ventilation:LOCAL AND MECHANICAL EXHAUST. Protective Gloves:RUBBER GLOVES Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES Other Protective Equipment:EYE BATH AND SAFETY SHOWER. Work Hygienic Practices:MAINTAIN GOOD PERSON HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION. Supplemental Sa fety and Health NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:244F,118C Vapor Density:>AIR Spec Gravity:1.5 VOC Grams/Liter:2.88 Evaporation Rate & Reference:SLOWER THAN ETHER Solubility in Water:ESSENTIALLY NIL Appearance and Odor:VISCOUS LIQUID, W/TYPICAL PAINT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:IGNITION S

SOURCES.

Hazardous Decomposition Products:CO & CO2.

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIAL ON SPILLS. DISPOSE
IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States o
f America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.