

TEMPO PRODUCTS CO A PLASTI-KOTE CO, INC -- AEROSOL SPRAY PAINT #16081 --  
8010-00-935-7065

===== Product Identification =====

Product ID:AEROSOL SPRAY PAINT #16081  
MSDS Date:02/10/1987  
FSC:8010  
NIIN:00-935-7065  
MSDS Number: CFMRK  
=== Responsible Party ===  
Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO, INC  
Address:1000 LAKE ROAD  
City:MEDINA  
State:OH  
ZIP:44256  
Country:US  
Info Phone Num:216-725-45  
11  
Emergency Phone Num:216-725-4511  
CAGE:07708  
=== Contractor Identification ===  
Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC  
Address:1000 LAKE ROAD  
Box:City:MEDINA  
State:OH  
ZIP:44256  
Country:US  
Phone:330-725-4511  
CAGE:07708

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA 313) (CERCLA)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 10-30%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:750PPM/1000STEL;9596  
EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA 313) (CERCLA)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 10-40%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM; Z-2

ACGIH TLV:50 PPM, A2; 9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10-15%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:PROPYLENE GLYCOL

MONOMETHYL ETHER ACETATE

CAS:108-65-6

RTECS #:AI8295000

Fraction by Wt: 0-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT ESTABLISHED.

ACGIH TLV:NOT ESTABLISHED.

Ingred Name:DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)

CAS:123-42-2

RTECS #:SA9100000

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM; 9596

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 0-5%

Other REC Limits:NONE R

ECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM/300STEL;9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:EYES- CAN CAUSE SEVERE IRRITATION.  
SKIN- IRRITATION. INHALATION- CAN CAUSE NASAL AND RESPIRATORY  
IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION- CAN  
CAUSE GA  
STROINTESTINAL IRRITATION. NO KNOWN CHRONIC EFFECTS.  
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS METHYLENE  
CHLORIDE.  
Effects of Overexposure:EYES- REDNESS, TEARING, BLURRED VISION. SKIN-  
PAINFUL IF CONFINED TO SKIN BY GLOVES, ETC. INHALATION-CAN CAUSE  
DIZZINESS,WEAKNESS, FATIGUE, NAUSEA, HEADACHES, POSSIBLE  
UNCONSCIOUSNESS AND ENVEN ASPH YXIATION. INGESTION- CAN CAUSE  
NAUSEA,VOMITING, DIARRHEA.  
Medical Cond Aggravated by Exposure:ALLERGIC RESPIRATORY AND/OR SKIN  
REACTIONS.

=====  
===== First Aid Measures =====

First Aid:EYES- FLUSH WITH WATER FOR 15 MIN. WHILE OCCASIONALLY HOLDING  
EYELIDS OPEN. SKIN- WASH WITH SOAP AND WATER OR VARIOUS HAND  
CLEANERS. WASH CLOTHING BEFORE RE-USE. INHALATION- REMOVE  
INDIVIDUAL TO FRE SH AIR. IF BREATHING IS DIFFICULT, ADMINISTER  
OXYGEN. GIVE CPR IF NEEDED. INGESTION- DO NOT INDUCE VOMITING  
(ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS). GET  
IMMEDIATE  
MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:0F,-18C  
Lower Limits:1.0  
Extinguishing Media:ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL.  
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO  
COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP. USE  
SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT. VAPORS ARE HEAVIER THA

N AIR AND MAY TRAVEL  
ALONG THE GROUND AND IGNITED BY PILOT LIGHTS, ETC.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES, EVACUATE AREA.  
VENTILATE AND AVOID BREATHING VAPORS. TURN OFF HEATING AND/OR AIR  
CONDITIONING SOURCES. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR  
ABSORBENT, OR OTHER MATERIAL AND TRANSFER TO CLOSED CONTAINERS.

===== Handling and Storage =====

Hand  
ling and Storage Precautions:DO NOT STORE IN AREAS ABOVE 120F, OR  
IN DIRECT SUNLIGHT, OR NEAR HEAT OR OPEN FLAMES.  
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE VAPOR CONCENTRATION IS GREATER THAN 100  
PPM, AN ORGANIC VAPOR TYPE RESPIRATOR IS ADVISED.  
Ventilation:DO NOT USE IN CONFINED AREAS. PROVIDE SUFFICIENT MECHANICAL  
(GENERAL) AND/OR LOCAL EXHAUST VENTILATION.  
Protective Gloves:CHEMICAL RESISTANT GLOVES.  
Eye Protection:CHEMICAL SPLASH GOGGLES.  
Other Protective Equipment:SOLVENT RESISTANT BOOTS, APRON, HEADGEAR  
AND/OR FACESHIELD.  
Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM. AS  
WITH ALL CHEMICALS, MINIMIZE PERSONAL CONTACT AND/OR BREATHING  
VAPORS.  
Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:F2  
Boiling Pt:B.P. Text:104-331F  
Vapor Density:>AIR  
Evaporation Rate & Reference:SOLVENT < THAN ETHER  
So

lubility in Water:SLIGHT TO MODERATE  
Appearance and Odor:TYPICAL SOLVENT PAINT.  
Percent Volatiles by Volume:85-90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS, HEAT, ALKALIES, HOT SURFACES AND REACTIVE METALS.

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES.

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, NITROGEN COMPOUNDS, ETC. CARBON DIOXIDE AND CARBON MONOXIDE.

=====

===== Disposal Considerations =====

Waste Disposal Methods:MATERIAL COLLECTED ON ABSORBENT MATERIAL MAY BE DEPOSITED IN A POSTED TOXIC SUBSTANCE LANDFILL IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.