

NILES CHEMICAL PAINT CO -- N-3809 YELLOW STENCIL INK, #33538 -- 7510-00-224-6733

=====
Product Identification
=====

Product ID:N-3809 YELLOW STENCIL INK, #33538

MSDS Date:01/17/1990

FSC:7510

NIIN:00-224-6733

MSDS Number: CFMYH

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergenc

y Phone Num:219-236-5856

Preparer's Name:MICHAEL LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA 313) (CERCLA) (VP = 22 @ 20C

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 42.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:100

PPM/STEL 150
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALKYD RESIN
CAS:66070-60-8
Fraction by Wt: 16.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SARA 313) (CERCLA) (VP = 7 @ 20C
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 7.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/STEL 150
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACRYLIC RESINS
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:BUTYL CELLOSOLVE (VP = 0.6
@ 20C
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:25 PPM

Ingred Name:COBALT COMPOUNDS (SARA 313)
CAS:7440-48-4
RTECS #:GF8750000
Fraction by Wt: 15 MIN. LIFT LIDS. GET IMMED MED AID. NO CONTACTS.
INGEST: DRINK 1-2 GLASSES WATER. DONT INDUCE VOMITING. CALL
DR/POISON CONTROL IMMEDIATELY. TREAT SYMPTOMS.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:40.0F,4.4C
Au

toignition Temp:Autoignition Temp Text:NE

Lower Limits:0.8

Upper Limits:10.0

Extinguishing Media:DRY CHEMICAL, FOAM, CO2.

Fire Fighting Procedures:USE SCBA W/FULL FACE PIECE IN POSITIVE PRESSURE MODE/PROTECTIVE CLOTHES. USE WATER TO COOL CLOSED CONTAINERS. PREVENT PRESSURE BUILD-UP/AUTOIGNIT/EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CNTNR TIGHTLY CLSD. VAPORS >AIR/TRAVEL TO IGNITS/FLASH BACK CLSD CNTNR MAY EXPLODE W/HIGH HEAT. APPLIC TO HOT SURFACES REQ SPEC PRECAUTIONS DECOM P PROD HAZ

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITS. AVOID VAPOR BREATHING/SKIN CONTACT. ABSORB/SHOVEL INTO DRUMS AND DISPOSE. DIKE.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE IN HIGH HEAT/NEAR IGNITS. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS HAZARDOUS WHEN EMPTY. DON'T WELD/FLAME CUT ON EMPTY DRUM

. SHOCK FROM DROPPING MAY SPLIT CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROPRIATE PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation:SUFFICIENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:CHEM GOGGLES/SAFETY GLASSES/FACE SHLD.

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING.

Work Hygienic Practices:WASH HANDS BEFORE EATING/SMOKING/USING RESTROOM. REMOVE CONTAM CLOTHES TO AVOID FLAMMABILITY HAZ

ARD. WASH

BEFORE REUSE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:231 TO 330F

Decomp Temp:Decomp Text:NE

Vapor Density:>AIR.

Viscosity:>100KU

Evaporation Rate & Reference:SLOWER THAN ETHER.

Solubility in Water:SLIGHT.

Appearance and Odor:LIQUID, ODOR OF SOLVENT.

Percent Volatiles by Volume:64.81

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YE

S

STRONG OXIDIZERS & CAUSTICS.

Stability Condition to Avoid:HIGH TEMPERATURES, SHOCK FROM DROPPING.

Hazardous Decomposition Products:CARBON MONOXIDE &/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:ACCORDING TO FEDERAL, STATE, LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manne

r whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.