

LHB INDUSTRIES -- SO-SURE WHITE #37875

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 00-878-5761
MSDS Date: 10/03/1995
MSDS Num: CFNBN
Product ID: SO-SURE WHITE #37875
MFN: 05
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST LOUIS MO 63134
Info Ph
one Number: 314-522-3141
Emergency Phone Number: 314-522-3141 800-424-9300(CHEMTREC)
Preparer's Name: GREGORY M. MCGOWAN
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Unit of Issue: PT
UI Container Qty: 0

=====
Ingredients
=====

Cas: 64742-89-8
RTE

CS #: SE7546500
Name: VM & P NAPHTHA
% Wt: 8.87
Other REC Limits: NONE SPECIFIED
OSHA PEL: 300 PPM
ACGIH TLV: 300 PPM

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA III)
% Wt: 14.66
Other REC Limits: NONE SPECIFIED
OSHA PEL: 200 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE (SARA 313)
% Wt: 25.42
Other REC Limits: NONE SPECIFIED
OSHA PEL: 1000 PPM
ACGIH TLV:
750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 14.91
Other REC Limits: NONE SPECIFIED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

Cas: 75-28-5
RTECS #: TZ4300000
Name: 2-METHYL PROPANE
% Wt: 3.67
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 800 PPM

Cas: 106-97-8
RTECS #: EJ4200000
Name: N-BUTANE
% Wt: 5.87
Other REC Limits: NONE

SPECIFIED
OSHA PEL: 800 PPM
ACGIH TLV: 800 PPM

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA 313)
% Wt: 3.55
Other REC Limits: NONE SPECIFIED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

RTECS #: 9999999VO
Name: VOC: 449 G/L
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 100-41-4
RTECS #: DA0700000
Name: ETHYL BENZENE
(SARA 313)
% Wt: <1.77
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS
=====

Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: INHAL: HARMFUL/FATAL. CHRONIC: BRAIN/NERVOUS SYSTER
DAMAGE, ANESTHETIC. IRRITATION OF SKIN

/RESPIRATORY TRACT (NAUSEA, HEADACHE, VOMITING, LIGHT HEADEDNESS, STAGGERING GAIT & GIDDINESS). EYE: IRRITATION.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.

First Aid: SKIN: WASH W/SOAP/WATER, WASH CLOTHES BEFORE REUSE. EYES: FLUSH W/WATER 15 MIN, CALL DR/OPHTHALMOLOGIST IMMEDIATELY. INGEST: DON'T INDUCE VOMIT. GET IMMEDIATE MED AID. INHAL: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NEEDED. GET MED AID. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====

=====

Handling and Disposal

=====

Spill Release Procedures: REMOVE IGNITION SOURCES AND VENT AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: IN ACCORDING WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. DISCARD IN TRASH PICK-UP. DO NOT PUT IN HOME TRASH COMPACTOR OR INCINERATE.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER PRESSURE.

DO NOT STORE WHERE >120F. AVOID BREATHING SPRAY/MIST/VAPOR.

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: 21.0F, -6.1C

Autoignition Temp Text: 874F

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. DON'T SPREAD BURNING LIQUID W/WATER SPRAY.

Fire Fighting Procedures: WATER INEFFECTIVE. USE H2O TO COOL CONTAINERS. WEAR

SELF-CONTAINED BREATHING APPARATUS. USE SHIELDING TO PROTECT PERSONNEL FROM BURSTING/RUPTURE/VENTING.

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURES (>120F) CONTAINERS MAY VENT/RUPTURE/BURST.

=====

Control Measures

=====

Respiratory Protection: USE NIOSH/MSHA APPROVED MASK.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL: ACCEPTABLE.

Protective

Gloves: YES

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DONT EAT/DRINK/SMOKE WHILE USING PRODUCT.

=====
Physical/Chemical Properties
=====

B.P. Text: NA

M.P/F.P Text: NA

Decomp Text: NA

Vapor Pres: 60.0

Vapor Density: >1.5

Spec Gravity: 1.007

PH: NA

Viscosity: NA

Solubility in Water:

INSOLUBLE

Appearance and Odor: WHITE PAINT

Corrosion Rate: NA

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT.

Materials To Avoid: NA

Hazardous Decomposition Products: CARBON MONOXIDE AND POSSIBLE HYDROGEN CHLORIDE.

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====

Other Information

=====

Transportation Information

Responsible Party Cage: 0FTT5
Trans ID NO: 89718
Product ID: SO-SURE WHITE #37875
MSDS Prepared Date: 10/03/1995
Review Date: 10/16/1997
MFN: 5
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Container QTY: 0

=====

=====
Detail DOT Information

=====

DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODU
CT ?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13

=====

Detail IATA Information

=====

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 7

5KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3

=====
HAZCOM Label
=====

=====
Product ID: SO-SURE WHITE #37875
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 314-522-3141 800-424-9300(CHEMTREC)
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: INHAL: HARMFUL/FATAL. CHRONIC: BRAIN/NERVOUS SYSTER
DAMAGE, ANESTHETIC. IRRITATION OF SKIN/REPRIATORY TRACT (NAUSEA,
HEADACHE,VOMITING, LIG
HT HEADEDNESS, STAGGERING GAIT & GIDDINESS). EYE:
IRRITATION.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department

of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.