

DEL PAINT CORP. -- TT-E-2784 GREEN, #34052 -- 8010-01-418-5429

===== Product Identification =====

Product ID:TT-E-2784 GREEN, #34052  
MSDS Date:06/14/1995  
FSC:8010  
NIIN:01-418-5429  
MSDS Number: CFNHF  
=== Responsible Party ===  
Company Name:DEL PAINT CORP.  
Address:3105 E. RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Info Phone Num:405-672-1431/FAX 405-672-0804  
Emergency Phone Num:800-424-930  
0 24 HRS  
CAGE:JO954  
=== Contractor Identification ===  
Company Name:DEL PAINT CORP.  
Address:3105 E. RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431/FAX 405-672-0804  
CAGE:JO954  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
Box:City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL  
CAS:57-55-6  
RTECS #:TY2000000  
Fraction by Wt: 6.25%  
Other REC Limit

s:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL MONOISOBUTYRATE  
CAS:25265-77-4  
Fraction by Wt: 4.86%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC  
CAS:108-01-0  
RTECS #:KK6125000  
Fraction by Wt: 0.38%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE  
CAS:123-96-6  
RTECS #:RH0795000  
Fraction by Wt: 0.18%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENTS  
Fraction by Wt: 88.33%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC = 1.7 LBS/GL  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT EST.

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: HEADACHE, NAUSEA, IRRITATION.  
EYE: IRRITATION. CHRONIC: SKIN: IRRITATION.  
Medical Cond Aggravated by Exposure:LUNG DISEASE

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES. CALL DR.  
SKIN: WASH W/SOAP & WATER. INGEST: GIVE 2 GLASSES OF WATER TO  
DRINK. CALL DR.

=====  
===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:>212F,>100C  
Autoignition Temp:Autoignition Temp Text:216F  
Lower Limits:NONE  
Upper Limits:NA  
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.  
Fire Fighting Procedures:USE SCBA (PRESSURE DEMAN

D NIOSH/MSHA APPROVED)  
& FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL MAY SPLATTER ABOVE 212F. POLYMER  
FILM MAY BURN.

===== Accidental Release Measures =====

Spill Release Procedures:EVAC AREA. FLOOR MAY BE SLIPPERY, USE CARE TO  
AVOID FALLING. DIKE/ABSORB. TRANSFER TO SEPARATE, SUITABLE  
CONTAINER FOR RECOVERY/DISPOSAL. DONT CONTAMINATE SEWERS, OPEN  
BODIES OF WATER.

===== Handling and Storage =====  
==

Handling and Storage Precautions:KEEP FROM FREEZING.  
Other Precautions:KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR  
Ventilation:NORMAL (FAN)  
Protective Gloves:RUBBER  
Eye Protection:SAFETY GLASSES/GOGGLES  
Other Protective Equipment:EYEWASH STATION  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F  
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C  
Decomp Temp:Decomp Text:350F,177C  
Vapor Pres:NONE  
Vapor Density:>AIR  
Spec Gravity:1.01  
pH: