

PIMA VALVE INC -- MOBIL DTE OIL HEAVY MEDIUM -- 9150-00-993-8588

===== Product Identification =====

Product ID:MOBIL DTE OIL HEAVY MEDIUM

MSDS Date:12/07/1994

FSC:9150

NIIN:00-993-8588

MSDS Number: CFRFH

=== Responsible Party ===

Company Name:PIMA VALVE INC

Address:6525 W. ALLISON RD

Box:5010

City:CHANDLER

State:AZ

ZIP:85226-9405

Country:US

Info Phone Num:520-796-1095

Emergency Phone Num:520-796-1

095

CAGE:MO457

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:PIMA VALVE INC

Address:6525 W. ALLISON RD

Box:5010

City:CHANDLER

State:AZ

ZIP:85226-9405

Country:US

Phone:520-796-1095

CAGE:MO457

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE

:0T5C6

=====
Composition/Information on Ingredients
=====

Ingred Name:PRODUCT IS NOT FORMULATED TO CONTAIN INGREDIENTS WHICH HAVE EXPOSURE LIMITS ESTABLISHED BY REGULATORY AGENCIES.
RTECS #:9999999ZZ
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2000 MG/KG
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards A
cute and Chronic:INGEST:PRACTICALLY NON-TOXIC.EYE'SKIN:
PRACTICALLY NON-IRRITATING AND NON-SENSITIZING.INHAL:NO HAZARD EXPECTED.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:NO SYMPTOMS ANTICIPATED.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF IRRITATION OCCURS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:NOT EXPECTED TO BE A PROBLEM.IF MORE THAN 1 PINT IS INGESTED,DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,GIVE 1-2 GLASSES OF WATER.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>400F,>204C
Lower Limits:0.6
U

ppert Limits:7.0

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.AVOID RUNOFF INTO WATER WAYS.REPORT SPILLS RESULTING IN SHEEN UPON WATER TO 800-424-8802.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.
Ventilation:USE GENERAL DILUTION VENTILATION.
Protective Gloves:NOT NEEDED IN NORMAL SERVICE.
Eye Protection:SAFETY GLASSES
Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.
Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.
Supplemental Safety and Health
NONE

===== Physical
/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>600F,>316C
Vapor Pres:41CS@104F
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIQUID;LIGHT AMBER;MILD ODOR.
Percent Volatiles by Volume: