

AGE REFINING -- JP-8 -- 9130-01-395-0945

===== Product Identification =====

Product ID:JP-8
MSDS Date:04/02/1996
FSC:9130
NIIN:01-395-0945
MSDS Number: CFTBF
=== Responsible Party ===
Company Name:AGE REFINING
Address:7811 S PRESA
City:SAN ANTONIO
State:TX
ZIP:78223
Country:US
Info Phone Num:210-532-5300
Emergency Phone Num:800-424-9300(CHEMTREC)
CAGE:MO635
=== Contractor Identification ===
Compan
y Name:AGE REFINING
Address:7811 S PRESA
Box:City:SAN ANTONIO
State:TX
ZIP:78223
Country:US
Phone:210-532-5300
CAGE:MO635
Company Name:AGE REFINING AND MARKETING
Address:7811 S PRESA
Box:City:SAN ANTONIO
State:TX
ZIP:78223-3531
Country:US
Phone:512-532-5300
CAGE:0T116

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBONS (MIXTURE)
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:BENZENE, TRIMETHYL- (MIXED ISOMERS); (TRIMETHYL BENZENE)
CONTAINING I

NG #3
CAS:25551-13-7
RTECS #:DC3220000
OSHA PEL:25 PPM
ACGIH TLV:25 PPM

Ingred Name:BENZENE, 1,2,4-TRIMETHYL-; (1,2,4-TRIMETHYLBENZENE)
CAS:95-63-6
RTECS #:DC3325000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:SUPP DATA: IRRITATES MUC MEMBS OF THROAT, ESOPHAGUS &
STOMACH. MAY CAUSE VOMIT. IF ABSORBED, CNS DEPRESS MAY OCCUR.
RTECS #:9999999ZZ

Ingred Name:FIRST AID PROC: NOTES TO PHYS: GASTRIC LAVAGE ONLY IF LRG
QTY HAS BEEN INGESTED. ASPIR INTO LUNGS MAY RSLT IN (ING 7)
RTECS #:9999999ZZ

Ingred Name:ING 6: CHEM PNEUM. IRREGULAR HEART BEAT MAY OCCUR; USE OF
ADRENALIN IS NOT ADVISED. TREAT SYMPTOMATICALLY.
RTECS #:9999999ZZ

Ingred Name:SPILL PROC: PRODS & CONTAMD MATLS ACCORD TO ALL APPLIC LOC,
ST, & FED REGS. WATER SPILL: KEEP SPILLS & CLEANING (ING 9)
RTECS #:9999999ZZ

Ingred Name:ING 8: RUNOFF OUT OF MUNICIPAL SEWERS & OPEN WATERWAYS.
CONTAIN W/DIKES & COLLECT MATL. STORE IN CHEM WASTE (ING 10)
RTECS #:9999999ZZ

Ingred Name:ING 9: CNTNRS FOR DISP. ADVISE AUTHORI
TIES IF PROD HAS
ENTERED OR MAY ENTER SEWERS, WATERCOURSE/EXTENSIVE LAND AREAS.
RTECS #:9999999ZZ

Ingred Name:OTHER PREC: PRODS. ECOLOGICAL INFO:KEROSENE & SIMILAR
HYDROCARBS ARE CONSIDERED DANGEROUS TO AQUATIC LIFE IN HIGH CONCS.
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Haza

Effects Acute and Chronic:DANGER! FLAMM LIQ. INHAL MAY CAUSE NARCOTIC EFFECTS LEADING TO RESP ARREST. SEV IRRIT TO EYES. SKIN IRRIT ON Prolonged Cont. Ingest MAY Result in Vomit & CNS Depression. INHAL: MAY CAUSE NARCOTIC EFFECTS INCL Dizziness, Headache, Incoordination, Anesthesia, Coma, Irregular Heart Rate, & RESP ARREST. Acts as CNS Depressant. (Effects of Overexposure)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:Health Hazard: Oxygen Deprivation is possible when working in confined area

EYE: SEV BURNING SENSATION w/TEMP IRRIT & SWELLING OF LIDS. 470 PPM for 15 mins leads to IRRIT. SKIN: IRRIT TO SKIN. Defatting may occur w/continued Prolonged Cont. IRRIT & BURNING SENSATION AFTER EXPOS TO LIQ. Drying, Chapping & Photosensitivity (Supdat)

Medical Condition Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. IF NOT Breathing, Apply ARTF RESP. SEEK MED ADVICE.

EYE: FLUSH w/LRG AMTS of RUNNING WATER for AT LST 15 mins. Hold lids apart to ensure flushing of entire eye. SEEK MED ATTN. SKIN: WASH EXPOS AREA w/soap & water. Remove contaminated clothes & footwear. SEEK MED ADVICE, if symptoms develop. Ingest: DO NOT induce vomit. Get MED ATTN. If spontaneous vomit occurs, keep head below (Ingestion)

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:100F,38C

Lower Limits:0.9%

Upper Limits:56%

Extinguishing

Media:USE EXTING MEDIA SUCH AS FOAM, DRY CHEM, & CARBON DIOXIDE APPROP FOR SURROUNDING CONDITIONS. WATER MAY BE INEFFECTIVE (Supdat)

Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. Approach fire from upwind side. AVOID BREATHING SMOKE, FUMES, MIST, OR VAPORS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:LAND SPILL: ABSORB &/OR CONFINE LIQ w/INERT

T,
NON-COMBUST MATL. KEEP SPILLS OUT OF MUNICIPAL SEWERS & OPEN
WATERWAYS. PLACE WASTE IN CHEM WASTE CNTNR FOR DISP. CONTINUE TO
OBSERVE PRECS FOR VOLATILE, C OMBUST VAPS FROM ABSORB MATL. DISP
WASTE (ING 8)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. USE
SPARK-PROOF TOOLS. AVOID BREATHING VAPORS AND SKIN/EYE CONTACT.
PROTECT CONTAIN
ERS AGAINST PHYSICAL DAMAGE.

Other Precautions:OUTSIDE/DETACHED STOR IS PREFERRED. STORE IN COOL,
WELL-VENT AREA AWAY FROM IGNIT SOURCES & OXIDIZING AGENTS. TO PVNT
FIRE/EXPLO RISK FROM STATIC ACCUMULATION & DISCHARGE, GROUND PROD
TRANSFER SYS I/A /W NFPA GUIDELINES FOR PETROLEUM(ING 11)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV EXCEEDED, NIOSH APPROVED ORGANIC VAPOR
MASK REQUIRED.

Ventilation:LOCAL VENTILATION TO CONTROL
VAPOR ACCUMULATION.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPROVED EYE WASH & DELUGE SHOWER .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

EXTING MEDIA: UNLESS USED UNDER FAVORABLE CNDTNS BY TRAINED FIRE
FIGHTERS. WATER CAN BE USED TO COOL & PROT MATLS & MEN, DISPERSE
VAPS, & FLUSH SPILLS AWAY FROM EXPOSURES. MATLS TO AVOID: CAUSE
FIRES & EXPLOSIONS. EFTS OF OV

EREXP: MAY DEVELOP AFTER RPTD CONT.

SKIN ABSORP IS NOT SIGNIFICANT. INGEST: HARMFUL. (ING 5)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>285F,>141C

Vapor Pres:5 @ 20C

Vapor Density:4-5

Volatile Org Content %:100

Spec Gravity:0.79

Solubility in Water:NEGLIGIBLE,