

INLAND, INC. -- INTERBOND ACRYLIC LATEX CHALK W/SILICONE -- 8030-01-075-1156

=====
Product Identification
=====

Product ID:INTERBOND ACRYLIC LATEX CHALK W/SILICONE

MSDS Date:05/01/1997

FSC:8030

NIIN:01-075-1156

MSDS Number: CFXBF

=== Responsible Party ===

Company Name:INLAND, INC.

Address:209 PETERSON DRIVE

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-737-6757

Emergency Pho

ne Num:502-737-6757

CAGE:KO471

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66712

Company Name:INLAND, INC.

Address:209 PETERSON DRIVE

Box:City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-737-6757

CAGE:KO471

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS (VP = 2 @ 68F)

CAS:64742-88-7

Fraction by Wt: 1.0%

Oth

er REC Limits:NONE RECOMMENDED

OSHA PEL:5 PPM

ACGIH TLV:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION.

=====
First Aid Measures
=====

First Aid:INGEST: DRINK 2 GLASSES OF WATER & INDUCE VOMITING. EYE:

FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SO

AP & WATER. IN ALL

CASES, GET MED AID.

=====
Fire Fighting Measures
=====

Flash Point:>200F,>93C

Extinguishing Media:NSPA CLASS B EXTINGUISHERS. (CARBON DIOXIDE/DRY
CHEMICAL/FOAM).

Fire Fighting Procedures:USE SCBA & PROTECTIVE EQUIPMENT. (EYE/FACE
SHIELD, FULL BUNKER GEAR). COOL CONTAINERS W/WATER SPRAY.

=====
Accidental Release Measures
=====

Spill Release Procedures:KEEP SPILLS OUT OF SEWERS & BODIES OF WATER.

A

REA MAY BE SLIPPERY.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE >140F. KEEP ABOVE
FREEZING.

=====
Exposure Controls/Personal Protection
=====

Protective Gloves:RECOMMENDED.

Eye Protection:RECOMMENDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:NA

Vapor Density:>Al

R
Spec Gravity:1.70
pH: 7.9
Viscosity:20-54 GPS
Solubility in Water:SOLUBLE.
Appearance and Odor:WHITE, LIGHT ACRYLIC.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:DECOMPOSITION MAY INVOLVE CARBON
DIOXIDE, CARBON MONOXIDE & TOXIC MONOMER FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE &
LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
part
icular situation.