View NSN Online: https://aerobasegroup.com/nsn/8010-01-242-2409

DEL PAINT CORP. -- TT-E-529G BLUE #25177 -- 8010-01-242-2409

Product ID:TT-E-529G BLUE #25177

MSDS Date:08/05/1997

FSC:8010

NIIN:01-242-2409

MSDS Number: CFXCC === Responsible Party ===

Company Name: DEL PAINT CORP.

Address:3105 E. RENO City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804

Emergency Phone Num:800-424-9300 2

4 HRS

Preparer's Name: ONEY FLEMING

CAGE:JO954

=== Contractor Identification === Company Name: DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY State:OK

ZIP:73117 Country:US

Phone: 405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name: DEL PAINT MFG

Address:3105 EAST RENO Box:City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Phone: 405-672-1431

CAGE:39934

====== Composition/Information on Ingredients ========

Ingred Name: MEDIUM ALIPHATIC SOLVENT NAPHTHA

CAS:64742-88-7

Fraction b

y Wt: 32.4%

Other REC Limits: NONE RECOMMENDED

Ingred Name: NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 67.6%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name: VOC = 2.97 LBS/GL

RTECS #:9999999VO

Other REC Limits: NONE RECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Healt

h Hazards Acute and Chronic:EYE: REDNESS, PAIN. SKIN: REDNESS.

INHAL: LABORED BREATHING, DULLNESS, DROWSINESS. INGEST: ABDOMINAL PAIN, NAUSEA. CHRONIC: EYE: IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: IRRITATION, DEFATTI NG, DERMATITIS. INHAL:

NASAL/RESPIRATORY IRRIT, DIZZINESS, NAUSEA, HEADACHE. INGEST: GI IRRITATION, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure: RESPIRATORY SYSTEM DISEASES.

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES, LIFT LIDS, GET MED AID. SKIN: REMOVE CONTAM CLOTHES, WASH BEFORE REUSE. WASH SKIN W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR. GIVE OXYGEN IF NEEDED. GET MED AID. INGEST: KEEP WARM/QUIET. GET MED AID. DONT INDUCE VOMIT.

============ Fire Fighting Measures =========================

Flash Point Method:TCC Flash Point:100F,38C

Autoignition Temp: Autoignition Temp Text: 540F

Lower Limits:1.0 Upper Limits:6.0

Extin

guishing Media:CO2, DRY CHEMICAL, FOAM. Fire Fighting Procedures:USE SCBA & FULL PROTECTIVE GEAR. USE WATER SPRAY TO COOL CONTAINERS. (PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION). Unusual Fire/Explosion Hazard:WATER MAY SPREAD FIRE. VAPORS >AIR, MAY TRAVEL TO IGNITION SOURCE & FLASH BACK.
======== Accidental Release Measures =========
Spill Release Procedures:VENT AREA. COVER W/INERT ABSORBENT. SHOVEL W/NONSPARKING TOOLS INTO CONTAINER. REMOVE TO SAFE AREA & SEAL.
========== Handling and Storage ============
Handling and Storage Precautions:STORE IN CLEAN, DRY AREA. KEEP AWAY FROM IGNITION SOURCES.
Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM CHILDREN. GROUND EQUIPMENT TO REDUCE STATIC ELECTRICITY HAZARD. USE NONSPARKING TOOLS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE A RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH APPROVED). Venti lation:LOCAL EXHAUST. Protective Gloves:CHEMICAL RESISTANT. Eye Protection:SAFETY GLASSES W/SIDE SHIELDS. Other Protective Equipment:EYEWASH STATION, SAFETY SHOWER & IMPERVIOUS
CLOTHING. Supplemental Safety and Health
NK
========== Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:305 TO 396F Melt/Freeze Pt:M.P/F.P Text:NA Decomp Temp:Decomp Text:752F,400C Vapor Pres:2.58 Vapor Density:>AIR Spec Gravity:1.1 pH:NA Viscosity:65-72 KU Evaporation Rate & Decomp Text:752F,400C

