

DEN-TAL-EZ DENTAL PRODUCTS INC,STAR DENTAL DIV -- DENTALUBE (#5476) -- 6520-00-140-7663

===== Product Identification =====

Product ID:DENTALUBE (#5476)

MSDS Date:11/11/1997

FSC:6520

NIIN:00-140-7663

Kit Part:Y

MSDS Number: CFYWK

=== Responsible Party ===

Company Name:DEN-TAL-EZ DENTAL PRODUCTS INC,STAR DENTAL DIV

Address:1816 COLONIAL VILLAGE LANE

City:LANCASTER

State:PA

ZIP:17601

Country:US

Info

Phone Num:717-291-1161

Emergency Phone Num:717-291-1161

CAGE:57078

=== Contractor Identification ===

Company Name:A-DEC INC

Address:2601 CRESTVIEW DR

Box:City:NEWBURG

State:OR

ZIP:97132

Country:US

Phone:503-537-2710

CAGE:51840

Company Name:DEN-TAL-EZ DENTAL PRODUCTS INC,STAR DENTAL DIV

Address:1816 COLONIAL VILLAGE LANE

Box:City:LANCASTER

State:PA

ZIP:17601

Country:US

Phone:717-291-1161

CAGE:57078

===== Composition/Information on Ingredients =====

Ingred Name:1,1,2-TRICHLORO-

1,2,2-TRIFLUOROETHANE (FREON 113) (SARA
III)

CAS:76-13-1

RTECS #:KJ4000000

Fraction by Wt: 61-75%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000PPM/1250STEL

ACGIH TLV:1000PPM/1250STEL9192

Ozone Depleting Chemical:1

Ingred Name:LUBRICATING OIL PETROLEUM BASE 10.5 TO 13.5%

Fraction by Wt: 10-13.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST

ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:LPG (LIQUEFIED PETROLEUM GAS)PROPANE/ISOBUTANE (PROPELLANT)

CAS:68476-85-7

RTECS #:SE7545000

Fracti

on by Wt: 18-22%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-EYE:CAN CAUSES

IRRITATION,REDNESS,TEARING. SKIN:PROLONGED/REPEATED CONTACT CAN
CAUSE IRRITATION,DEFATTING,DERMATITIS. INHALED:CAN CAUSE SHORTNESS
OF BREATH,LIGHT HEADINESS,POSSI

BLE NARCOSIS,GIDD INESS,DIZZINESS &

POSSIBLE CARDIAC ARRHYTHMIAS AT HIGH CONCENTRATIONS.ORAL:MAY CAUSE
ILLNESS.CHRONIC-DERMATITIS.

Effects of Overexposure:CAN CAUSES EYE IRRITATION, REDNESS, TEARING.

PROLONGED/REPEATED SKIN CONTACT CAN CAUSE IRRITATION, DEFATTING,
DERMATITIS. INHALATION CAN CAUSE SHORTNESS OF BREATH, LIGHT
HEADINESS, POSSIBLE NARCOSIS, GIDDINESS, DIZZINESS & POSSIBLE
CARDIACARRHYTHMIAS AT HIGH CONCENTRATIONS. MAY CAUSE ILLNESS IF
INGESTED.

Medical Co

nd Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE
MORE SUSCEPTIBLE TO THIS MATERIAL.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION.SKIN:WASH WITH SOAP AND
WATER.INHALATION:REMOVE TO FRESH AIR & PROVIDE CPR/OXYGEN IF
NECESSARY. EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE
HOLDING EYELIDS OPEN. INGEST ION:DO NOT INDUCE VOMITING.CALL A
PHYSICIAN.IF CONSCIOUS,DILUTE BY DRINKING WATER OR MILK.NOTE TO

PHYSICIAN:DO NOT ADMINISTER EPINEPHRINE OR SIMILAR DRUGS.THIS CAN
INDUCE SEVERE CARDIAC IRREGULARITIES

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:-139F PROPELLANT

Lower Limits:2.0 PROPANE

Upper Limits:10 PROPANE

Extinguishing Media:WATER FOG, CARBON DIOXIDE, FOAM OR DRY CHEMICAL.
FOR SURROUNDING FIRE, USE WATER SPRAY TO COOL FIRE EXPOSED
CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-
APP

ROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE
OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:AT ELEVATED TEMPERATURES, ABOVE 130F,
CONTAINERS MAY VENT, RUPTURE OR BURST. CONTAINS PROPANE.

===== Accidental Release Measures =====

Spill Release Procedures:AREA SHOULD BE VENTILATED. REMOVE ALL SOURCES
OF IGNITION. REMOVE WITH INERT ABSORBENT MATERIALS AND
NON-SPARKING TOOLS. PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN A COOL,VENTILATED
AREA BELOW 120F.DO NOT PUNCTURE OR INCINERATE.

Other Precautions:"EMPTY" CONTAINERS MAY RETAIN RESIDUE AND CAN BE
DANGEROUS. DO NOT PRESSURIZE, CUT, WELD OR EXPOSE SUCH CONTAINERS
TO HEAT OR FLAMES. THEY MAY EXPLODE AND CAUSE INJURY/DEATH. AVOID
CONTACT WITH EYES A ND SKIN. DO NOT BREATHE VAPORS OR MISTS.

===== Exposure Controls/Personnel =====

nal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS. IF TLV IS EXCEEDED THEN USE NIOSH APPROVED SELF- CONTAINED BREATHING APPARATUS. AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.

Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.

Protective Gloves:RUBBER, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protec

tive Equipment:EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health

THIS ITEM IS PART OF THE KIT 36-0099-00 SUPPLIED BY A-DEC INC (CAGE 51840).

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:118F,48C

Vapor Pres:3691 PROPA

Vapor Density:1

Spec Gravity:1.467

Evaporation Rate & Reference:1 (N-BUTYL ACETATE=1)

Solubility in

Water:NEGLIGIBLE

Appearance and Odor:CONCENTRATE: CLEAR, ORANGE LIQUID - SLIGHT PETROLEUM HYDROCARBON ETHEREAL ODOR

Percent Volatiles by Volume: 88%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, ALKALI OR ALKALINE EARTH METALS, POWDERED ALUMINUM, ZINC, BERYLLIUM, ETC...

Stability Condition to Avoid:DO NOT EXPOSE TO TEMPERATURES ABOVE 120F.

Hazardous Decomposition Products:HYDROCHLORIC-HYDROFLUORIC ACIDS

, POSSIBLY PHOSGENE, CARBON MONOXIDE, SULFUR OXIDES, ALDEHYDES & OTHER DECOMP. PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods:ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS. DO NOT INCINERATE CLOSED OR EMPTY CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements o

f the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.