

THOMAS SCIENTIFIC ATTN: WALTER KOWALSKI -- LUBRISEAL -- 9150-00-190-0923

=====
Product Identification
=====

Product ID:LUBRISEAL

MSDS Date:01/04/1993

FSC:9150

NIIN:00-190-0923

Kit Part:Y

MSDS Number: CFYWQ

=== Responsible Party ===

Company Name:THOMAS SCIENTIFIC ATTN: WALTER KOWALSKI

Address:99 HIGH HILL ROAD AT 1-295

Box:99

City:SWEDESBORO

State:NJ

ZIP:08085-0099

Country:US

Info Phone Num:609-4

67-2000

Emergency Phone Num:609-467-2000

CAGE:59728

=== Contractor Identification ===

Company Name:THOMAS SCIENTIFIC COMPANY

Address:99 HIGH HILL ROAD AT I-295

Box:City:SWEDESBORO

State:NJ

ZIP:08085-0099

Country:US

Phone:856-467-2000

CAGE:59728

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLATUM

CAS:8009-03-8

Fraction by Wt: NA

Other REC Limits:NONE RECOMMENDED

Ingred Name:RUBBER LATEX

CAS:9003-55-8

Fraction by Wt: NA

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE OR SKIN CONTACT OR VAPOR
 INHALATION MAY CAUSE IRRITATION. INGESTION MAY ACT AS A LAXATIVE.
Explanation of Carcinogenicity:NONE ESTABLISHED.
Effects of Overexposure:IRRITATION - SEE "HEALTH HAZARD"
Medical Cond Aggravated by Exposure:SENSITIVITY TO PETROLEUM PRODUCTS.

=====
===== First Aid Measures =====

First Aid:EYE-FLUSH THOROUGHLY WITH WATER. SKIN-WASH WITH SOAP AND
 WATER. INHALATION-REMOVE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:>203F,>95C
Extinguishing Media:FOAM, WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP AND CONTAINERIZE FOR PROPER DISPOSAL.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR IGNITION SOURCES.
 AVOID CONTACT WITH EYES.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED IF BEING OVERHEATED.
Ventilation:LOCAL EXHAUST, IF BEING OVERHEATED.
Protective Gloves:IF LARGE QUANTITIES ARE BEING

HANDLED.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:AVOID EYE OR SKIN CONTACT, BREATHING VAPORS;
IGNITION SOURCES OR OXIDIZERS.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>644F,>340C

Melt/Freeze Pt:M.P/F.P Text:>122F,>50C

Spec Gravity:0.85-0.95

Appearance and Odor:PALE YELLOW TO LIGHT BROWN GREASE - NO ODOR.

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PURE OXYGEN OR OXIDIZERS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON MONOXIDE, VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:TO BE PERFORMED IN COMPLIANCE WITH ALL CURRENT
LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the comping agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.