

HIGH QAULITY ALLOYS -- HQA/5554 ALUMINUM WELDING WIRE & ROD -- 3439-00-803-9499

===== Product Identification =====

Product ID:HQA/5554 ALUMINUM WELDING WIRE & ROD

MSDS Date:03/15/1993

FSC:3439

NIIN:00-803-9499

MSDS Number: CFYXX

=== Responsible Party ===

Company Name:HIGH QAULITY ALLOYS

Address:12329 TELEGRAPH ROAD

City:SANTA FE SPRINGS

State:CA

ZIP:90670

Country:US

Info Phone Num:310-941-3264

Eme

rgency Phone Num:310-941-3264

Preparer's Name:MARK A. COMSTOCK

CAGE:KO878

=== Contractor Identification ===

Company Name:HIGH QAULITY ALLOYS

Address:12329 TELEGRAPH ROAD

Box:City:SANTA FE SPRINGS

State:CA

ZIP:90670

Country:US

Phone:310-941-3264

CAGE:KO878

Company Name:HIGH QUALITY ALLOYS

Address:12328 TELEGRAPH RD

Box:City:SANTA FE SPRINGS

State:CA

ZIP:80670

Country:US

Phone:213-841-3264

CAGE:2Z398

===== Composition/Information on Ingredients =====

Ingred Name:IRON (FE)

CAS:7

439-89-6
RTECS #:NO4565500
Fraction by Wt: 0.40%
Other REC Limits:NONE RECOMMENDED

Ingred Name:COPPER (SARA 313) (CERCLA) (CU)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0.10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2 MG/M3 FUME; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE (SARA 313) (MN)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 0.10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 5 MG/M3 (FUME)
ACGIH TLV:0.2 MG/M3; 9596

Ingred Name:SILICON (SI)
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 0.25%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:CHROMIUM (SARA 313) (CERCLA) (CR)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 0.20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9596
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MAGNESIUM OXIDE (MG)
CAS:1309-48-4
RTECS #:OM3850000
Fraction by Wt: 3.0%
Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 PARTICULATE
ACGIH TLV:10 MG/M3; FUME; 9596

Ingred Name:TITANIUM (TI)
CAS:7440-32-6
RTECS #:XR1700000
Fraction by Wt: 0.20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC OXIDE (SARA 313) (CERCLA) (ZN)
CAS:1314-13-2
RTECS #:ZH4810000
Fraction by Wt: 0.25%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:ALUMINUM (SARA 313) (AL)
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: REMAINT
Other REC Limits:NONE RECOMMENDED
OSH
A PEL:15 MG/M3 DUST
ACGIH TLV:10 MG/M3 DUST; 9596

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EXPO TO DUST/WELDING
FUME/GAS:SHORT-TERM-METALLIC TASTE,NAU,TIGHTNESS OF
CHEST,FEVER,IRRIT EYE/NOSE/THROAT/SKIN,UNCONSC/DEATH DUE TO WELDING
GAS/LACK OF OXY.LONG-TERM-ADVERSE EFFECTS FRM LONGTERM WELD
FUME/GAS/DUST EXPO,SKIN SENS,NEUROLOGICAL DMG,RESP
DISEASE(BRONCHIAL ASTHMA,LUNG FIBROSIS,PNEUMOCONOSIS).
Explanation of Carcinogenicity:PER MSDS:CR MUST BE CONSIDERED POSSIBLE
CARC UNDER OSHA,IARC.
Effects of Overexposure:EXPO TO DUST/WELDING
FUME/GAS:SHORT-TERM-METALLIC TASTE,NAU,TIGHTNESS OF
CHEST,FEVER,IRRIT EYE/NOSE/THROAT/SKIN,UNCONSC/DEATH DUE TO WELDING
GAS/LACK OF OXY.LONG-TERM-ADVERSE EFFECTS FRM LONGTERM WELD
FUME/GAS/DUST E

XPO,SKIN SENS,NEUROLOGICAL DMG,RESP
DISEASE(BRONCHIAL ASTHMA,LUNG FIBROSIS,PNEUMOCONOSIS).
Medical Cond Aggravated by Exposure:AGGRAVATION OF PRE-EXISTING
RESPIRATORY OR ALLERGIC CONDITIONS MAY OCCUR IN OSME WORKERS.

===== First Aid Measures =====

First Aid:REMOVE FROM EXPO & OBTAIN PROMPT MED ATTN.IF VICTIM IS
UNCONSCIOUS ADMINISTER OXYGEN.IF NOT BREATHING RESUSCITATE IMMED.

===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE
Autoignition Temp:Autoignition Temp Text:NP
Lower Limits:NP
Upper Limits:NP
Extinguishing Media:NONE SPECIFIED BY MANUFACTURER.
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.
Unusual Fire/Explosion Hazard:WELDING ARC/SPARKS CAN IGNITE
COMBUSTIBLES.REFER:AMER NAT STD Z49.1 FOR PREVENTION/PROTECTION
INFO DURING USE OF WELDING/RELATED PROCEDURES.

===== Accidental Release Measures =====

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:READ/UNDERSTAND MFG
INSTRUCTIONS/PRECAUTION LABEL ON PROD.SEE AMER NAT STD Z49.1 & OSHA
29CFR1910 FOR MORE DETAIL INFO ON VENTILATION,RESP PROT,EYE/SKIN PROT.
Other Precautions:DETERMINE ACTUAL EXPOSURE BY INDUSTRIAL HYG MONITORING.
AT MIN INCLUDE WELDERS GLOVES,PROTECTIVE FACESHIELD,MAY INCLUDE ARM
PROTECTORS,APRONS,HATS,SHOULDER PROTECTION AS WELL AS DARK
SUBSTANTIAL CLOTHING.
G.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED
RESPIRATION WHEN WELDING IN CONFINED SPACE OR WHEN LOCAL EXHAUST OR
VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.
Ventilation:USE ENOUGH VENTILATION,LOCAL EXHAUST @ARC OR BOTH TO KEEP FUMES/GAS
BELOW TLV IN WORKER BREATH ZONE/GENERAL AREA.TRAIN WELDER KEEP (SUPP)
Protective Gloves:WELD GLOVES(MIN)
Eye Protection:HELMET,FACESHIELD W/FILTER LENS SHADE #10/DK
Other Protection

ctive Equipment:PROTECTIVE SCREEN/FALSH GOGG IF NECESSARY TO
SHIELD OTHERS.HAND/HEAD/BODY PROT-PREVENT RADIATION/SPARK/ELECT
SHOCK INJUR

Work Hygienic Practices:TRAIN WELDER NOT TOUCH LIVE ELECTRICAL PARTS &
TO INSULATE HIMSELF FRM WORK/GROUND.

Supplemental Safety and Health

DECOMPO PROD:OXIDES OF METALS,CHROMATES,FLUORIDES,COMPLEX METALLIC.GAS
MAY INCLUDE CO,OZONE,OXIDES OF NITROGEN.CHLORINATED SOLVTS MAY BE
DECOMPO BY ARC INTO TOXIC GASES(PHOSGENE).MAY ALSO FIND COBALT,

CU,IRON OXIDE,SILICON,MG,AL,MN,MO,TI,ZNFUMES/OXIDES. VENTI:HEAD OUT
OF FUMES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NP

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:NP

Vapor Density:NP

Spec Gravity:NP

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NP

Solubility in Water:NP

Appearance and Odor:SOLID METALS SHAPED AS WIRE OF VARIOUS DIAMETERS

Percent Volatiles by Volume:NP

Corrosion Rate:NP

=====

==== Stability and Reactivity Data =====

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CANT BE CLASSIFIED SIMPLY.COMPO/QUANT
DEPEND ON METAL BEING WELD,PROCESS,PROCEDURES,ELECTRODES USED.MAY
INCLUDE (SUPPLE)

===== Disposal Considerations =====

Waste Disposal Methods:NONE SPECIFIED BY MANUFACTURER.

=====

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.