

SAFT AMERICA INC, POWER SOURCES DIV -- NICKEL CADMIUM AIRCRAFT BATTERY --
6140-00-881-6887

===== Product Identification =====

Product ID:NICKEL CADMIUM AIRCRAFT BATTERY

MSDS Date:12/01/1991

FSC:6140

NIIN:00-881-6887

MSDS Number: CFYYD

=== Responsible Party ===

Company Name:SAFT AMERICA INC, POWER SOURCES DIV

Address:711 INDUSTRIAL BLVD

City:VALDOSTA

State:GA

ZIP:31603

Country:US

Info Phone Num:91

2-247-2331

Emergency Phone Num:912-247-2331/800-424-9300(CHEMTREC)

CAGE:09052

=== Contractor Identification ===

Company Name:BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA

ZIP:23324

Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name:SAFT AMERICA INC.

Address:711 INDUSTRIAL BLVD

Box:1886

City:VALDOSTA

State:GA

ZIP:31602

Country:US

Phone:912-247-2331

CAGE:09052

===== Composition/Information on Ingredients =====

Ingred Name:NICKEL OXIDE

CAS:1313-9

9-1

RTECS #:QR8400000

Fraction by Wt: 18%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3 AS NI

ACGIH TLV:1 MG/M3 AS NI

Ingred Name:POTASSIUM HYDROXIDE (CERCLA) (30% SOLUTION)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: 19%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CADMIUM OXIDE (SARA 302/313) (CERCLA)

CAS:1306-19-0

RTECS #:EV1925000

Fraction by Wt: 13%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0

.2 MG (CD)/M3 DUST

ACGIH TLV:0.01 MG(CD)/M3; 9596

Ingred Name:COPPER (SARA 313) (CERCLA)

CAS:7440-50-8

RTECS #:GL5325000

Fraction by Wt: 9%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.2 MG/M3 FUME; 9596

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NYLON 11

CAS:25587-80-8

Fraction by Wt: 15%

Other REC Limits:NONE RECOMMENDED

==== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT GIVEN

Routes of En

try: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY & GI TRACTS. ACUTE- ELECTROLYTE IS CORROSIVE. INHALE:MIST MAY CAUSE SEVERE IRRITATION OF RESPIRATORY TRACT. EYE:MAY CAUSE PERMANENT BLINDNESS. SKIN: CAUSES BURNS, SENSITIZATION. ORAL:CAUSES TISSUE DAMAGE TO THROAT AREA & GI TRACT. CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:CONTAINS CADMIUM [7440-43-9] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. CONTAINS NICKEL.

Effects of Overexposure:IF LEAKING OR INCINERATED: IRRITATION, BURNS, CHEST PAIN, COUGHING, SWEATING, CHILLS, SHORTNESS OF BREATH, WEAKNESS, BLINDNESS

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.

EYES:FLUSH WITH WATER FOR 15

MINUTES, HOLDING EYELIDS OPEN. SEE DOCTOR. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS,RINSE MOUTH WITH WATER & DRINK 1-2 GLASSES OF WATER/MILK. SEEK IMMEDIATE MEDICAL ATTENTION. IF SPONTANEOUS VOMITING OCCURS, MONITOR FOR BREATHING DIFFICULTY.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:CARBON DIOXIDE, SAND. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS TO AVOID BREATHING TOXIC FUMES. WEAR PROTECTIVE CLOTHING AND EQUIPMENT TO PREVENT POTENTIAL BODY CONTACT WITH ELECTROLYTE

Unusual Fire/Explosion Hazard:ELECTROLYTE WILL REACT VIOLENTLY WITH MANY ORGANIC CHEMICALS. CADMIUM FUMES MAY BE RELEASED WHEN BATTERIES ARE SUBJECTED TO HIGH TEMPERATURES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:BATTERY AND CELL CASES W

ILL NORMALLY CONTAIN

MATERIALS OF CONCERN. USE INDUSTRIAL ABSORBENT TO COLLECT LIQUID POTASSIUM HYDROXIDE. WEAR GLOVES. NEUTRALIZE WITH CITRIC ACID.

Neutralizing Agent:CITRIC ACID

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE MATERIALS. AVOID BREAKING, CRUSHING OR OTHERWISE DESTROYING THE PHYSICAL INTEGRITY OF THE CELL OR BATTERY.

Other Precautions:DO NOT INCINERATE. DO NOT TOUCH BROKEN OR LEAKING

BATTERIES. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING FUMES OR DUST. KEEP OUT OF REACH OF SMALL CHILDREN. DO NOT TRANSPORT BATTERIES WITHOUT VENT CAP IN PLACE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED MIST OR DUST MASK WHEN HANDLING THE LIQUID IN THE BATTERY. WEAR RESPIRATORY PROTECTION IF TLV EXCEEDED.

Ventilation:USE ADEQUATE LOCAL EXHAUST VENTILATION WHEN HANDLING THE LIQUID IN THE BATTERY OR FUMES PRESENT.

Protective Gloves:NEOPRENE, NITRILE FOR LEAKERS

Eye Protection:SAFETY GOGGLES FOR LEAKERS

Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:B1

Spec Gravity:1.250-1.30

Solubility in Water:ELECTROLYTE-SOLUBLE

Appearance and Odor:BATTERY; NO ODOR. 3.6 VOLTS, 2 TERMINALS, 3 CELLS.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ELECTROLYTE WILL REACT WITH ALUMINUM, ZINC, TIN, ACIDS, CHLORINATED AND AROMATIC HYDROCARBONS, NITROCARBONS, HALOCARBON.

Stability Condition to Avoid:EXCESSIVE HEAT, FIRE. DO NOT ADD SULFURIC ACID.

Hazardous Decomposition Products:POTASSIUM HYDROXIDE, TOXIC FUMES OF CADMIUM, CADMIUM OXIDE AND NICKEL

L OXIDE

===== Disposal Considerations =====

Waste Disposal Methods:CELLS AND BATTERIES MAY BE RETURNED AT SENDERS EXPENSE TO A PERMITTED TREATMENT, STORAGE, DISPOSAL FACILITY (TSDf). DISPOSAL MUST BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAW S AND REGULATIONS. MAY BE SENT TO SAFT TO RECYCLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.