

GENERAL ELECTRIC CO -- SILICONE RUBBER SEALANT -- 8040-00-181-8380

===== Product Identification =====

Product ID:SILICONE RUBBER SEALANT

MSDS Date:02/12/1993

FSC:8040

NIIN:00-181-8380

Kit Part:Y

MSDS Number: CGFBC

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO

Address:3135 EASTON TURNPIKE

City:FAIRFIELD

State:CT

ZIP:06431

Country:US

Info Phone Num:203-254-5400

Emergency Phone Num:203-

254-5400

Preparer's Name:D. A. POLSINELLI

CAGE:0D426

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC COMPANY

Address:3135 EASTON TURNPIKE

Box:City:FAIRFIELD

State:CT

ZIP:06431

Country:US

Phone:203-254-5400

CAGE:0D426

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYLSILOXANE SILANOL/STPD (LD50 >40000 MG/KG ORAL
RAT, LC50> 535 MG/L 4 HR INHAL RAT)

CAS:70131-67-8

Fraction by Wt: 60-80%

Other REC Limits:NONE RECOMMENDED

Ingred Name:M

ETHYLTRIACETOXYSILANE (ORAL LD50 2060 MG/KG RAT)

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 1-5.0%

Other REC Limits:10 PPM RECOMMENDED

Ingred Name:TRADE SECRET COMPONENT (NON-HAZARDOUS INGREDIENTS) (ORAL
LD50 >40000 MG/KG RAT ESTIMATED INHAL LC50 >535 MG/L ESTIMATED

Fraction by Wt: 10-30.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

Ingred Name:TRADE SECRET COMPONENT (NON-HAZARDOUS INGREDIENTS)

Fraction by Wt: 10-30.0%

Other REC Limits:NONE RECOMMEN

DED

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:VOC = 65 G/L

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGEST: HARMFUL. SKIN: IRRITATION.

INHAL: IRRITATION. EYE: IRRITATION.

=====
===== First Aid Measures =

=====

First Aid:INGEST: RINSE MOUTH W/WATER SEVERAL TIMES. SKIN: REMOVE
COMPLETELY W/DRY CLOTH OR PAPER TOWEL. WASH W/DETERGENT & WATER,
GET IMMED MED AID. EYE: IMMED FLUSH W/PLENTY OF WATER FOR >15
MINUTES, GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point:NA

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE/SCRAPE/S

OAK UP ON ABSORBENT.

CONTAINERIZE. WASH W/DETERGENT/WATER. WEAR PROPER PROTECTIVE EQUIPMENT. INCREASE AREA VENTILATION.

=====
===== Handling and Storage =====

Handling and Storage Precautions:REMOVE CONTACTS BEFORE USE. RESIDUAL SEALANT MAY REMAIN ON FINGERS FOR SEVERAL DAYS.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:YES

Protective Gloves:CLOTH.

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH FOU

NTAIN

Supplemental Safety and Health

MORE INFORMATION ON FILE

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Spec Gravity:1.06

pH:NA

Evaporation Rate & Reference: