

GRIGGS PAINT -- MIL-L-81352, #17038 GLOSS BLACK, #700B10 -- 8010-00-935-7078

=====
Product Identification
=====

Product ID:MIL-L-81352, #17038 GLOSS BLACK, #700B10

MSDS Date:12/15/1995

FSC:8010

NIIN:00-935-7078

MSDS Number: CGFCQ

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:

800-424-9300 CHEMTREC

Preparer's Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

=====
Composition/Information on Ingredients
=====

Ingred Name:VOC = 4.81 LB/GL (413 G/L)

RTECS #:9999999VO

Fraction by Wt: NA

Other REC

Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:XYLENE (SARA 313) (CERCLA) (VP = 5.1 @ 68F)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 41.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYLENE GLYCOL MONOBUTYL ETHER (SARA 313) (VP = 0.6 @ 68F)
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 13.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:75 PPM

Ingred Name:ME
THYL ISOBUTYL KETONE (SARA 313) (CERCLA) (VP = 16.0 @
68F)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 7.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:75 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL METHACRYLATE (SARA 313) (CERCLA)
CAS:80-62-6
RTECS #:OZ5075000
Fraction by Wt: 35.0%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalat

IN
CONFINED AREAS, TANKS OR PITS WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MSHA/NIOSH APPROVED UNITS. USE UNITS PER CURRENT 29 CFR 1910.134 REGULATIONS & FOLLOW MANUFACTURERS' INSTRUCTIONS & WARNINGS. AIR PURIFYING OV/FILTER UNITS MAY BE ACCEPTABLE.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves:RUBBER GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective E

quipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSON HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:260 TO 336F

Decomp Temp:Decomp Text:NA

Vapor Density:>AIR

Spec Gravity:0.9

pH:NA

Viscosity:16-22 #3 FC

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:ESSENTIALLY NIL

Appearance and Odor:VISCOUS LI

QUID WITH STRONG SOLVENT ODOR

Percent Volatiles by Volume:68.39

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:IGNITION SOURCES.

Hazardous Decomposition Products:CO & CO2.

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIAL ON SPILLS. DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.