

GENERAL SEALANTS INCORPORATED -- GS #424 (MIL-S-11030E, TYPE III) -- 8030-00-965-2438

=====
Product Identification
=====

Product ID:GS #424 (MIL-S-11030E, TYPE III)

MSDS Date:10/22/1990

FSC:8030

NIIN:00-965-2438

MSDS Number: CGFCV

=== Responsible Party ===

Company Name:GENERAL SEALANTS INCORPORATED

Address:300 SOUTH TURNBULL CANYON ROAD

City:CITY OF INDUSTRY,

State:CA

ZIP:91745

Country:US

Info Ph

one Num:818-961-0211

Emergency Phone Num:818-961-0211

CAGE:53992

=== Contractor Identification ===

Company Name:GENERAL SEALANTS INC

Address:300 S TURNBULL CANYON RD

Box:3855

City:CITY OF INDUSTRY

State:CA

ZIP:91744

Country:US

Phone:818-961-0211

CAGE:53992

=====
Composition/Information on Ingredients
=====

Ingred Name:CHLORINATED PARAFFINS

CAS:68920-70-7

RTECS #:UZ2996400

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SOLID MATERIAL MAY BURN AT OR ABOVE
FLASH POINT. CONCENTRATED AIRBORNE DUST MAY CAUSE IRRITATION TO
BREATHING IN SENSITIVE INDIVIDUALS.
Medical Cond Aggravated by Exposure:NA

===== First Aid Measures =====

First Aid:NA

===== Fire Fighting Measures =====

Flas
h Point:800F,427C
Extinguishing Media:WATER, CARBON DIOXIDE.
Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED
CONTAINERS & TO PROTECT PERSONNEL. RESPIRATORY/EYE PROTECTION
REQUIRED.
Unusual Fire/Explosion Hazard:NON-EXPLOSIVE, BUT MAY PRODUCE CO, &
IRRITATING SMOKE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITS. STOP LEAK IF SAFE. NOTIFY
AUTHORITIES IF APPROPRIATE.

===== Handling and
Storage =====

Handling and Storage Precautions:STORE AT 72F.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NA
Ventilation:NA
Protective Gloves:USE WHEN MATERIAL IS HOT.
Eye Protection:NONE
Other Protective Equipment:NONE
Work Hygienic Practices:NONE
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:SOLID.
Melt/Freeze Pt:M.P/F.P Text:

230F,110C

Vapor Pres:SOLID.

Vapor Density: