View NSN Online: https://aerobasegroup.kr/nsn/8010-01-333-9826

Product ID:TT-E-2784A MSDS Date:09/15/1997 FSC:8010 NIIN:01-333-9826 MSDS Number: CGFFR === Responsible Party === **Company Name: DURANT PAINT** Address:960 BROADWAY City:REVERE State:MA ZIP:02051 Country:US Info Phone Num:617-289-1400 Emergency Phone Num:617-289-1400 CAGE:NO367 === Contractor Identification === Company N ame:DURANT PAINT Address:950 BROADWAY Box:City:REVERE State:MA ZIP:02051 Country:US Phone:617-289-1400 CAGE:NO367 Company Name: DURANT PAINTS INC Address:112 RAILROAD ST Box:City:REVERE State:MA ZIP:02151-4007 Country:US Phone:781-289-8415 CAGE:3F338

Ingred Name:GLYCOL ETHER (VAPOR PRESSURE 25%) CAS:111-77-3 RTECS #:KL6125000 Fraction by Wt: 7.20% Other REC Limits:NONE RECOMMENDED

Ingred Name: GLYCOL ETHER (VAPOR PRESSURE 0.1%

) CAS:770-35-4 Fraction by Wt: 1.30% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION. INHAL: IRRITATING TO NOSE/THROAT. INGEST: TOXIC. Effects of Overexposure:INHAL: HEADACHE, NAUSEA, VOMITING, DROWSINESS. Medical Cond Aggravated by Exposure:HEART CONDITIONS, AS THMA.

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES. INHAL: GET FRESH AIR. OXYGEN IF NEEDED. INGEST: GIVE TWO GLASSES OF WATER. INDUCE VOMIT.

Flash Point:NONFLAMMABLE Extinguishing Media:CO2, FOAM. Fire Fighting Procedures:USE FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:COOL CONTA INERS W/WATER STEAM IN EVENT OF A FIRE.

| Spill Release | Procedures:DIKE & | CONTAIN. | SOAK UP | RESIDUE V | N/ABSORBE | INT |
|---------------|-------------------|----------|---------|------------------|-----------|-----|
| MATERIAL | | | | | | |

| Handling and Storage | Precautions: STORE IN A COOL, | DRY PLACE. | PROTECT |
|----------------------|-------------------------------|------------|---------|
| FROM FREEZING. | | | |

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:REQUIRED. Ventilation:REQUIRED. Protective Gloves:RE QUIRED. Eye Protection:REQUIRED. Other Protective Equipment:APRON. Work Hygienic Practices:WASH AFTER HANDLING. Supplemental Safety and Health NK

| | Ph | ysical/Chemical | Pro | perties | |
|--|----|-----------------|-----|---------|--|
|--|----|-----------------|-----|---------|--|

Boiling Pt:B.P. Text:212F,156C Vapor Density:>AIR VOC Pounds/Gallon:1 Evaporation Rate & amp; Reference:VALUE NOT STATED Solubility in Water:100% Percent Volatiles by Volume:58.9

Stability Indicator/Materials to Av oid:YES OXIDIZING MATERIALS. Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME. Hazardous Decomposition Products:CARBON MONOXIDE & UNIDENTIFIED ORGANIC COMPOUNDS.

Waste Disposal Methods: DISPOSE OF IN RECKA APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.