

EASTMAN KODAK COMPANY -- 196 5482 FLEXICOLOR STABILIZER III & REPLENISHER
CONCENTRATE -- 6750-01-035-9180

===== Product Identification =====

Product ID:196 5482 FLEXICOLOR STABILIZER III & REPLENISHER CONCENTRATE

MSDS Date:11/07/1997

FSC:6750

NIIN:01-035-9180

Kit Part:Y

MSDS Number: CGMHP

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 80-85%
Other REC Limits:NONE RECOMMENDED

Ingred Name:FORMALDEHYDE (SARA 302/313) (CERCLA)
CAS:50-00-0
RTECS #:LP8925000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1048
ACGIH TLV:C 0.3 PPM, A2; 9596
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 200 PPM
ACGIH TLV:S,200PPM/250STEL; 96
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ANIONIC SURFACTANT, NEW JERSEY TRADE SECRET: 80100185-5062P
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ANIONIC SURFACTANT, NEW JERSEY TRADE SECRET: 80100185-5059P
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY M

ANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:INHALATION MAY PRODUCE EXPOSURE TO FORMALDEHYDE WHICH MAY CAUSE RESPIRATORY SENSITIZATION OR AGGRAVATE PRE-EXISTING ASTHMATIC CONDITIONS. CAUSES SKIN AND EYE IRRITATION, MAY CAUSE ALLERGIC SKIN REACTI ON. HARMFUL IF SWALLOWED, MAY CAUSE IRRITATION OF THE GI TRACT.

Explanation of Carcinogenicity:CONTAINS F [50-00-0] W
HIGH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALED-RESPIRATORY IRRITATION/SENSITIZATION.
EYES-IRRITATION, TEARING. SKIN-IRRITATION, ALLERGIC SKIN REACTION.
INGESTED-IRRITATION OF GI TRACT.

Medical Cond Aggravated by Exposure:PRE-EXISTING ASTHMATIC CONDITIONS.

=====
First Aid Measures
=====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING.WASH WITH WATER.GET MEDICAL ATTENTION IF IRRITATION PERSIS

TS.EYES:IMMEDIATELY FLUSH WITH WATER

FOR 15 MINUTES.CALL PHYSICIAN.INHALED:REMOVE TO FRESH AIR.TREAT SYMTOMA TICALLY.INGEST:DO NOT INDUCE VOMITING.IF CONSCIOUS,GIVE GLASS OF WATER.CALL A PHYSICIAN OR POISON CONTROL CENTER.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NP

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED B
REATHING APPARATUS &

PROTECTIVE CLOTHING. FIRE AND EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE.

=====
Accidental Release Measures
=====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAM INATION.

Neutralizing Agent:NONE SPE

CIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM INCOMPATIBLE MATERIALS. USE ONLY WITH ADEQUATE VENTILATION.

Other Precautions:WASH THOROUGHLY AFTER HANDLING. DO NOT BREATH VAPOR. DO NOT GET IN EYES, ON SKIN, ON CLOTHES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:A FULL FACEPEICE WITH CARTRIDGES OR CANISTERS

SPECIFICALLY APPROVED BY NIOSH FOR PROTECTION AGAINST FORMALDEHYDE OR A TYPE C SUPPLIED AIR RESPIRATOR OR AN APPROPRIATE NIOSH APPROVED RESPIRATOR FOR ORG ANIC VAPORS SHOULD BE WORN IF NEEDED.

Ventilation:LOCAL EXHAUST VENTILATION OR AN ENCLOSED HANDLING SYSTEM MAY BE NEEDED TO CONTROL AIR CONTAMINANTS.

Protective Gloves:NITRILE OR NEOPRENE.

Eye Protection:GOGGLE AND FACE SHIELD.

Other Protective Equipment:USE CHEMICAL PROTECTIVE CLOTHING MADE MATERIAL IMPERVIOUS TO FORMALDEHYDE AND THE USE OF OTHER PROTECTIVE CLOTHING.

Work Hygienic Practices:THE ROUTINE USE OF A NON-ALKALINE (ACID) TYPE OF SKIN CLEANER & REGULAR CLEANING OF WORKING SURFACE.

Supplemental Safety and Health

KEY1=N1. MSDS IS FOR CONCENTRATE. MAKES 5 GALLONS WORKING SOLUTION WHEN MIXED WITH WATER (PNI X). PNI A, B, W WERE ERRONEOUSLY ADDED TO HMIS (CATALOGUE NUMBER OR P/N TRADE NAME DO NOT MATCH WHAT IS IN KODAK CATALOGUE FOR THIS NSN); HOPEFULLY IT WILL NOT BE TO LONG

BEFORE THEY ARE CONVERTED TO A LIIN.

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>205F,>96C

Vapor Pres:18 @20C

Vapor Density:0.6

Spec Gravity:1.02

pH:6.0

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID, COLORLESS, FORMALDEHYDE ODOR.

Percent Volatiles by Volume:80-85

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoi

d:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
OXIDES OF NITROGEN, FORMALDEHYDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE BY INCINERATION OR CONTACT A LICENSED
CHEMICAL WASTE DISPOSAL AGENCY. DISCHARGE MAY BE SUBJECT TO
LOCAL,STATE, FEDERAL LAWS. EMPTY CONTAINERS RETAIN PRODUCT RESIDUE,
FOLLOW LABEL WARNINGS EVEN AFTER
CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to t
heir
particular situation.