View NSN Online: https://aerobasegroup.kr/nsn/5970-01-339-7511

DOW CORNING CORP -- 3110 RTV SILICONE RUBBER ENCAPSULANT -- 5970-01-339-7511

Product ID:3110 RTV SILICONE RUBBER ENCAPSULANT

MSDS Date:08/02/1996

FSC:5970

NIIN:01-339-7511

Kit Part:Y

MSDS Number: CGMLG === Responsible Party ===

Company Name: DOW CORNING CORP

Address:3901 S. SAGINAW RD

Box:997

City:MIDLAND

State:MI ZIP:48686 Country:US

Info Phone Num:517-496-6000

Ε

mergency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name: DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name: DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI ZIP:48611 Country:US

Phone:517-496-4388

CAGE:71984

Company Name: RUEBEN BURTON INC

Box:UNKNOW CAGE:2V475

====== Composition/Information on Ingredients ========

Ingred Name

:ALUMINA HYDRATE Fraction by Wt: 7% Other REC Limits:NONE RECOMMENDED

Ingred Name: TETRAPROPYL SILICATE

CAS:682-01-9 Fraction by Wt: 3%

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ================

LD50 LC50 Mixture: NOT GIVEN FOR PRODUCT AS A WHOLE

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:DIRECT EYE CONTACT IRRITATES SLIGHTLY.

A SINGLE SHORT EXPOSURE T

O SKIN CAUSES NO KNOWN ADVERSE EFFECT.

SEVERAL PROLONGED OR REPEATED EXPOSURES MAY IRRITATE.. IRRITATES RESPIRATORY PASSAGES AND EYES SL IGHTLY. SMALL AMOUNTS TRANSFERRED TO THE MOUTH SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY CAUSE DISCOMFORT.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE REDNESS, EYE SWELLING, SKIN IRRITATION, RES

PIRATORY TRACT IRRITATION, EYE IRRITATION, DIGESTIVE DISCOMFORT. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: NO FIRST AID SHOULD BE REQUIRED. INHALATION: NO FIRST AID SHOULD BE REQUIRED. INGESTION: NO F IRST AID SHOULD BE REQUIRED. TREAT ACCORDING TO PERSON'S CONDITION AN

D SPECIFICS OF EXPOSURE.

========= Fire Fighting Measures ==============

Flash Point Method:CC Flash Point:>212F,>100C Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN

Extinguishing Media:WATER, WATER FOG (OR SPRAY), CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.

==========

	-		
 Accidental	Ralasca	Maggurae	===========

Spill Release Procedures:MOP UP OR WIPE UP OR SOAK UP WITH ABSORBENT AND CONTAIN FOR SALVAGE OR DISPOSAL. CLEAN ANY REMAINING SLIPPERY SURFACES BY APPROPRIATE TECHNIQUES: SUCH AS MOPPING OR SWABBING WITH APPROPRIATE SOLVENTS; WASHING WITH MILD, CAUSTIC DETERGENTS OR SOLUTION

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

============= Handling and Storage ==========================

Handling and Storage Precautions :KEEP CONTAINER CLOSED AND STORE AWAY FROM WATER OR MOISTURE.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

====== Exposure Controls/Personal Protection =========

Respiratory Protection: NONE REQUIRED UNDER NORMAL CONDITIONS Ventilation: LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN EXPOSURE LEVELS.

Protective Gloves: WASHING AT END OF SHIFT ADEQUATE.

Eve Protection: NONE REQUIRED UNDER NORMAL CONDITIONS

Other Protective Equipment: AN EMERGENCY

EYEWASH AND SHOWER SHOULD BE

AVAILABLE.

Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

N-PROPYL ALCOHOL IS FORMED UPON CONTACT WITH WATER OR HUMID AIR. PROVIDE ADEQUATE VENTILATION TO CONTROL EXPOSURES WITH GUIDELINES OF OSHA PEL.

======== Physical/Chemical Properties ==========

HCC:N1

Boiling Pt:B.P. Text:NOT GIVEN Melt/Freeze Pt:M.P/F.P Text:NOT G

IVEN

Vapor Pres:NOT GIVEN Vapor Density:NOT GIVEN

Spec Gravity:1.14

Evaporation Rate & Evaporation R

Solubility in Water: NOT GIVEN

Appearance and Odor:OFF-WHITE, VISCOUS LIQUID

======== Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS

Stability Condition to Avoid:WATER, MOISTURE, OR HUMID AIR CAN CAUSE HAZARDOUS VAPORS TO FORM.

Hazardous Decomposition Products: CARBON OXIDES, TRACES OF INCOMPLETELY BURNED

CARBON COMPOUNDS, SILICON DIOXIDE, FORMALDEHYDE, QUARTZ, METAL OXIDES.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSAL OF COLLECTED PRODUCT, RESIDUE AND CLEANUP MATERIALS MAY BE GOVERNMENTALLY REGULATED. OBSERVE ALL APPLICABLE LOCAL, STATE AND FEDERAL WASTE MANAGEMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defe

nse. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.