

NEO-FLO,INC,MICROCOPY DIV -- INSTA-FIX FIXER -- 6525-01-125-6593

===== Product Identification =====

Product ID:INSTA-FIX FIXER

MSDS Date:07/08/1993

FSC:6525

NIIN:01-125-6593

Kit Part:Y

MSDS Number: CGMXH

=== Responsible Party ===

Company Name:NEO-FLO,INC,MICROCOPY DIV

Address:3120 MOON STATION ROAD

Box:2017

City:KENNESAW

State:GA

ZIP:30144

Country:US

Info Phone Num:800-235-1863, 404-425-5715

Emerg

ency Phone Num:770-425-5715

Preparer's Name:GORDON LAPEAN

CAGE:MO994

=== Contractor Identification ===

Company Name:MICROCOPY-DIVISION OF NEO-FLO, INC.

Address:3120 MOON STATION ROAD

Box:City:KENNESAW

State:GA

ZIP:30144

Country:US

Phone:404-425-5715

CAGE:63763

Company Name:NEO-FLO,INC,MICROCOPY DIV

Address:3120 MOON STATION ROAD

Box:2017

City:KENNESAW

State:GA

ZIP:30144

Country:US

Phone:800-235-1863, 404-425-5715

CAGE:MO994

===== Composition/Information on Ingredients =====

I

ngred Name:SODIUM SULFITE  
CAS:7757-83-7  
RTECS #:WE2150000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE  
CAS:7783-18-8  
RTECS #:XN6465000  
Fraction by Wt: 25-30%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM METABISULFITE  
CAS:7681-57-4  
RTECS #:UX8225000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9596

Ingred Name:BORAX  
CAS:1303-96-4  
RTECS #:VZ2275000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMEN  
DED  
OSHA PEL:10 MG/M3  
ACGIH TLV:5 MG/M3; 9596

Ingred Name:ACETIC ACID, GLACIAL (CERCLA)  
CAS:64-19-7  
RTECS #:AF1225000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 PPM  
ACGIH TLV:10 PPM/15 STEL; 9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ALUMINUM SULFATE  
CAS:10043-01-3  
RTECS #:BD1700000  
Fraction by Wt: 93C  
Extinguishing Media:USE APPROPRIATE AGENT FOR SURROUNDING FIRE.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA  
AND FULL PROTECT

IVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE  
WATER SPRAY TO COOL CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE PRODUCTION OF  
SULFUR DIOXIDE VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP SPILL WITH ABSORBENT OR USE A  
COMMERCIAL AVAILABLE CHEMICAL SPILL KIT.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handli  
ng and Storage Precautions:STORE IN SEALED CONTAINERS IN A COOL,  
DRY, WELL VENTILATED AREA. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.  
Other Precautions:DO NOT STORE FOOD, DRINK, OR TOBACCO IN AREAS WITH  
THIS PRODUCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION  
CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGHER THAN APPROVED  
EXPOSURE, USE AN APPROPRIATE NIOSH ORGANIC ACID VAPOR RESPIRATOR.  
Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.  
LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.  
Protective Gloves:WEAR LATEX OR NEOPRENE GLOVES.  
Eye Protection:SAFETY CHEMICAL GOGGLES RECOMMENDED.  
Other Protective Equipment:PROVIDE EYE WASH STATION AND SAFETY SHOWER.  
WEAR INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.  
Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,  
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Su  
pplemental Safety and Health  
KEY1:N1. THIS ENTRY DESCRIBES PART A OF A X-RAY FILM CHAMBER. SEE THIS  
SAME NSN, P/N IND B, FOR PART B DATA. KIT ALSO INCLUDES A MANUAL  
TABLE TOP DARKROOM.

===== Physical/Chemical Properties =====

HCC:N1  
Boiling Pt:B.P. Text:220F,104C  
Vapor Pres:16  
Vapor Density: