View NSN Online: https://aerobasegroup.com/nsn/8030-00-555-2878

THOMPSON & FORMBY INC. -- THOMPSON'S WATERSEAL BRAND WATERPROOFING FORMULA -- 8030-00-555-2878

Product ID: THOMPSON'S WATERSEAL BRAND WATERPROOFING FORMULA MSDS Date:06/23/1991 FSC:8030 NIIN:00-555-2878 MSDS Number: CGNFV === Responsible Party === Company Name: THOMPSON & FORMBY INC. Address:10136 MAGNOLIA DRIVE **City:OLIVE BRANCH** State:MS ZIP:38654 Country:US Info Phone Num:601-895-5594 Emergency Phone Num:901-685-7555 CAGE:THOMP === Contractor Identification === Company Name: THOMPSON & FORMBY INC. Address:10136 MAGNOLIA DRIVE **City:OLIVE BRANCH** State:MS ZIP:38654 Country:US Phone:901-685-7555 OR 714-864-2310 CAGE:THOMP Ingred Name: ALIPHATIC PETROLEUM DISTILLATE (MINERAL SPIRITS) CAS:64742-88-7 Fraction by Wt: 85.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM ACGIH TLV:100 PPM Ingred Name:VOC = 680 G/L LESS WATER RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRIT, REDNESS, TEARING, BLURRED VISION. SKIN: IRRIT, DEFATTING, DERMATITIS. INHAL: NASAL AND RESPIRATORY IRRIT, DIZZY, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUS, ASPHYXIATION. INGEST: GI IRRIT, NAUSEA, VOMIT, DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAUSES CHEMICAL PNEUMONITIS, FATAL.

First Aid:EYE: FLUSH W/WATER, LIFTING LIDS. SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES, WASH BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM/QUIET. INGEST: DONT INDUCE VOMIT. KEEP WARM/QUIET. IN ALL CASES, GET MED AID.

Flash Point Method:SCC Flash Point:>101F,>38C Lower Limits:1.0 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:USE SCBA W/FULL FACE PIECE OPERATED IN PRESSURE DEMAND MODE OR OTHER POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO IGNIT SOURCES.

=========== Accidental Release Measures ==========

======

Spill Release Procedures: HANDLE AS COMBUSTIBLE LIQUID. ABSORB ON SAND, CLAY OR OTHER ABSORBENT MATERIAL. ELIMINATE IGNIT SOURCES.

Handling and Storage Precautions: KEEP CONTAINER CLOSED. STORE AWAY FROM HIGH TEMPS & IGNIT SOURCES. USE ONLY W/ADEQUATE VENT. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: GROUND CONTAINERS WHEN POURING & LIMIT FREEFALL TO A FEW INCES TO PREVENT STATIC SPARKS.

=========

=== Exposure Controls/Personal Protection =========

Respiratory Protection: IF TLV IS EXCEEDED, USE NIOSH/MSHA APPROVED RESPIRATOR. Ventilation: USE W/ADEQUATE VENT TO PREVENT EXCEEDING TLV. Protective Gloves: HYDROCARBON/INSOLUBLE RUBBER OR PLASTIC Eye Protection: SAFETY GLASSES OR GOGGLES Supplemental Safety and Health NK

Boiling Pt:B.P. Text:300 TO 430F Vapor Pres:2.0 Vapor Density:4.9 AIR =1 Spec Gravity:.800 H20=1

Evaporation Rate & amp; Reference:70.0 ETHYL ETHER=1 Appearance and Odor:COLORLESS LIQUID, W/PETROLEUM DISTILLATE ODOR. Percent Volatiles by Volume:85%

Stability Indicator/Materials to Avoid:YES OXYGEN AND STRONG OXIDIZERS. Stability Condition to Avoid:KEEP AWAY FROM IGNIT SOURCES. Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE.

Waste Di

sposal Methods:PLACE WASTE IN CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE AND FEDERAL REGULATIONS GOVERNING COMBUSTIBLE WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this docume nt should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.