View NSN Online: https://aerobasegroup.kr/nsn/7930-01-440-0246

Product ID:CLEAN-N-POLISH MSDS Date:03/03/1996 FSC:7930 NIIN:01-440-0246 MSDS Number: CGNQV === Responsible Party === Company Name: WERTH SANITARY SUPPLY COMPANY, INC. Address:1561 PIONEER WAY **City:EL CAJON** State:CA ZIP:92020 Country:US Info Phone Num:800-535-5053 Emergency Phone Num:800-535 -5053 CAGE:5T372 === Contractor Identification === Company Name: WERTH SANITARY SUPPLY CO INC Address:1561 PIONEER WAY Box:City:EL CAJON State:CA ZIP:92020-1637 Country:US Phone:800-535-5053/619-440-2000 CAGE:5T372 Ingred Name:NON-HAZARDOUS INGREDIENTS Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Routes of Entry: Inhalation

:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: PERMANENT DAMAGE, IRRIT. SKIN: IRRIT, DERMATITIS. INHAL: HEADACHE, NAUSEA, IRRIT OF NOSE/THROAT/LUNGS.
Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG DISEASE MAY BE AGGRAVATED.
======================================
First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES. CONTACT LENSES SHOULD BE REMOVED IF INITIAL FLUSH DOESN'T WASH THEM OUT. SKIN: WASH W/SOAP &
WATER. REMOVE CONTAM CLOTHES/SHOES, WASH BEFORE USE. INHAL: REMOVE TO FR ESH AIR. INGEST: DRINK TWO GLASSES OF WATER. IN ALL CASES, GET IMMED MED AID.
======================================
Flash Point Method:SCC Flash Point:>300F,>149C Autoignition Temp:Autoignition Temp Text:NE Lower Limits:NA
Upper Limits:NA Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL FOAM, WATER FOG, CO2. Fire Fighting Procedure
s:AVOID USE OF WATER. Unusual Fire/Explosion Hazard:DENSE SMOKE. FIRE FIGHTERS SHOULD USE SCBA.
======================================
Spill Release Procedures: SPILLS ARE SLIPPERY. ELIMINATE ALL IGNITS. DIKE & CONTAIN W/INERT ABSORBENT MATERIAL. COLLECT FOR DISPOSAL.
======================================

Handling and Storage Precautions:STORE IN A DRY AREA. KEEP CONTAINER TIGHTLY CLOSED. KEEP FROM FREEZING. Other Precauti ons:KEEP AWAY FROM CHILDREN.

Respiratory Protection:USE NIOSH/OSHA APPROVED RESPIRATOR W/ORGANIC VAPOR CARTRIDGE IF VAPOR CONCENTRATION EXCEEDS PERMISSIBLE EXPOSURE LIMITS. Ventilation:LOCAL VENTILATION Protective Gloves:OIL RESISTANT Eye Protection:SAFETY GLASSES Other Protective Equipment:EMERGENCY SAFETY SHOWER & EYE WASH FOUNTAIN NEAR WORK AREA. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:20.0 Vapor Density: