

LHB INDUSTRIES -- SO-SURE YELLOW #13555 (0014-133)

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 00-141-2950
MSDS Date: 10/02/1997
MSDS Num: CGXJQ
Product ID: SO-SURE YELLOW #13555 (0014-133)
MFN: 07
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
63134
Info Phone Number: 314-522-3141
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141
Preparer's Name: ROBIN C. GANNON
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: A-A-665
Unit of Issue: PT
UI Container Qty: 0

=====
Ingredients
=====

=====

Cas: 108-88-3

RTECS #: XS5250000

Name: TOLUENE (SARA 313) (CERCLA)

% Wt: 20.55

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 200 PPM

ACGIH TLV: 100 PPM

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

Cas: 74-98-6

RTECS #: TX2275000

Name: PROPANE

% Wt: 16.72

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 1000 PPM

ACGIH TLV: 1000 PPM

Cas: 67-64-1

RTECS #: AL3150000

Name: ACETONE (SARA 313) (CERCLA)

% Wt: 16.28

Other REC Limits: NONE RE

COMMENDED

OSHA PEL: 1000 PPM

ACGIH TLV: 750 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

Cas: 8032-32-4

RTECS #: OI6180000

Name: VM&P NAPHTHA

% Wt: 14.76

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 300 PPM

ACGIH TLV: 300 PPM

Cas: 106-97-8

RTECS #: EJ4200000

Name: N-BUTANE

% Wt: 5.58

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM

Cas: 8052-41-3

RTECS #: WJ8925000

Name: STO

DDARD SOLVENT

% Wt: 5.51

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM

Cas: 75-28-5

RTECS #: TZ4300000

Name: 2-METHYL PROPANE

% Wt: 4.11

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 800 PPM

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYE: IRRIT. SKIN: IRRIT. INHAL: RESPIRATORY TRACT AND THROAT IRRIT, HEADACHE, NAUSEA, VOMIT, HARMFUL, FATAL, BRAIN/NS DAMAGE, ANESTHETIC, LIGHTHEADED, STAGGERING GAIT, GIDDY, NAUSEA. INGEST: HARMFUL.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS

First Aid: EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER.

WASH CLOTHES BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. ARTIFICIAL RESPIRATION IF NEEDED. INGEST: DONT INDUCE VOMIT. I

N ALL CASES, GET IMMEDIATE MED AID.

=====
Handling and Disposal
=====

Spill Release Procedures: REMOVE IGNIT SOURCES. VENTILATE AREA. MOP SPILL W/INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS. DONT PUNCTURE, INCINERATE OR STORE >120F. EXPOSURE TO HEAT OR SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN TRASH P

ICK-UP. DONT PLACE

IN HOME TRASH COMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CAUTION: CONTENTS UNDER PRESSURE. DONT STORE >120F.

Other Precautions: USE W/GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: -156F,-104C

Autoignition Temp Text: 847F

Lower Limits: 1

.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.
AVOID SPREADING ANY BURNING LIQUID W/WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFCTIVE. USE WATER TO KEEP CONTAINERS COOL. USE SCBA. USE SHIELDING TO PROTECT AGAINST BURSTING, RUPTURING OR VENTING OF CONTAINERS.

Unusual Fire/Explosion Hazard: DONT SPRAY NEAR OPEN FLAME. AT TEMPS >120F CONTAINERS MAY VENT, RUPTURE OR BURST. AEROSOL CONTAINERS: DONT EXPOSE TO TEMPS >120F.

=

=====
Control Measures
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: REQUIRED

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN, EYEWASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DONT EAT, DRINK OR SMOKE WHILE USING PRODUCT.

=====
Physical/Chemical Properties
=====

B.P. Text: NA

M.P/F.P Text: NA

Decomp Text: NA

Vapor Pres: 60 @ 68F

Vapor Density: >1.5

Spec Gravity: 0.752 AEROSOL

PH: NA

VOC Grams/Liter: 493

Viscosity: NA

Solubility in Water: INSOLUBLE

Appearance and Odor: YELLOW PAINT

Corrosion Rate: NA
=====

=====

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT

Materials To Avoid: NA

Hazardous Decomposition Products: CARBON MONOXIDE AND POSSIBLE HYDROCHLORIDE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NA

=====
Toxicological Information

=====
Ecological Information

=====
MSDS Transport Information

=====
Regulatory Information

=====
Other Information

=====
Other Information: VOC = 493 G/L

=====
Transportation Information

Responsible Party Code: 0FTT5

Trans ID NO: 49944

Product ID: SO-SURE YELLOW #13555 (0014-133)

MSDS Prepared Date: 10/02/1997

Review Date: 04/13/1998

MFN: 7

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: PT

Container QTY: 0

=====
Detail DOT Information

=====

=====
DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

=====
Detail IMO Information
=====

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN N
umber: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

=====
Detail IATA Information
=====

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging
Note Cargo: 203
=====

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

=====
HAZCOM Label
=====

=====

Product ID: SO-SURE YELLOW #13555 (0014-133)

Cage: 0FTT5

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 10/12/1999

Status Code: A

Origination Code: G

Hazard And Precautions: EYE: IRRIT. SKIN: IRRIT. INHAL: RESPIRATORY TRACT AND THROAT IRRIT, HEADACHE, NAUSEA, VOMIT, HARMFUL, FATAL, BRAIN/NS DAMAGE, ANESTHETIC, LIGHTHEADED, STAGGERING G AIT, GIDDY, NAUSEA. INGEST: HARMFUL.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.