

PARKER PAINTS -- BROWN #30099 -- 8010-00-598-5462

=====  
===== Product Identification =====

Product ID:BROWN #30099  
MSDS Date:07/16/1997  
FSC:8010  
NIIN:00-598-5462  
MSDS Number: CGXMB  
=== Responsible Party ===  
Company Name:PARKER PAINTS  
Address:3003 SOUTH TACOMA WAY  
Box:11047  
City:TACOMA  
State:WA  
ZIP:98409  
Country:US  
Info Phone Num:206-473-1122  
Emergency Phone Num:800-255-3924  
Preparer's Name:J. BURNWORTH  
CAGE:LO231  
=== Contractor Identification ===  
Company Name:PARKER PAINT  
Address:3003 SOUTH TACOMA WAY  
Box:11047  
City:TACOMA  
State:WA  
ZIP:98409  
Country:US  
Phone:253-473-1122  
CAGE:9H480  
Company Name:PARKER PAINTS  
Address:3003 SOUTH TACOMA WAY  
Box:11047  
City:TACOMA  
State:WA  
ZIP:98409  
Country:US  
Phone:206-473-1122  
CAGE:LO231

=====  
===== Composition/Information on Ingredients =====

Ingred Name:RULE 66 MINERAL SPIRITS (SARA 313) (VP = 2 @ 68F)  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by W

t: 17.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:NAPHTHA, HEAVY ALKYLATE(ODORLESS) (SARA 313) (VP = 2 @ 68F)  
CAS:64741-65-7  
Fraction by Wt: 7.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:AROMATIC HYDROCARBON (SARA 313) (VP = 3 @ 68F)  
CAS:64742-95-6  
Fraction by Wt: 2.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM

Ingred Name:1,2,4 TRIMETHYLBENZENE (SARA 313)  
CAS:95-63-6  
RTECS #:DC3325000  
Fraction by Wt: 0.18  
%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:25 PPM  
ACGIH TLV:25 PPM

Ingred Name:ETHYLBENZENE (SARA 313)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: 0.08%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE: IRRIT, REDN

ESS, TEARING, BLURRED

VISION. SKIN: IRRIT, DERMATITIS. INHAL: HEADACHE, NAUSEA, ASPHYXIATION, UNCONSCIOUS, NS DEPRESSION, NASAL IRRIT, CONFUSION, LIVER/KIDNEY DAMAGE. INGEST: GI IRRIT, NAUSEA, VOMIT, DIARRHEA, CHEMICAL PNEUMONITIS.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES. INHAL: REMOVE TO FRESH AIR. ARTIF RESP IF NEEDED. INGEST: DRINK 1-2 GLASSES OF WATER. DONT INDUCE VOMIT. CALL POISON CONTROL CENTER. IN ALL CASES, GET MEDAID.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:105F,41C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT W/SCBA. USE WATER TO COOL CONTAINERS.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS CLOSED. KEEP FROM IGNITS.

CLOSED CONTAINERS EXPLODE IN HIGH HE

AT. DURING EMERGENCY

CONDITIONS, OVEREXPOSURE TO DECOMP PRODUCTS MAY BE A HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITS. USE PROTECTIVE EQUIPMENT.

CONTAIN AND REMOVE W/INERT ABSORBENT USING NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, WELL VENTED AREA AWAY FROM IGNITS. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMP

LY  
W/OSHA 1910.106.

Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A PROPERLY FITTED NIOSH/MSHA APPROVED VAPOR PARTICULATE RESPIRATOR OR AIR-SUPPLIED RESPIRATOR UNLESS VENT IS ADEQUATE TO KEEP AIRBORNE CONTAM BELOW PEL/TLV LIMITS.

Ventilation:SUFFICIENT VENT IN VOLUME & PATTERN W/EXPOSURE-PROOF EQUIPMENT TO KEEP CONTAM CONCENTRATIONS BELOW PEL/TLV LIMITS.

Protective Gloves:RUBBER OR

NEOPRENE

Eye Protection:CHEMICAL SAFETY GOGGLES/FULL FACE SHEILD

Other Protective Equipment:USE COVERALLS & HOOD DURING SPRAY

APPLICATIONS. PROTECTIVE CREAMS MAY BE USED FOR EASE OF CLEANUP,  
NOT FOR PROTECTION.

Work Hygienic Practices:WASH HANDS BEFORE EATING AND USING RESTROOMS.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:314F,157C

Vapor Density:>AIR

Spec Gravity:1.39 (H2O = 1)

VOC Grams/Liter:3.11

Evapor

ation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INSOLUBLE

Appearance and Odor:COLORED LIQUID, W/ALIPHATIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS.

Stability Condition to Avoid:EXTREME HEAT, SPARKS OR OPEN FLAME.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN PRODUCE  
CARBON MONOXIDE.

===== Disposal Considerations =====

Waste D

isposal Methods:DONT ALLOW MATERIAL TO CONTAMINATE GROUND WATER

SYSTEMS. ABSORB LARGE SPILLS W/SAND, CLAY, DIATOMACEOUS EARTH.

DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implie

d, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.