View NSN Online: https://aerobasegroup.kr/nsn/8010-00-684-8789

HOME OIL COMPANY, INC -- BOILED LINSEED OIL -- 8010-00-684-8789

Product ID:BOILED LINSEED OIL MSDS Date:09/10/1997 FSC:8010 NIIN:00-684-8789 MSDS Number: CGXMN === Responsible Party === Company Name:HOME OIL COMPANY, INC Address:3511 N OHIO Box:2609 City:WICHITA State:KS ZIP:67201-2609 Country:US Info Phone Num:316-838-4663 Emergency Phone Num:800-633-8253 (PERS)

CAGE:0A9L8 === Contractor Identification === Company Name:HOC INDUSTRIES, INC Address:3511 N. OHIO Box:2609 City:WICHITA State:KS ZIP:67219 Country:US Phone:316-838-4663 CAGE:0A9L8

Ingred Name:BOILED LINSEED OIL IS NOT A HAZARDOUS MATERIAL ACCORDING TO 29 CFR 1910.1200 CAS:8001-26-1 RTECS #:OI9690000 Other REC Limits:NONE RECOMMENDED

Routes of Entry:

Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: IRRIT, DERMATITIS. INGEST: IRRIT STOMACH & INTESTINES. ASPIRATED INTO LUNGS RESULTING IN CHEMCIAL PNEUMONITIS.

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: REMOVE CONTAM CLOTHES & SHOES. WASH W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION AT ONCE. INGEST: DONT INDUCE VOMIT. KEEP WARM & QUIET. GE T MEDICAL ATTENTION.

Flash Point Method:TCC

Flash Point:200F,93C

Extinguishing Media:WATER, CARBON DIOXIDE, FOAM EXTINGUISHERS FOR CLASS III B LIQUID FIRES.

Fire Fighting Procedures:USE SCBA. SHUT OFF SOURCE. WATER FOG/SPRAY TO COOL CONTAINERS OR EQUIPMENT. DONT SPRAY WATER DIRECTLY ON FIRE. PRODUCT WILL FLOAT & REIGNITED ON SURFACE.

Unusual Fire/Explosion Hazard:BOILED

LINSEED OIL WILL OXIDIZE & CAUSE

SPONTANEOUS COMBUSTION. AVOID SPONTANEOUS COMBUSTION OF CONTAM RAGS/IGNITABLE ABSORBENT MATERIAL, BY IMMERSING IN WATER.

Spill Release Procedures: ELIMINATE IGNIT SOURCES. VENT AREA. USE SUPPLIED-AIR MASK FOR LARGE SPILLS OR IN CONFINED AREAS. CONTAIN SPILL. REMOVE W/INERT ABSORBENT. AVOID ALLOWING PRODUCT TO ENTER STREAMS OR SEWERS.

======================== Handling and Stor

Handling and Storage Precautions:TRANSPORT, HANDLE, STORE IN ACCORDANCE W/29 CFR (1910.106) & DOT REGULATIONS. GROUND & ELECTRICALLY INTERCONNECT CONTAINERS FOR TRANSFER.

Respiratory Protection: RESPIRATORY PROTECTION MAY BE REQUIRED IF MATERIAL IS USED IN POORLY VENTILATED AREAS OR IF MATERIAL IS SPRAYED OR HEATED. Ventilation: GENERAL VENTILATION IS RECOMMENDED. LOCAL VENTILATION MA Y BE REQUIRED IF MATERIAL IS SPRAYED OR HEATED. Protective Gloves:NEOPRENE RUBBER Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:PROTECTIVE CLOTHES SUCH AS UNIFORMS. EYE WASH STATION AVAILABLE. Work Hygienic Practices:DONT WEAR CONTACT LENSES. FOLLOW SAFE WORK PRACTICES. WASH HANDS PRIOR TO EATING OR SMOKING. Supplemental Safety and Health NK

Spec Gravity:0.93 @ 77F pH:NA Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, LOW ODOR. Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND POSSIBLY ACROLEIN.

Waste Disposal Methods:INCINERATE OR PLACE IN RCRA PERMITTED WASTE MANAGEMENT FACILITY IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULA TIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume res ponsibility for the suitability of this information to their particular situation.