

INTERNATIONAL PAINT CO INC -- PRA25F1 INTERSHIELD PRORECO ELASTOMER GRAY --
8010-01-024-7001

===== Product Identification =====

Product ID:PRA25F1 INTERSHIELD PRORECO ELASTOMER GRAY

MSDS Date:07/17/1995

FSC:8010

NIIN:01-024-7001

Kit Part:Y

MSDS Number: CGXNX

=== Responsible Party ===

Company Name:INTERNATIONAL PAINT CO INC

Address:2270 MORRIS AVE

Box:386

City:UNION

State:NJ

ZIP:07083-5704

Country

:US

Info Phone Num:713-682-1711

Emergency Phone Num:800-854-6813

CAGE:26351

=== Contractor Identification ===

Company Name:INTERNATIONAL PAINT INC

Address:6001 ANTOINE DR

Box:City:HOUSTON

State:TX

ZIP:77091

Country:US

Phone:800-589-1267/800-854-6813

CAGE:26351

===== Composition/Information on Ingredients =====

Ingred Name:METHANE CHLORIDE

CAS:50-09-2

Fraction by Wt: 0.08%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

Ingred Name:2-PROPANOL, 1-METHOY-ACET

ATE (VP = 3.8 @ 20C)
CAS:108-65-6
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:MAGNESIUM OXIDE
CAS:1309-48-4
RTECS #:OM3850000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMORPHOUS FUMED SILICA
CAS:12945-52-5
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6.0 MG/M3

Ingred Name:MANGANESE COMPOUND
CAS:12688-94-7
Fraction by Wt: 0-1.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5.0 MG/M3
ACGIH TLV:5.0 MG/M3

Ingred Name:DETA, REACTIO
N PRODUCT W/ETHYLENE OXIDE 9VP = 10.0 @ 20C)
CAS:28063-82-3
Fraction by Wt: 15-20%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRIT, VISION IMPAIRMENT,
BLINDNESS, CORROSION, DAMAGE. SKIN: IRRIT, BURNS. INHAL:
RESPIRATORY TRACT IRRIT, HEADACHE, DIZZY, UNCONSCIOUS, CORROSIVE,
PAIN, VOMIT, SEVERE BURNS OF MOUTH & THROAT, FATAL.
Medical Cond Aggravated by Exposure:SKIN AND RESPIRATORY CONDITIONS.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: REMOVE CONTAM
CLOTHES, WASH BEFORE REUSE. WASH W/SOAP & WATER. INHAL: REMOVE TO
FRESH AIR. ARTIF RESP IF NEEDED. INGEST: CALL DR. IN ALL CASES, GET
MED AID.

=====
===== Fire Fighting Measures =====

Flash Point:172

F,78C

Lower Limits:1.5

Extinguishing Media:FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:SMOTHER FLAMES W/EXTINGUISHING MEDIA. USE WATER TO COOL CONTAINERS. PREVENT SPREADING OF BURNING LIQUID W/WATER. CONTAINERS EXPLODE IN EXTREME HEAT.

Unusual Fire/Explosion Hazard:CONTAINS METHYLENE CHLORIDE. DECOMPOSES IN FIRE OR ON HOT SURFACES TO HIGHLY TOXIC SUBSTANCES. CONTAINERS MAY EXPLODE IN EXTREME HEAT.

===== Accidental Release Measures =====

Spill R

Release Procedures:REMOVE IGNITS. VENT AREA. CLEAN-UP W/ABSORBENT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A BUILDING DESIGNED AND PROTECTED FROM STORAGE OF LIQUIDS W/NFPA CLASS GIVEN BY OSHA CLASS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR/OPEN AREAS W/UNRESTRICTED VENT, USE NIOSH FILTER RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAYING

DURING SPRAY APPLICATION. RESTRICTED VENT AREAS, USE NIOSH APPROVED RESP TO REMOVE COMBINATION OF PARTICULATES & VAPORS.

Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP TLV & LEVEL OF HAZARDOUS INGREDIENTS BELOW LIMITS.

Protective Gloves:SOLVENT RESISTANT

Eye Protection:SAFETY GLASSES/CHEM GOGGLES/FACE SHIELD

Other Protective Equipment:APPROPRIATE IMPERVIOUS PROTECTIVE CLOTHES TO PREVENT SKIN CONTACT.

Work Hygienic Practices:REMOVE & WASH SOILED CLOTHES BEFORE REUSE. WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:284 TO 586F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:7.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS AND ALUMINUM COMPOUNDS.

Stability Condition to Avoid:STORE AWAY FROM DIREC

T HEAT, FLAME OR
SPARKS. AVOID USE OF PRODUCT & EQUIPMENT CONTAINING ALUMINUM.
Hazardous Decomposition Products:CO, CO2, VARIOUS HYDROCARBON
FRAGMENTS, HYDROGEN CHLORIDE & PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE AND LOCAL
REGULATIONS. DONT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elemen
ts of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.