View NSN Online: https://aerobasegroup.com/nsn/8010-01-441-6033

COURTAULDS AEROSPACE -- 515X386 WATERBORNE PRIMER -- 8010-01-441-6033

Product ID:515X386 WATERBORNE PRIMER MSDS Date:09/24/1996 FSC:8010 NIIN:01-441-6033 MSDS Number: CGYBW === Responsible Party === Company Name: COURTAULDS AEROSPACE Address:5430 SAN FERNANDO ROAD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 **Emergency Phone Num** :800-228-5635/800-424-9300 CHEMTREC CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

Ingred Name:EPOXY RESIN CAS:25068-38-6 RTECS #:KC2100000 Fraction by Wt: 20.0% Other REC Limits:NONE RECOMMENDED

Ingred Name: 2-PROPOXYETHANOL ETHANOL, 2-PROPOXY VP 1.3

CAS:2807-30-9 RTECS #:KM2800000 Fraction by Wt: 10.0% Other REC Limits:NONE RECOMMENDED ACGIH TLV:25 PPM

Ingred Name:STRONTIUM CHROMATE (SARA 313) (CERCLA) CAS:7789-06-2 RTECS #:GB3240000 Fraction by Wt: 10.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:STEL 0.05 MG/M3 ACGIH TLV:0.0005 MG/M3 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 200F,>93C Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM. Fire Fighting Procedures:W ATER SPRAY INEFFECTIVE. COOL FIRE EXPOSED CONTAINERS W/WATER. FOG NOZZLES PREFERRED. WEAR NIOSH/MSHA SCBA. PROTECTIVE CLOTHING. PREVENT CONTACT SKIN/EYES. Unusual Fire/Explosion Hazard:VAPORS MAY ACCUMULATE, FORM EXPLOSIVE MIXTURES, TRAVEL, FLASH BACK OR FLAME MAY OCCUR. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Spill Release Procedures: PROTECT FROM IGNITS. WEAR AIR-SUPPLIED RESPIRATOR. CO VER W/ABSORBENT MATERIAL. SCOOP INTO CONTAINER. CLEAN RESIDUE W/SUITABLE SOLVENT. CERCLA RQ FOR STRONTIUM CHROMATE 10 LBS.

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT, SPARKS, OPEN FLAME AND ELECTRICAL EQUIP. DONT STORE >120F.

Other Precautions: EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT/PUNCTURE/WELD. VAPORS > AIR, MAY COLLECT IN LOW/CONFINED AREAS.

========

=== Exposure Controls/Personal Protection =========

Respiratory Protection:LIKEKLY TO PRODUCE AIRBORNE LEVELS OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV. USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR. Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW TLV AND PEL. Protective Gloves:SOLVENT RESISTANT Eye Protection:GOGGLES OR FULL FACE SHIELD. Other Protective Equipment:PROTECTIVE CLOTHING. Work Hygienic Practices:SAFETY SHOWER, EYEBATH AND WASHING FACILITIES SHOU LD BE AVAILABLE. Supplemental Safety and Health

NK

Boiling Pt:B.P. Text:212 TO 301F Melt/Freeze Pt:M.P/F.P Text:NA Decomp Temp:Decomp Text:NA Vapor Pres:NA Vapor Density:>AIR Spec Gravity:1.27 VOC Pounds/Gallon:339 pH:NA Evaporation Rate & amp; Reference:NA Solubility in Water:NA Appearance and Odor:LIQUID, SOLVENT ODOR. Percent Volatiles by Volume:63.5 Corrosion Rate:NA

====== Stability and Reactivity Data =====

============

Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencie	es):
This information is formulated for use by	

elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.