View NSN Online: https://aerobasegroup.kr/nsn/6850-00-237-3457

LILLY INDUSTRIES

-- MR225 87-X26

MSDS Safety Information

FSC: 3680

NIIN: 00-237-3457 MSDS Date: 07/28/1997 MSDS Num: CHHMV

Product ID: MR225 87-X26

MFN: 05

Responsible Party Cage: IO245

Name: LILLY INDUSTRIES Address: 210 E ALONDRA BLVD City: GARDENA CA 90248-5000

Info Phone

Number: 310-352-3087/800-472-6243

Emergency Phone Number: 310-352-3087/800-472-6243

Review Ind: Y Published: Y

Contractor Summary

Cage: 7Z016

Name: KAMPI COMPONENTS CO., INC.

Address: 210 RT 13

Box: 721

City: BRISTOL PA 19007-3517

Phone: 215-736-2000

Cage: 0MTA9

Name: LILLY IND INC

Address: 210 E ALONDRA BLVD

City: GARDENA CA 90248

Phone: 310-352-3087

Cage: IO245

Name: LILLY INDUSTRIE

S INC

Address: 210 E ALONDRA BLVD

City: GARDENA CA 90248 Phone: 213-321-0710

Item Description Information

Item Manager: S9G

Item Name: PARTING COMPOUND, FOUNDRY MOLD

Specification Number: NONE Type/Grade/Class: NONE

Unit of Issue: CN

Quantitative Expression: 0000000015OZ

UI Container Qty: 0

Type of Container: AEROSOL CAN

Ingredie

Cas: 64742-89-8

Name: LIGHT ALIPHATIC NAPHTHA, VM & DAPHTHA, LACOLENE

% Wt: 65

OSHA PEL: 200 PPM ACGIH TLV: 100 PPM

Cas: 67-63-0

RTECS #: NT8050000

Name: ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL CARBINOL

% Wt: 28

Other REC Limits: 400 PPM

OSHA PEL: 400 PPM ACGIH TLV: 400 PPM

Cas: 1330-20-7

RTECS #: ZE2100000

Name: XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GRO

UP 3) 95-2 % Wt: 2

Other REC Limits: 100 PPM

OSHA PEL: 100 PPM

ACGIH TLV: 100 PPM, SKIN EPA Rpt Qty: 1000 LBS DOT Rpt Qty: 1000 LBS

Cas: 8052-41-3

RTECS #: WJ8925000

Name: STODDARD SOLVENT

% Wt: 1

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM; 9596

Health Hazards Data

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: INGESTION: GI TRACT IRRITANT, POSSIBLE KIDNEY DAMAGE.

ORGANIC SOLVENTS-EYE, SKIN & Amp; RESPIRATORY TRACT IRRITANT. EYES: MAY CAUSE CORNEAL INJURY. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE PER

MANENT BRAIN & amp; NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY

CONCENTRATING/INHALING THE CONTENTS, MAY BE HARMFUL/FATAL.

Explanation Of Carcinogenicity: NONE

Signs And Symptions Of Overexposure: IRRITATION. ORGANIC

SOLVENTS-IRRITATION.

TEARING, REDNESS, DRYING/CRACKING OF THE SKIN, DIZZINESS, NAUSEA, FATIGUE, VOMITING

First Aid: EYES: FLUSH W/LUKE WARM WATER FOR 15 MINS. SKIN: FLUSH WASH W/COPIOUS AMOUNTS OF LUKEWARM WATER. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. INGESTION: RINSE MOUTH IMMEDIATELY. GIVE 6-8 OUNCES OF LIQUID. NEVER GIVE ANYTHING BY MOUTH IF CONSCIOUS. DON'T INDUCE VOMITING UNLESS ADVISED BY A PHYSICIAN. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Handling and Disposal

Spill Release Procedures: STAY UPWIND & DEATH AND AREA UNLESS WEARING PROTECTIVE EQUIPMENT. STOP/CONTAIN DISCHARGE SAFELY. KEEP IGNITION SOURCES AWAY. VENTILATE AREA. USE NON-SPARKING TOOLS FOR CLEANUP. COVER W/INERT MATERIAL. KEEP OUT OF DRAINS, SEWERS/WATERWAYS.

Waste Disposal Methods: DON'T FLUSH TO SEWER, WATERSHED/WATERWAY. DON'T INCINERATE CLOSED CONTAINERS. DISPOSE O

F IN ACCORDANCE W/LOCAL, STATE & amp;

FEDERAL REGULATIONS.

Handling And Storage Precautions: KEEP CONTAINERS COOL, DRY & Samp; AWAY FROM IGNITION SOURCES. USE/STORE W/ADEQUATE VENTILATION. DON'T SMOKE IN STORAGE AREAS.

Other Precautions: AVOID INHALATION OF VAPORS. AVOID CONTACT W/SKIN & DESCRIPTION CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES, PRECAUTIONS GIVEN MUST BE OBSERVED.

======

Fire and Explosion Hazard Information

Flash Point Method: TCC Flash Point Text: 16.0F,-8.9C

Lower Limits: 0.7 Upper Limits: 12

Extinguishing Media: CO2, DRY CHEMICAL/FOAM EXTINGUISHER

Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, USE FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard: CLOSED CONTAINER MAY EXPLODE WHEN

EXPOSED TO

EXTREME HEAT. NEVER USE WELDING/CUTTING TORCH ON/NEAR CONTAINER (EVEN RESIDUE), PRODUCT MAY IGNITE EXPLOSIVELY.

Control Measures

Respiratory Protection: IN OUTDOOR/OPEN AREA, USE NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE AIRBORNE PARTICLES. IN RESTRICTED AREA, A NIOSH/MSHA APPROVED CHEMICAL-MECHANICAL FILTERS. IN CONFINED AREAS, A NIO SH/MSHA APPR

OVED AIRLINE RESPIRATOR/HOOD

Ventilation: GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN VOLUME & amp; PATTERN TO KEEP TLV OF THE INGREDIENTS BELOW ACCEPTABLE LIMITS

Protective Gloves: NATURAL RUBBER, NEOPRENE, BUNA N/NITRILE

Eye Protection: GOGGLES

Other Protective Equipment: SAFETY EYEWEAR W/PERFORATED SIDESHIELDS, EYE WASH STATIONS, SAFETY SHOWERS

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS THOROUGHLY BEFORE EATING & USING WASHROOM.

=========

Physical/Chemical Properties

HCC: V3

B.P. Text: 180-383F Vapor Density: >1

Evaporation Rate & Evaporation R

Percent Volatiles by Volume: 97

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: HEAT, SPARKS, OPEN FLAME, HOT SURFACES,

ELECTRI

CAL EQUIPMENT & OTHER IGNITION SOURCES

Materials To Avoid: STRONG ACIDS

Hazardous Decomposition Products: CO, CO2, OXIDES OF NITROGEN

Hazardous Polymerization Indicator: NO

Toxicological Information

Ecological Information

===

Regulatory Information

MSDS Transport Information

Other Information

Transportation Information

Respo

nsible Party Cage: IO245 Trans ID NO: 59145

Product ID: MR225 87-X26

MSDS Prepared Date: 07/28/1997

Review Date: 07/17/1998

MFN: 5

Tech Entry NOS Shipping Nm: XYLENE, ISOPROPANOL

Net Unit Weight: 16 OZ Multiple KIT Number: 0

Review IND: Y Unit Of Issue: CN Container QTY: 0

Type Of Container: AEROSOL CAN

PID STATE TO USE A 4G.

========

Detail DOT Information

DOT PSN Code: AGC

DOT Proper Shipping Name: AEROSOLS, FLAMMABLE, DOT PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)

Hazard Class: 2.1 UN ID Num: UN1950 Label: FLAMMABLE GAS Special Provision: N82 Non Bulk Pack: NONE Bulk Pack: NONE Max Qty Pass: 75 KG

Max Qty Cargo: 150 KG Vessel Stow Req: A

Water/Ship/Other Req: 40,48,85

=====

Detail IMO Information

IMO PSN Code: AKD

IMO Proper Shipping Name: AEROSOLS o

IMDG Page Number: 2102

UN Number: 1950 UN Hazard Class: 2(T) IMO Packaging Group: -Subsidiary Risk Label: T EMS Number: 2-13

MED First Aid Guide NUM: 620

Detail IATA Information

IATA PSN Code: ALS IATA UN ID Num: 1950 IATA Proper Shipping Name: AEROSOLS, FLAMMABLE

IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)

IATA UN Class: 2.1

IATA Label: FLAMMABLE GAS Packing Note Passenger: 203

Max Quant Pass: 75KG Max Quant Cargo: 150KG Packaging Note Cargo: 203

Detail AFI Information

AFI PSN Code: ALR AFI Symbols: *

AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S. AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)

AFI Hazar d Class: 2.1

AFI UN ID NUM: UN1950 Special Provisions: P4 Back Pack Reference: A6.3

HAZCOM Label

Product ID: MR225 87-X26

Cage: IO245 Assigned IND: Y

Company Name: LILLY INDUSTRIES INC

Street: 210 E ALONDRA BLVD

City: GARDENA CA Zipcode: 90248

Health Emergency Phone: 310-352-3087/800-472-6243

Label Required IND: Y

Date Of Label Review: 07/17/1998

Status Code: C

Label Date: 07/17/1998

Origination Code: F
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Severe Contact Hazard: Moderate

Fire Hazard: Severe Reactivity Hazard: None

Hazard And Precautions: INGESTION: GI TRACT IRRITANT, POSSIBLE KIDNEY DAMAGE.

ORGANIC SOLVENTS-EYE, SKIN & ESPIRATORY TRACT IRRITANT. EYES: MAY CAUSE CORNEAL INJURY. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE PER MANENT BRAIN & DERVOUS SYST

EM DAMAGE. INTENTIONAL MISUSE BY

CONCENTRATING/INHALING THE CONTENTS, MAY BE HARMFUL/FATAL. IRRITATION. ORGANIC SOLVENTS-IRRITATION, TEARING, REDNESS, DRYING/CRACKING OF THE SKIN, DIZZINESS, NAUSEA, FATIGUE, VOMITING

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibi

lity for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.