

ALLIED PHOTO PRODUCT CO,SUB OF ALLIED PRODUCT CORP -- 28023 PHOTAFIX 224
FIXER/REPLENISHER (ITEM #2605) -- 6750-01-426-9542

===== Product Identification =====

Product ID:28023 PHOTAFIX 224 FIXER/REPLENISHER (ITEM #2605)

MSDS Date:03/18/1991

FSC:6750

NIIN:01-426-9542

Kit Part:Y

MSDS Number: CHHYX

=== Responsible Party ===

Company Name:ALLIED PHOTO PRODUCT CO,SUB OF ALLIED PRODUCT CORP

Address:5440-

A OAKBROOK PKY

City:NORCROSS

State:GA

ZIP:30093-2251

Country:US

Info Phone Num:770-448-0250

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:1CG79

=== Contractor Identification ===

Company Name:ALLIED PHOTO PRODUCT CO,SUB OF ALLIED PRODUCT CORP

Address:5440-A OAKBROOK PKY

Box:City:NORCROSS

State:GA

ZIP:30093-2251

Country:US

Phone:770-448-0250

CAGE:1CG79

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fraction

by Wt: 15-20%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE

CAS:7757-83-7

RTECS #:WE2150000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (CERCLA)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9596

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:WATER

= Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL:LOW HAZ FOR ORDINARY INDUSTRIAL
HNDLG.EYE:CONTACT MAY CAUSE IRRIT.SKIN:REP/PROL CONTACT MAY CAUSE
IRRIT.INGEST:DONT TAKE INTERNALLY.MAY BE HARMFUL IF SWALLOWED.
Effects of Overexposure:EYE IRRIT, SKIN IRRIT, HARMFUL IF SWALLOWED.
Medical Cond
Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/LG AMTS OF WATER FOR 15MINS.SEEK MED
ATTN.SKIN:WASH SKIN W/SOAP/WATER.IF IRRIT OCCURS SEEK MED
ATTN.INGEST:INDUCE VOMITING.SEEK MED ATTN IMMED GIVING FULL DETAILS
OF AMT INGESTED & TOXICIT Y.INHAL:MOVE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp
Text:NP
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:USE METHOD APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:USE PROTECTIVE CLOTHING TO PREVENT CONTACT
W/SKIN/EYES.
Unusual Fire/Explosion Hazard:WHEN HEATED TO DECOMPOSITION, IT CAN EMIT
TOXIC FUMES OF SOX AND AMMONIA.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING AS SPECIFIED IN
MSDS.NEUTRALIZE W/SODIUM BICARBONATE.IF LOCAL, STATE AND FEDERAL
LAW PERMIT FLUSH TO SEWER W/LG AMTS OF WATER.
Neutralizing Agent:SODIUM BICARBONATE.

===== Handling and Storage =====

Handling and Storage Precautions:DONT STORE OR CONSUME
FOOD/DRINK/TOBACCO IN SURROUNDING AREA.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SHOULD NOT BE NECESSARY UNDER NORMAL
CONDITIONS.IF EXPOSED TO VAPORS THAT EXCEED TLV OR PE

L WEAR

APPROVED VAPOR RESPIRATOR.

Ventilation:GOOD LOCAL MECHANICAL VENTILATION SHOULD BE SUFFICIENT.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:WEAR PROTECTIVE GOGGLES

Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.EYEWASH FACILITIES IN VICINITY OF USE.

Work Hygienic Practices:WASH THOROUGHLY AFTER USE.

Supplemental Safety and Health

DISPO:TO ASCERTAIN PROPER DISPO PROCEDURES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling

Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:17.0

Vapor Density:0.6

Spec Gravity:1.33

pH:4.6

Viscosity:NP

Evaporation Rate & Reference:NA

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, SLIGHT VINEGAR ODOR

Percent Volatiles by Volume:65

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MINERAL ACIDS.

Stability Condition to Avoid:NONE KNOWN.

Hazardous Decom

position Products:WHEN HEATED TO DECOMPOSITION,IT CAN
EMIT TOXIC FUMES OF SO₂,CO₂ AND POSSIBLY CO.

===== Disposal Considerations =====

Waste Disposal Methods:NEUTRALIZE W/SODIUM BICARBONATE.IF FED/STATE
&/OR LOC LAWS PERMIT FLUSH TO SEWER W/LG ATMS OF WATER.OTHERWISE
DISPO OF CONTAM PROD & MATLS USED IN CLEANING UP SPILL IN MANNER
APPROVED FOR THIS MATL.CO NSULT PROPER FED/STATE &/OR LOC REG
AGENCIES(SUPP)

Disclaimer (provided with this in

formation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.