

DEL PAINT CORP. -- INT/EXT ALKYD ENAMEL WHITE #17886 MIL-E-1115D -- 8010-01-434-1268
===== Product Identification =====

Product ID:INT/EXT ALKYD ENAMEL WHITE #17886 MIL-E-1115D

MSDS Date:08/05/1997

FSC:8010

NIIN:01-434-1268

MSDS Number: CHKMG

=== Responsible Party ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431/FAX

405-672-0804

Emergency Phone Num:800-424-9300 24 HRS

Preparer's Name:ONEY FLEMING

CAGE:JO954

=== Contractor Identification ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA, M

EDIUM ALIPHATIC SOLVENT

CAS:64742-88-7

Fraction by Wt: 24.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 76.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: REDNESS, PAIN, IRRITATION,
TEARING, BLURRE

D VISION. SKIN: IRRITATION, DEFATTING, DERMATITIS,

REDNESS. INHAL: IRRIT, DIZZY, NAUSEA, HEADACHE, DIFF BREATHING,

DULLNESS, DROWSY. INGEST: GI IRRIT, NA USEA, VOMIT, ABDOMINAL PAIN.

Medical Cond Aggravated by Exposure:RESPIRATORY DISEASES.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER 15 MINUTES, LIFTING LIDS. GET MED AID.

SKIN: REMOVE CONTAM CLOTHES, WASH BEFORE REUSE. WASH W/SOAP &
WATER. INHAL: REMOVE TO FRESH AIR, GIVE OX

YGEN. GET MED AID.

INGEST: KEEP WARM/Q UIET, GET MED AID. DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:100F,38C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED

CONTAINERS. WEAR NIOSH/MSHA RSCBA IN PRESSURE DEMAND MODE, FULL
PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:VAPORS >AIR, MAY TRAVEL, M

OVED BY VENT.
IGNITED BY IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:VENT AREA. COVER W/INERT ABSORBENT. SHOVEL
W/NON-SPARKING TOOLS. PLACE IN CONTAINER. SEAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLEAN DRY AREA. KEEP AWAY
FROM IGNIT SOURCES.
Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM
CHILDREN. GROUND EQUIPMENT TO RED
UCE STATIC ELECTRICITY. USE
NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED CARTRIDGE RESPIRATOR.
ENGINEERING/MANAGEMENT CONTROLS SHOULD BE IMPLEMENTED TO REDUCE
EXPOSURE.

Ventilation:LOCAL EXHAUST

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.

Other Protective Equipment:EYEBATH, WASHING FACILITIES, IMPERVIOUS
CLOTHING.

Supplemental Safety and Health

NK

===

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:305 TO 396F

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:752F,400C

Vapor Pres:2.58

Vapor Density:>AIR

Spec Gravity:1.04 (H2O =1)

pH:NA

VOC Grams/Liter:2.8

Viscosity:70-80 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NO

Appearance and Odor:WHITE LIQUID W/SLIGHT ODOR.

Percent Volatiles by Volume:47.29

===== Stability and Reactivity Data =====

St

ability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: DONT STORE NEAR HEATED SURFACES, OPEN FLAMES OR IGNITION SOURCES.

Hazardous Decomposition Products: CARBON DIOXIDE

=====
===== Disposal Considerations =====

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS.

=====
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.