

INTERNATIOAL LUBRICANTS CO INC -- WATER SOLUBLE CUTTING OIL,VV-C-846 C --
9150-00-265-9405

===== Product Identification =====

Product ID:WATER SOLUBLE CUTTING OIL,VV-C-846 C

MSDS Date:10/01/1996

FSC:9150

NIIN:00-265-9405

MSDS Number: CHMBP

=== Responsible Party ===

Company Name:INTERNATIOAL LUBRICANTS CO INC

Address:10363 AIRLINE HIGHWAY

City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Info Phone Nu

m:504-469-0940

Emergency Phone Num:504-469-0940

CAGE:JO811

=== Contractor Identification ===

Company Name:INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

Company Name:INTERNATIONAL LUBRICATES INC

Address:10363 AIRLINE HIGHWAY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940

CAGE:JO811

Company Name:SDB CONSULTANTS LTD

Address:401 WHITNEY AVE SUITE 120

Box:City:GRETNA

State

:LA
ZIP:70056
Country:US
Phone:504-366-9105
CAGE:0PGK2

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER SOLUBLE CUTTING OIL
CAS:64142-52-5
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IAR
C:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY &
GI TRACTS. ACUTE- EYE:MAY CAUSE IRRITATION. SKIN:PROLONGED/REPEATED
CONTACT MAY CAUSE IRRITATION. INHALE:HIGH VAPOR/MISTS
CONCENTRATIONS MAY CAUSE DROWSINESS & IRRITATION. ORAL:IF MORE
THAN SEVERAL MOUTHFULS ARE SWALLOWED, ABDOMINAL DISCOMFORT MAY
OCCUR. CHRONIC- DERMATITIS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, NAUSEA, ABDOMINAL DISCOMFORT,
COUGHING, HE
ADACHE, DROWSINESS, VOMITING, DIARRHEA
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:CALL A DOCTOR IF SYMPTOMS OCCUR. EYE:FLUSH WITH WATER. HOLD
EYELIDS OPEN. SKIN:WIPE EXCESS OFF. WASH SKIN WITH SOAP & WATER OR
A WATERLESS HAND CLEANER FOLLOWED BY SOAP & WATER. INHALE

D:MOVE TO

FRESH AIR. ORAL:IF CONSCIOUS, RINSE OUT MOUTH WITH WATER. GET MEDICAL ADVICE.

===== Fire Fighting Measures =====

Extinguishing Media:USE CARBON DIOXIDE, FOAM/DRY CHEMICAL. DIRECTLY SPRAYING WATER/FOAM ONTO BURNING OIL MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

===== Accident
al Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. PROVIDE ADEQUATE VENTILATION. REMOVE SPILL WITH INERT ABORBENT SUCH AS SAND, CLAY, EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF TO ENTER SEWERS OR WATE RWAYS. REPORT SPILLS AS REQUIRED TO AUTHORITIES.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HIGH HEAT & STRONG

OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDER BEFORE RE-USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES

EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED ORGANIC VAPOR AND MI ST RESPIRATOR (REFER TO 29 CFR 1910.134)

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves:RUBBER FOR REPEATED CONTACT

Eye Protection:SAFETY GLASSES/GOGGLES IF SPLASHING

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic P

ractices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. WASH BEFORE EATING OR DRINKING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
NRC/State Lic Num:NOT RELEVANT
Solubility in Water:SOLUBLE
Appearance and Odor:WATER-SOLUBLE CUTTING OIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:EXCES
SIVE HEAT
Hazardous Decomposition Products:MAY PRODUCE SMOKE, CARBON MONOXIDE,
CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN COMPLIANCE WITH LOCAL, STATE
AND FEDERAL REGULATIONS. THIS IS AN OIL. SPILLS THAT CAUSE A SHEEN
MUST BE REPORTED TO 800-424-8002. DO NOT CONTAMINATE ANY LAKES,
STREAMS, PONDS OR UN DERGROUND WATER SUPPLY. INCINERATION
RECOMMENDED.

Disclaimer (provided with this informat
ion by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.