

CHEVRON INTERNATIONAL OIL CO -- DELO 400 SAE 10 W-30 -- 9150-01-230-9748

===== Product Identification =====

Product ID:DELO 400 SAE 10 W-30

MSDS Date:06/07/1997

FSC:9150

NIIN:01-230-9748

MSDS Number: CHMFH

=== Responsible Party ===

Company Name:CHEVRON INTERNATIONAL OIL CO

Address:570 MARKET ST

City:SAN FRANCISCO

State:CA

ZIP:94106-2856

Country:US

Info Phone Num:415-894-2858/416-894-1899

Emergenc

y Phone Num:202-483-7616/800-424-9300(CHEMTREC)

CAGE:2H740

=== Contractor Identification ===

Company Name:CHEVRON ENVIRONMENTAL HEALTH CENTER INC

Address:15299 SAN PABLO AVE

Box:4054

City:RICHMOND

State:CA

ZIP:94804

Country:US

Phone:800-582-3835

CAGE:0AHD1

Company Name:CHEVRON PRODUCTS CO GLOBAL LUBRICANTS

Address:555 MARKET STREET ROOM 803

Box:City:SAN FRANCISCO

State:CA

ZIP:94105-2870

Country:US

Phone:800-228-3500/415-894-0703

CAGE:2H740

Company Name:CHEVRON USA INC DBA CHEVRON PRODUCTS CO

Add

ress:575 LENNON LN
Box:City:WALNUT CREEK
State:CA
ZIP:94598
Country:US
Phone:510-977-7283
CAGE:04BH0

=====
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL, SOLVENT REFFINED HEAVY PARAFFINIC, SEVERELY
HYDROTREATED

CAS:64741-88-4

RTECS #:PY8040501

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PETROLEUM OIL

CAS:64741-89-5

RTECS #:PY8041500

Fraction by Wt: 0 - >75%

Other RE

C Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT REFINED (MILD),
HEAVY NAPHTHENIC (CARCENOGENIC - IARC)

CAS:64741-96-4

RTECS #:PY8040000

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT REFINED
(SEVERE), LIGHT NAPHTHENIC, (NON-CARCINOGENIC - IARC)

CAS:64741-97-5

RTECS #:PY80

41001

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:SOLVENT REFINED RESIDUE

CAS:64742-01-4

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 OIL MIST

ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:MINERAL OIL, HYDROTREATED (MILD), HEAVY NAPHTHENIC
DISTILLATE, PETROLEUM

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

A

CGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:MINERAL OIL

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED
(MILD), HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:SOLVENT DEWAXED RESIDUAL OIL (PETROLEUM)

CAS:6

4742-62-7

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD),
HEAVY PARAFFINIC/PETROLEUM LUBE OIL

CAS:64742-65-0

RTECS #:PY8038500

Fraction by Wt: 0 - >75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:LUBRICATING BASE OIL, SEVERELY REFINED PETROLEUM DISTILLATE

CAS:72623-83-7

Fraction by Wt: 0 - >

75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 OIL MIST

ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:ADDITIVES

Fraction by Wt: