

CHEMICAL COMMODITIES AGENCY, INC. -- ISOPROPYL ALCOHOL -- 6810-00-855-6160

=====  
Product Identification  
=====

Product ID:ISOPROPYL ALCOHOL

MSDS Date:08/01/1993

FSC:6810

NIIN:00-855-6160

MSDS Number: CHQKD

=== Responsible Party ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Info Phone Num:909-864-2310/FAX 6220 D. ANG

ELO

Emergency Phone Num:909-864-2310

CAGE:60777

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: >99%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL;9596

=====

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION-IRRITATION OF NOSE & THROAT. EXPOSURE TO HIGH CONCENTRATIONS HAS A NARCOTIC AFFECT. SKIN-HAS A DEFATTING ACTION OF THE SKIN. EYES-VAPORS MAY CAUSE IRRITATION TO THE EYES. CHRONIC: DERMATIT IS.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:INHALATION

-DROWSINESS, HEADACHE, STAGGERING, UNCONSCIOUSNESS. INGESTION-DROWSINESS, UNCONSCIOUSNESS AND DEATH. PAIN, CRAMPS, NAUSEA AND DIZZINESS MAY RESULT. SKIN-STINGING AND BURNING SENSATION. EYES- CORNEAL BURNS AND EYE INJURY.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS OR EYE PROBLEMS, IMPAIRED RESPIRATORY FUNCTIONS MAY BE MORE SUSCEPTIBLE.

=====  
First Aid Measures  
=====

First Aid:INHALATION-MOVE TO FRESH AIR. GIVE SRTIFICIAL RESPIRATION IF

NEEDED. GIVE OXYGEN IF AVAILABLE. INGESTION-GIVE WATER TO DRINK. INDUCE VOMITING. SEEK MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. WASH SKIN WITH SOAP AND WATER FOR AT LEAST 15 MIN. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. EYES-FLUSH WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MIN. SEEK MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point:53.6F,12.0C

Lower Limits:2

Upper Limits:12

Extingui

shing Media:WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM OR CARBON DIOXIDE. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING & SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE GEAR. WATER MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURES & DILUTE.

Unusual Fire/Explosion Hazard:VAPORS CAN FLOW ALONG SURFACES TO DISTANT IGNITION SOURCE & FLASH BACK. ABOVE FLASH POINT, VAPOR-AIR MIXTURES ARE EXPLOSIVE WITHIN FL

AMMABLE LIMITS LISTED ABOVE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA OF SPILL OR LEAK. CLEAN-UP PERSONNEL MAY REQUIRE PROTECTIVE CLOTHING AND RESPIRATORY PROTECTION FROM VAPORS. SMALL SPILLS MAY BE ABSORBED ON PAPER TOWELS AND EVAPORATED IN A FUME HOOD. ALLOW ENOUGH TIME.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE.

Other Precautions:OUTSIDE OR DETACHED STORAGE IS PREFERRED, SEPERATE FROM OXIDIZING MATERIALS. CONTAINERS MAY BE BONDED. STORAGE AND USE AREAS SHOULD NOT BE SMOKING AREAS. USE NONSPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF THE TLV IS EXCEEDED A FULL FACEPIECE CHEMICAL

CARTRIDGE RESPIRATOR MAY BE WORN.

Ventilation:LOCAL OR GENERAL EXHAUST.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL GOGGLES/FULL FACE SHIELD.

Other Protective Equipment:BOOTS, GLOVES, LAB COAT, APRON, COVERALLS.

Work Hygienic Practices:EYE WASH FOUNTAIN, QUICK DRENCH SHOWER.

Supplemental Safety and Health

FLAMMABLE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:180F,82C

Melt/Freeze Pt:M.P/F.P Text:-128F,-89C

Vapor Pres:33

Vap

or Density:2.1  
Spec Gravity:0.79  
Evaporation Rate & Reference:2.83  
Solubility in Water:INFINITE IN WATER  
Appearance and Odor:CLEAR, COLORLESS LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
HEAT, FLAMES, STRONG OXIDANTS, ACETALDEHYDE, CHLORINE, ETHYLENE OXIDE,  
HYDROGEN-PALLADINE, ETC.

Stability Condition to Avoid:STABLE UNDER ORDINARY CONDITIONS OF USE &  
STORAGE, HEAT & SUNLIGHT CAN CONTRIBUTE TO INSTABILITY.

Hazardous Decomposition Products:TOXIC GASES, CARBON MONOXIDE,  
TERT-BUTOXIDE, HYPOCHLOROUS ACID, ISOCYANATES, NITROFORM,  
PERCHLORIC ACID.

===== Disposal Considerations =====

Waste Disposal Methods:CONTAIN AND RECOVER LIQUID FOR RECLAMATION IF  
POSSIBLE. LARGER SPILLS AND LOT SIZES CAN BE COLLECTED AS HAZARDOUS  
WASTE AND ATOMIZED IN A SUITABLE RCRA APPROVED COMBUSTION CHAMBER  
OR ABSORBED WITH VER MICULITE, DRY SAND OR SIMILIAR MATERIAL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.