View NSN Online: https://aerobasegroup.kr/nsn/6750-01-097-0773

EASTMAN KODAK COMPANY -- 812 1188 T-MAX 100 DIRECT POSITIVE FILM CLEARING BATH, WS -- 6750-01-097-0773

Product ID:812 1188 T-MAX 100 DIRECT POSITIVE FILM CLEARING BATH, WS MSDS Date:03/11/1998 FSC:6750 NIIN:01-097-0773 MSDS Number: CHQLT === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country :US Info Phone Num:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

====== Compo

sition/Information on Ingredients ==========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 85-90% Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE CAS:10117-38-1 RTECS #:WT3530000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM CARBONATE CAS:584-08-7 RTECS #:TS7750000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM BICARBONATE CAS:144-55-8 RTECS #:VZ0950000 Fraction by Wt: < 1% Other REC Limits:NO NE RECOMMENDED

LD50 LC50 Mixture:ORAL LD50 (RAT): NOT GIVEN Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY LIBERATE SULFUR DIOXIDE GAS WHICH IS IRRITATING TO THE RESPIRATORY TRACT. EYE CONTACT CAUSES IRRITATION. SKIN CONTACT CAUSES IRRITA TION. MAY CAUSE SKIN SENSITIZATION. HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF THE GASTROINTESTINAL TRACT. Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure:RESPIRATORY TRACT IRRITATION, DIFFICULT

Effects of Overexposure:RESPIRATORY TRACT IRRITATION, DIFFICULT BREATHING, EYE IRRITATION, SKIN IRRITATION, ALLERGIC SKIN REACTION, WHEEZING, CHEST ITIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS, DIARRHEA.

Medical Cond

Aggravated by Exposure:SOME ASTHMATICS OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, DIFFICULT BREATHING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS, DIARRHEA.

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP & WATER. GET ME

DICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER.SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Flash Point:NONFLAMMABLE Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN Extinguishing Media:NONFLAMMABLE. USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXC

ESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

Spill Release Procedures: FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUA L CONTAMINATION. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION.

Other Precautions: KEEP CONTAINER CLOSED. KEEP AWAY FROM INCOMPATIBLE MATERIALS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE SHOULD BE NEEDED. A RESPIRATOR SHOULD BE WORN IF HAZARDOUS DECOMPOSITION

PRODUCTS ARE LIKELY TO BE OR HAVE BEEN RELEASED. RESPIRATOR TYPE: ACID GAS. IF RESPIRATORS ARE USED, A PROGRAM SHOULD BE I NSTITUTED TO ASSURE COMPLIANCE WITH OSHA Ventilation: GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS. Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE. Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health FORMULATION DIFFERENT FROM OTHER P/NS. 

HCC:B3 Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.09 pH:10.1 Evaporation Rate & amp; Reference:NOT GIVEN Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID, NO ODOR Percent Volatiles by Volume:85-90%

Stability Indicator/Materials to Avoid:YES STRONG ACIDS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:SULFUR DIOXIDE.

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR

LOCAL LAWS. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. SINCE EMPTIED CONTAINERS RETAIN PRO DUCT RESIDUE, FOLLOW LABEL WARNINGS AFTER EMPTY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for

its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.