View NSN Online: https://aerobasegroup.kr/nsn/1630-01-116-1618

ALLIED SIGNAL INC., AIRCRAFT LANDING SYSTEM -- CADMIUM PLATED AIRCRAFT PART #2606616

-- 1630-01-116-1618

Product ID:CADMIUM PLATED AIRCRAFT PART #2606616

MSDS Date:12/01/1993

FSC:1630

NIIN:01-116-1618 Status Code:A

MSDS Number: CHXBB === Responsible Party ===

Company Name: ALLIED SIGNAL INC., AIRCRAFT LANDING SYSTEM

Address:3520 WESTMOOR STREET

City:SOUTH BEND

Sta te:IN

ZIP:46628 Country:US

Info Phone Num:219-231-2302

Emergency Phone Num:219-231-2000

CAGE:55284

=== Contractor Identification ===

Company Name: HONEYWELL INTL INC, AIRCRAFT LANDING SYSTEM ALS

Address:3520 WESTMOOR STREET

Box:City:SOUTH BEND

State:IN

ZIP:46628-1373 Country:US

Phone:219-231-2201

CAGE:55284

======= Composition/Information on Ingredients ========

Ingred Name: CADMIUM (SARA 313) (CERCLA)

CAS:7440-43-9

RTECS #:EU9800000 Fraction by Wt: TRACE

Other REC Limits: NONE RECO

MMENDED
OSHA PEL:0.2 MG/M3 DUST; Z-2
ACGIH TLV:0.01 MG/M3 DUST;9596

EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

========== Hazards Identification ===============

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT GIVEN Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, LUNG, KIDNEY, PROSTATE. PRODUCT IS NOT HAZARDOUS. HEALTH HAZARDS ARE DUE TO DUSTS/FUMES CREATED D

URING MACHINING. ACUTE- EYE: MAY CAUSE PAIN.

SKIN/INHALE:MAY CAUSE IRRITATION. ORAL:MAY CAUSE HEADACHE, VOMITING, SORETHROAT. CHRONIC- MAY CAUSE KIDNEY DAMAGE, LUNG AND PROSTATE CANCER.

Explanation of Carcinogenicity: CONTAINS C [7440-43-9] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION, SHORTNESS OF BREATH, CHEST PAIN, FLU-LIKE SYMPTOMS SUCH AS WEAKNESS, HEADACHE, CHILLS AND MUSCULAR PAIN, NAUSEA, VOMITING, DIARRH

EA, SORE THROAT, REDNESS AND PAIN OF EYES, SWEATING, FEVER.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, KIDNEYS, CNS MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH

SOAP/MILD DETERGENT & LARGE AMOUNT OF WATER.

INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. ORAL:TREATMENT MUST BE ADMINISTERED BY MEDICAL PERSONNEL. ADVICE TO PHYSICIAN:DO NOT PERFORM CHELATION THERAPY.

Flash Point:NONE

Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN

Extinguishing Media:DRY SAND, DRY DOLOMITE, DRY GRAPHITE OR SODIUM

CHLORIDE

Fire Fighting Procedures: WEAR PROTECTIVE CLOTHING AND NI

SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:CADMIUM DUST CREATED DURING MACHINING MAY PRESENT A MODERATE EXPLOSION HAZARD WHEN EXPOSED TO FLAME. DUST AND STRONG OXIDIZERS MAY CAUSE FIRE OR EXPLOSION.
========= Accidental Release Measures ==========
Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. VACUUM OR SWEEP UP SPILLAGE. AVOID CREATING DUST. PLACE SPILLAGE IN APPROPRIATE CONTAINER FOR WASTE DISPOSAL. VENTILATE AR EA. SPILLS AND RELEASES MAY HAVE TO BE REPORTED TO FEDERAL AND/OR LOCAL AUTHORITIES. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:SHIPPING & STORAGE MUST FOLLOW INSTRUCTIONS AS SPECIFIED IN 29 CFR 1910.1027 BEARING WARNING LABLE: DANGER, CONTAINS CADMIUM. CANCER HAZARD. Other Precautions:AVOID CREATING DUST. AVOID CONTACT TO EYES AND SKIN. AVOID INHALATION OF DUST. WASH TH OROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN. OBEY HAZARD WARNING LABEL. USE WITH ADEQUATE VENTILATION. CAN CAUSE LUNG AND KIDNEY DISEASES.
====== Exposure Controls/Personal Protection ========

OSH-APPROVED

Respiratory Protection:IF TLV