

EASTMAN KODAK COMPANY -- 190 1891 MICROFILM DEVELOPER REPLENISHER, (1:2) WORKING  
SOLN -- 6750-01-148-3602

===== Product Identification =====

Product ID:190 1891 MICROFILM DEVELOPER REPLENISHER, (1:2) WORKING SOLN

MSDS Date:07/17/1998

FSC:6750

NIIN:01-148-3602

Status Code:A

MSDS Number: CHXBG

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:

NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====  
Composition/Information on Ingredients  
=====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 80-85%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE  
CAS:10117-38-1  
RTECS #:WT3530000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA)  
CAS:123-31-9  
RTECS #:MX3500000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3; 9596  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL  
CAS:111-46-6  
RTECS #:ID5950000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM BROMIDE  
CAS:7758-02-3  
RTECS #:TS7650000  
Fraction by Wt: < 1%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROXYMETHYL-4-METHYL-1-PHENYL-3-PYRAZOLIDONE  
CAS:13047-13-7  
Fraction by Wt: < 1%  
Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:ORAL LD50 (RAT): NOT GIVEN  
Routes of E

ntry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY LIBERATE SULFUR DIOXIDE GAS WHICH IS IRRITATING TO RESPIRATORY TRACT. EYE CONTACT CAUSES IRRITATION. SKIN CONTACT MAY CAUSE ALLERGI C SKIN REACTION/DEPIGMENTATION. PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION. HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity:THIS COMPOU

ND CONTAINS NO INGREDIENTS AT

CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:RESPIRATORY TRACT IRRITATION, EYE IRRITATION, ALLERGIC SKIN REACTION, SKIN DEPIGMENTATION, SKIN IRRITATION, WHEEZING, CHESST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS, DIARRHEA, GI TRACT IR RITATION.

Medical Cond Aggravated by Exposure:SOME ASTHMATICS OR SULFITE

SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, S

TOMACH UPSET, HIVES, FAINTNESS, WEAKNESS, DIARRHEA.

===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION:ONLY INDUCE VOMITING AT INSTRUCTION OF MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH IF UNC  
ONSCIOUS. CALL PHYSICIAN OR  
POISON CONTROL ASAP.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTU

RER.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING MIST OR VAPOR. AVOID

CONTACT WITH EYES, SKIN AND CLOTHING. USE WITH ADEQUATE VENTILATION. KEEP FROM CONTACT WITH OXIDIZING MATERIALS.

Other Precautions:KEEP CONTAINER CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES. THE ROUTINE USE OF A NONALKALINE (ACID) TYPE OF HAND CLEANER AND REGULAR CLEANING OF WORKING SURFACES WILL HELP MINIMIZE THE POSSIBILITY OF A SKIN REACTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED. A RESPIRATOR SHOULD BE

WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE OR HAVE BEEN RELEASED. RESPIRATOR TYPE: ACID GAS. IF USED, A RESPIRATOR PROGRAM SHOULD BE USED IN COMPLIANCE WITH OSHA 29CFR 1910.134.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING

AS NECESSARY TO

PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Decomp Temp:Decomp Text:NOT GIVEN

Va

por Pres:18  
Vapor Density:0.6  
Spec Gravity:1.11  
pH:10.9  
Viscosity:NOT GIVEN  
Evaporation Rate & Reference:NOT GIVEN  
Solubility in Water:COMPLETE  
Appearance and Odor:COLORLESS LIQUID, NO ODOR  
Percent Volatiles by Volume:80-85%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS, STRONG ACIDS.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.  
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MO  
NOXIDE,  
OXIDES OF SULFUR

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT  
TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH  
< 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE  
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of  
Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.