

MINE SAFETY APPLIANCES - CORP HQTRS -- P/N 812144 CALIBRATION CHECK GAS --
6830-01-441-1263

===== Product Identification =====

Product ID:P/N 812144 CALIBRATION CHECK GAS

MSDS Date:05/01/1995

FSC:6830

NIIN:01-441-1263

Status Code:A

MSDS Number: CHXDS

=== Responsible Party ===

Company Name:MINE SAFETY APPLIANCES - CORP HQTRS

Address:121 GAMMA DR

Box:426

City:PITTSBURGH

State:PA

ZIP:15230-0426

Count

ry:US

Info Phone Num:412-967-3000

Emergency Phone Num:412-967-3000

CAGE:8F723

=== Contractor Identification ===

Company Name:MINE SAFETY APPLIANCES CO

Address:121 GAMMA DR

Box:426

City:PITTSBURGH

State:PA

ZIP:15230-0426

Country:US

Phone:724-733-9270

CAGE:8F723

===== Composition/Information on Ingredients =====

Ingred Name:NITRIC OXIDE (SARA 302)

CAS:10102-43-9

RTECS #:QX0525000

Fraction by Wt: 0.001%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:25 PPM

ACGIH TLV:25 PPM; 9596

EPA

Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:NITROGEN
CAS:7727-37-9
RTECS #:QW9700000
Fraction by Wt: BALANCE
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:ASPHYXIAN; 9596

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NITRIC OXIDE IS A HIGHLY TOXIC GAS.
THE TLV-TWA IS 25 PPM AND THE IDLH ASPHYXIAN. THE DILUTE NITROGEN
IS
A SIMPLE ASPHYXIAN.
Explanation of Carcinogenicity:NOT LISTED BY RTECS, OSHA, NTP OR IARC.
Effects of Overexposure:OVEREXPOSURE TO NITROGEN OXIDES CAN CAUSE
COUGH, DIFFICULT BREATHING, FATIGUE, NAUSEA, CHEST CONGESTION,
IRRITATION OF EYES AND RESPIRATORY TRACT, PULMONARY EDEMA AND
DELAYED EDEMA, AND POSSIBLY METHE MOGLOBINEMIA.
Medical Cond Aggravated by Exposure:NO INFORMATION.

===== First Aid Measures =====

First Aid:REMOVE THE VICTIM TO FRE
SH AIR. APPLY ARTIFICIAL RESPIRATION
IF THE VICTIM IS NOT BREATHING. GIVE OXYGEN IF BREATHING IS
DIFFICULT. GET MEDICAL ATTENTION IMMEDIATELY, EVEN IF THE VICTIM IS
NOT COMPLAI NING OF DISCOMFORT. IMMEDIATE MEDICAL ATTENTION IS
ADVISED IN ALL CASES WHERE APPRECIABLE INHALATION OF NO/NO2 IS
BELIEVED TO HAVE OCCURRED, AS PULMONARY EDEMA MAY DEVELOP.

===== Fire Fighting Measures =====

Extinguishing Media:THIS CALIBRATION GAS MIXTURE ISN'T FLAM
MABLE.
Unusual Fire/Explosion Hazard:GAS UNDER PRESSURE, 500 PSIG AT 70F.
DON'T EXCEED 120F.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. AVOID BREATHING GAS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY WELL VENTILATED
AREA. DON'T EXCEED 130F.
Other Precautions:AVOID BREATHING GAS.

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:DUE TO LIMITED AMOUNT OF GAS IN THE CYLINDER, &
THE LOW RELEASE RATE EMPLOYED IN INSTRUMENT CALIBRATION,
RESPIRATORY PROTECTION ISN'T INDICATED UNDER CONDITIONS OF INTENDED
USE.

Ventilation:USE IN WELL VENTILATED AREA.ITABLE.

Work Hygienic Practices:AVOID BREATHING GAS.

Supplemental Safety and Health

FOLLOW THE CALIBRATION PROCEDURE DETAILED IN THE MSA INSTRUCTIONS
MANUAL PROVIDED WITH THE INSTRUMENT UNDER CALIBRATION.

===== Physical/C
hemical Properties =====

HCC:G3

Vapor Density:130F.

===== Disposal Considerations =====

Waste Disposal Methods:DON'T PUNCTURE/INCINERATE CYLINDER. BEFORE
DISCARDING CYLINDER, SLOWLY RELEASE CONTENTS TO A SAFE EXHAUST.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or impl
ied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.