

FARWEST PAINT MFG CO -- #40 VITANIC BLACK ASPHALT VARNISH -- 8010-00-160-5856

=====  
Product Identification  
=====

Product ID:#40 VITANIC BLACK ASPHALT VARNISH

MSDS Date:07/01/1997

FSC:8010

NIIN:00-160-5856

MSDS Number: CHXRJ

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:SEATTLE

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergen

cy Phone Num:206-244-8844

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 59%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM; 9495

Ingred Name:TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM; Z-2  
ACGIH TLV:100 PPM; 9495  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:GLYCOL ETHER EP SOLVENT  
CAS:2807-30-9  
RTECS #:KM2800000  
Fraction by Wt: 1%  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN  
: IRRITATION, SENSITIZATION,  
DEFATTING; INHALE: HEADACHE, DIZZINESS, NAUSEA, LOSS OF  
CONSCIOUSNESS, POSSIBLE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE;  
EYES: IRRITANT  
Effects of Overexposure:ASPIRATION CAN CAUSE CHEMICAL PNEUMONITIS  
Medical Cond Aggravated by Exposure:NONE

=====  
===== First Aid Measures =====  
=====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER; REMOVE AND WASH ANY  
CONTAM CLOTHING BEFORE REUSE. EYES: FLUSH WITH LARGE QUANTITIES OF  
WATER FOR 15 MINUTES; GET MED AID. INGEST: DO NOT INDUCE VOMITING;  
KEEP PERSON WARM AND QUIET; GET MED AID. INHALE: REMOVE TO FRESH  
AIR IMMEDIATELY; GET MED AID AT ONCE.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:TCC  
Flash Point:100F,38C  
Autoignition Temp:Autoignition Temp Text:NONE  
Lower Limits:1  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG, AND ANY  
CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE; USE TO COOL  
CONT

A

Fire Fighting Procedures:WEAR SCUBA; EVACUATE AREA, WEAR PROTECTIVE CLOTHING

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION; VENTILLATE AREA; ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE, OR S AND AND PLACE MATERIAL INTO CLOSED CONTAINER. IF LARGE SPILL: DIKE - PREVENT FROM ENTERING WATER SYSTEMS OR SEWERS;PROT EQUIP

===== Handling and Storage =====

Handling and Storage Precautions:AVOID ALL UNNECESSARY CONTACT WITH THIS MATERIAL; KEEP AWAY FROM IGNITABLES; DO NOT WELD ON FULL OR EMPTY CONTAINERS; KEEP CONTAINERS CLOSED ; LABEL

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANNISTER TYPE RESPIRATOR IS REQUIRED

Ventilation:GENERAL VENTILATION IS REQUIRED FOR NORMAL USE; LOCAL VENTILATION MAY BE REQUIRED MAY BE REQUIRED SOMETIMES

Protective Gloves:CHEM RESIST NITRILE, NEOPRENE, RUBBER

Eye Protection:FACE SHIELD; CHEM GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING, EYEWASH STATION, SAFETY SHOWER

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boi

ling Pt:B.P. Text:300F,149C

Vapor Pres:15

Vapor Density:>1 AIR=1

VOC Pounds/Gallon:525

Viscosity:50 SEC

Evaporation Rate & Reference: